View NSN Online: https://aerobasegroup.de/nsn/8010-01-333-9438

FARWEST PAINT MFG CO -- EXT. TRIM ENAMEL GREEN 14050 LEAD AND CHROM 8010-01-333-9438

============= Product Identification ==================

Product ID:EXT. TRIM ENAMEL GREEN 14050 LEAD AND CHROM

MSDS Date:09/19/1991

FSC:8010

NIIN:01-333-9438

MSDS Number: BQSQL === Responsible Party ===

Company Name: FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA ZIP:98168 Country:US

Info Phone Num: 206-244-8844

Eme

rgency Phone Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name: FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA ZIP:98168 Country:US

Phone:206-244-8844

CAGE:6F266

======= Composition/Information on Ingredients ========

Ingred Name: ETHYLENE GLYCOL

CAS:107-21-1

RTECS #:KW2975000 Fraction by Wt: 4%

Other REC Limits: NONE SPECIFIED

OSHA PEL:50 PPM ACGIH TLV:50 PPM EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: TEXANOL (ESTER


OSHA PEL:100 PPM ACGIH TLV:100 PPM ========== Hazards Identification =============== Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: INHALATION: PROLONGED INHALATION, IN CONFINED AREAS, MAY LEAD TO MUCOUS MEMBRANE IRRITATION-DIZZINESS-HEADACHE. SKIN: IRRITATION. EYE: IRRI TATION. INGESTION: AMOUNTS INGESTED INCIDENTAL TO CONSUMER AN D INDUSTRIAL HANDLING ARE NOT LIKELY TOCAUSE INJURY, HOWEVER, INGESTION OF LARGER AMOUNTS COULD CAUSE SERIOUS INJURY First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS DEVELOP-SEEK MEDICAL ATTN IMMEDIATELY. SKIN: WASH OFF QUICKLY WITH PLENTY OF WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. EYE: FL USH IMMEDIATELY WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR 15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY. Extinguishing Media: FOAM, DRY CHEMICAL, WATER, OR WATER FOG Fire Fighting Procedures: WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS. Unusual Fire/Explosion Hazard: WILL NOT BURN, CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEA T OR FIRE. ======== Accidental Release Measures ============ Spill Release Procedures: COMPLY WITH ALL APPLICABLE HEALTH AND ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS. ============= Handling and Storage ================= Handling and Storage Precautions: AVOID TEMPERATURES BELOW 40F. KEEP FROM FREEZING, STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED. Other Precautions: USE ONL

ALCOHOL) (SARA 313)

Other REC Limits: NONE SPECIFIED

RTECS #:UF6000000 Fraction by Wt: 2%

CAS:25265-77-4



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied

, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.