

PRATTVILLE BUILDERS INC -- LAC SPRAYING WHITE 17875 ID 793716 -- 8010-00-165-6141  
===== Product Identification =====

Product ID:LAC SPRAYING WHITE 17875 ID 793716  
MSDS Date:07/15/1992  
FSC:8010  
NIIN:00-165-6141  
MSDS Number: BQVZM  
=== Responsible Party ===  
Company Name:PRATTVILLE BUILDERS INC  
Address:474 E MAIN ST  
Box:2153  
City:PRATTVILLE  
State:AL  
ZIP:36067  
Country:US  
Info Phone Num:205-365-2396/21  
45/312-455-2662NIGHT  
Emergency Phone Num:205-365-2396/2145/312-455-2662NIGHT  
Preparer's Name:W. A. ELLISON  
CAGE:0EAH4  
=== Contractor Identification ===  
Company Name:PRATT AND LAMBERT INC  
Box:6027  
City:CLEVELAND  
State:OH  
ZIP:44101-1027  
Country:US  
Phone:216-566-2902  
CAGE:61196  
Company Name:PRATTVILLE BUILDERS INC  
Address:474 E MAIN ST  
Box:2153  
City:PRATTVILLE  
State:AL  
ZIP:36067  
Country:US  
Phone:205-365-2396/2145/312-455-2662NIGHT  
CAGE:0EAH4

===== Composition/Information on Ingredients =

=====

Ingred Name:ISOBUTYL ACETATE (SOLVENT) (LFL 2.0 / UFL 11.0)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 25%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM/700 MG/M3

ACGIH TLV:150 PPM/700 MG/M3

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SOLVENT) (VAPOR PRESSURE 33 MM HG @ 20C)  
(LFL 3.0 / UFL 13.0)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/STEL 500 PPM

ACGIH TLV:400 PPM/STEL 500 PPM

Ingre

d Name:NITROCELLULOSE (RESIN)

CAS:9004-70-0

RTECS #:QW0970000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:NONE ESTABLISHED

ACGIH TLV:NONE ESTABLISHED

Ingred Name:ISOBUTYL ALCOHOL (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)  
(LFL 1.0 / UFL 11.0)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TITANIUM DIOXIDE (PIGMENT)

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:XYLENE (SOLVENT) (SARA 313) (VAPOR PRESSURE 5 MM HG @ 20C)  
(LFL 1.0 / UFL 7.0)

CAS:1330-20-7  
RTECS #:ZE2100000

Fraction by Wt: 5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/STEL 150 PPM  
ACGIH TLV:100 PPM/STEL 150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SOLVENT) (SARA 313) (VAPOR PRESSURE 1 MM HG  
@ 20C) (LFL 1.0 / UFL 6.7) (SKIN)

C  
AS:100-41-4  
RTECS #:DA0700000

Fraction by Wt: 115F (46 C) AND SOURCES  
OF IGNITION.

Hazardous Decomposition Products:BURNING-INCLUDING WHEN HEATED BY  
WELDING/ CUTTING, PRODUCES SMOKE-CARBON MONOXIDE-CARBON  
DIOXIDE-POSS OXIDES OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/FEDERAL-STATE-LOCAL  
LAWS/ REGS. INCINERATE ONLY IN EPA FACILITY. DO NOT INCINERATE  
CLOSED CNTNRS. OBSERVE PRECAUTIONS FOR DISP  
OSAL OF FLAMMABLE  
MATERIALS. DISPOSE CONTAMINATED ABSORBANT IN HAZARDOUS WASTE  
LANDFILL. RCRA-D001.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional ad

vice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.