

CRAWFORD LABS, INC -- LACQUER TT-L-20A BLACK 37038 -- 8010-00-166-3147

=====  
Product Identification  
=====

Product ID:LACQUER TT-L-20A BLACK 37038

MSDS Date:01/31/1991

FSC:8010

NIIN:00-166-3147

MSDS Number: BQVZP

=== Responsible Party ===

Company Name:CRAWFORD LABS, INC

Address:4165 S EMERALD AVE

City:CHICAGO

State:IL

ZIP:60609

Country:US

Info Phone Num:312-376-7132

Emergency Phone Num:312-433-130

7

CAGE:5V430

=== Contractor Identification ===

Company Name:CRAWFORD LABORATORIES, INC

Address:4165 SOUTH EMERALD AVENUE

Box:City:CHICAGO

State:IL

ZIP:60609

Country:US

Phone:312-376-7132

CAGE:5V430

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (SARA III) (ITEM CONTAINS A TRACE OF BENZENE)  
(VAPOR PRESSURE 38 MM HG)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 20-50%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPANOL (SARA III) (VAPOR PRESSURE 33 MM HG)  
CAS:67-63-0  
RTECS #:NT8050000  
Fraction by Wt: 5-20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM

Ingred Name:NORMAL BUTYL ALCOHOL (SARA III) (VAPOR PRESSURE 4.3 MM HG)  
CAS:71-36-3  
RTECS #:EO1400000  
Fraction by Wt: 1-5%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:S, C 50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE (VAPO  
R PRESSURE 129 MM HG)  
CAS:141-78-6  
RTECS #:AH5425000  
Fraction by Wt: 5-20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:400 PPM  
ACGIH TLV:400 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III) (VAPOR PRESSURE 15 MM  
HG)  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 5-20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:CELLOSOLVE ACETATE (VAPOR PRESSURE 1.2 MM

HG) (ABSORBED  
THRU SKIN IN TOXIC AMOUNTS)  
CAS:111-15-9  
RTECS #:KK8225000  
Fraction by Wt: 5-20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:5 PPM  
ACGIH TLV:100 PPM

Ingred Name:CRYSTALLINE SILICA  
CAS:14464-46-1  
RTECS #:VV7325000  
Fraction by Wt: AIR  
Spec Gravity:8.95 LBS/GAL  
Evaporation Rate & Reference:1.39 X N-BUTYL ACETATE  
Appearance and Odor:BLACK LIQUID  
Percent Volatiles by Volume:81.3

===== Stability and Reactivity Data =====

Stability Indicator/Materials to  
Avoid:YES  
MAY BE INCOMPATIBLE WITH OXIDIZING AGENTS AND STRONG ALKALIES.  
Stability Condition to Avoid:AVOID HEAT, SPARKS, OPEN FLAMES, AND  
INCOMPATIBILITIES.  
Hazardous Decomposition Products:INCOMPLETE COMBUSTION FOR PRODUCTS  
LIKE THIS MAY GENERATE HIGHLY POISONOUS CARBON MONOXIDE AND OTHER  
TOXIC GASES.  
Conditions to Avoid Polymerization:AVOID HEAT, SPARKS, OPEN FLAMES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL MUST BE IN A  
CCORDANCE WITH CURRENT  
LOCAL, STATE, AND FEDERAL REGULATIONS. CONTACT AN APPROVED DISPOSAL  
FACILITY.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional ad

vice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.