

R.H. CARLSON COMPANY, INC. -- NORSIL RTV 140 -- 8040-01-009-1562

=====
Product Identification
=====

Product ID:NORSIL RTV 140

MSDS Date:02/13/1992

FSC:8040

NIIN:01-009-1562

Kit Part:Y

MSDS Number: BQWFJ

=== Responsible Party ===

Company Name:R.H. CARLSON COMPANY, INC.

Address:41 CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Info Phone Num:203-531-5500

Emergency Phone Num:800-424-93

00 CHEMTREC/203-531-5500

Preparer's Name:W.J. BUCHLER

CAGE:MO500

=== Contractor Identification ===

Company Name:R.H. CARLSON COMPANY, INC.

Address:41 CHESTNUT STREET

City:GREENWICH

State:CT

ZIP:06830

Country:US

Phone:203-531-5500

CAGE:MO500

Company Name:R.H.CARLSON COMPANY,INC.

Address:41-CHESTNUT STREET

Box:1687

City:GREENWICH

State:CT

ZIP:06830-5921

Country:US

Phone:203-531-5500

CAGE:33530

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIE

NTS
Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:WARNING! MAY CAUSE IRRITATION. AVOID CONTACT WITH SKIN, EYES, AND CLOTHING, DIRECT CONTACT WITH UNCURED PRODUCT OR VAPOR MAY CAUSE SLIGHT IRRITATION. INHALATION OF VAPORS MAY PRODUCE RESPIRATORY IRRITATION. INGESTION OF MAT'L MAY PRODUCE ABDOMINAL PAIN AND DIARRHEA.

=====
===== First Aid Measures =====

First Aid:INGEST:DONT INDUCE VOMIT, IF OCCURS, GIVE FLUID. CALL DR. DONT GIVE LIQ IF UNCONSCIOUS. SKIN: FLUSH W/WATER 15 MIN. REMOVE CONTAM CLOTH/SHOES. GET MED AID IF IRRIT. EYE: IMMED FLUSH W/WATER 15 MIN, HOLD EYELIDS APART. DONT NEUTRALZ. GET MED AID ASAP. FLUSH 15 MIN MORE IF NO MED AID. INHAL: REMOVE FROM AREA. GET MED AID IF BREATH DIFFICULT. OXYGEN IF DR'S ADVICE. NOT BREATH, GIVE ARTIF RESPIRTN

=====
===== Fire Fighting Measures =====

Fire Fighting Procedures:EVACUATE NON-ESSENTIAL PERSONNEL. FIREFIGHTERS SHOULD WEAR FULL FACE SCBA & IMPERVIOUS PROTECTIVE CLOTHING. USE STANDARD FIREFIGHTING TECHNIQUES.

=====
===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW GOOD INDUSTRIAL HYGIENE. WEAR PROTECTIVE CLOTHING, SPLASH GOGGLES, SOAK UP W/ABSORBENT (SAWDUST,CLAY,OIL ABSORBR). SWEEP UP ABSORBENT. PLACE IN DRUM. WASH UP WITH DETERGNT & WATER. FLUSH WITH WATER. LARGE SPILL: DIKE & PUMP TO DRUM.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH SKIN AND EYES, USE ONLY IN A WELL VENTILATED AREA. CONTACT LENS WEARERS TAKE APPROPRIATE PRECAUTION.
Other Precautions:STORE IN COOL PLACE AND KEEP AWAY FROM HEAT, SPARKS, AND FLAME. PRODUCT EVOLVES SLIGHT AMOUNTS OF ACETONE WHEN EXPOSED TO WATER OR HUMID AIR. OBSERVE LIMITS

FOR ACETONE FORMED ON
EXPOSURE TO WATER OR HUMID AIR OSHA PEL & ACGIH TLV 750 PPM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF CONDITIONS GENERATE VAPOR, HANDLE MAT'L IN
OPEN OR WELL-VENTED AREA. WHERE ADEQUATE VENT IS NOT AVAILABLE, USE
NIOSH APPROVED ORGANIC VAPOR RESPIRATORS. WHERE HIGHER EXPOSURES,
RECOMMEND POSITIVE P RESSURE AIR SUPPLY RESPIRATOR.

Ventilation:LOCAL EXHAUST IS REQUIRED & GENERAL MECHANICAL VENTILATION

IS SUGGESTED IN A CLOSED AREA.

Protective Gloves:PLASTIC FILM OR RUBBER GLOVES SUGGESTED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:PROTECTIVE APRON OR COVERALLS

Work Hygienic Practices:KEEP AWAY FORM HEAT, SPARKS, AND FLAME. AVOID
PROLONGED VAPOR BREATHING AND CONTACT WITH SKIN AND EYES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Vapor Pres:NEGLIGIBLE

Vapor Density:>1

Spec Gravity:1.05

Viscosity:>50,000 CPS

Evaporatio

n Rate & Reference: