View NSN Online: https://aerobasegroup.de/nsn/6810-01-063-4534

FISHER SCIENTIFIC -- HEXANES -- 6810-01-063-4534

Product ID:HEXANES MSDS Date:02/12/1986

FSC:6810

NIIN:01-063-4534

MSDS Number: BQWGC === Responsible Party ===

Company Name: FISHER SCIENTIFIC

Address: 1 REAGENT LANE

City:FAIR LAWN

State:NJ ZIP:07410 Country:US

Info Phone Num:201-796-7100

Emergency Phone Num:201-796-7100;800-424-9300(CHEMTREC)

CAGE:1B464 === Contrac

tor Identification ===

Company Name: FISHER SCIENTIFIC CO. CHEMICAL MFG DIV

Address: 1 REAGENT LANE

Box:City:FAIRLAWN

State:NJ

ZIP:07410-2802 Country:US

Phone:201-796-7100

CAGE:1B464

======= Composition/Information on Ingredients ========

Ingred Name: HEXANE

CAS:110-54-3

RTECS #:MN9275000 Fraction by Wt: 100% OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:SUPP DATA:COOL CNTNRS W/FLOODING QTYS OF WATER, APPLY FROM AS FAR A DISTANCE AS POSSI

BLE. AVOID BRTHG TOX VAPS, (ING 3) RTECS #:9999999ZZ

Ingred Name:ING 2: KEEP UPWIND. EVAC TO A RADIUS OF 1500 FEET FOR UNCONTROLLABLE FIRES. EVAC DOWNWIND FOR LEAKS (BUREAU OF (ING 4) RTECS #:9999999ZZ

Ingred Name:ING 3:EXPLO, EMER HNDLG OF HAZ MATLS IN SURF TRANSPORTATION, 1981). WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP.

RTECS #:9999999ZZ

Ingred Name: CNDTNS TO AVOID (STAB): CNTNR MAY EXPLO IN HEAT/FIRE. VAP EXPLOSION HAZ INDOORS, OUTDOORS OR IN SEWERS. RUNOFF (ING 6) RTEC

S#:999999ZZ

Ingred Name:ING 5: TO SEWER MAY CREATE FIRE OR EXPLOSION HAZARD. RTECS #:9999992Z

Ingred Name:EFTS OF OVEREXP: & MUSCLE WEAKNESS. ALCOHOL MAY ENHANCE THE TOXIC EFFECTS.

RTECS #:9999992Z

Ingred Name:FIRST AID PROC:(APPROX 15-20 MIN). GET MED ATTN IMMED. EYES: WASH IMMED W/LRG AMTS OF WATER FOR @ LST 15 MIN, (ING 9) RTECS #:9999992Z

Ingred Name:ING 8:OCCASNLY LIFTING UPPER & LOWER LIDS UNTIL NO EVIDENCE OF CHEM REMAINS. GET MED ATTN. INGEST:DO NOT INDUCE(ING 10) RT

ECS #:9999992Z

Ingred Name:ING 9: VOMITING. GET IMMEDIATE MEDICAL ATTENTION. RTECS #:9999992Z

Ingred Name:SPILL PROC:PRACTICAL & EFFTIVE IN ORDER TO REDUCE THE CONTAM & THE AMT OF MATL TO DISP.NO SMOKING, FLAMES/FLARES(ING 12) RTECS #:9999999ZZ

Ingred Name:ING 11: IN THE HAZARD AREA. KEEP UNNECESSARY PEOPLE AWAY; ISOLATE HAZARD AREA AND DENY ENTRY. RTECS #:9999999ZZ

Ingred Name:RESP PROT:ESCAPE: GAS-MASK W/ORGANIC VAP CANISTER (CHIN-STYLE OR FRONT OR BACK-MOUNTED CANISTER). SEL

F-CONTAINED(ING 14) RTECS #:9999999ZZ Other REC Limits:N/L

Ingred Name:ING 13: BREATHING APPARATUS. FIREFIGHTING: SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED (ING 15) RTECS #:9999992Z

Ingred Name:ING 14: IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. RTECS #:9999999ZZ

Ingred Name:OTHER PROT EQUIP: APPROP PROT (IMPERVIOUS) CLOTHING AND EQUIPMENT TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. RTECS #:9999992Z

==	 ===	Hazards	Identificatio
n	 	_	

LD50 LC50 Mixture:LD50:(ORAL,RAT) 28710 MG/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:IRRIT/NEUROTOXIN. 5000 PPM IMMED DANGEROUS TO LIFE OR HLTH. ACUTE:LIGHTHEADEDNESS, NAUS, VOMIT, NARCOSIS, HDCH, IRRIT OF THE UPPER RESP TRACT. CHRONIC:PRLNGD EXPOS MAY CAUSE PERIPHERAL NEUROPATH Y & CARDIAC SENSIT.

SKIN:IRRIT/NARCOTIC. ACUTE:PRLNGD CNTCT MAY PROD

UCE MOD IRRIT. MAY

BE ABSORBED, (EFTS OF OVEREXP)

Explanation of Carcinogenicity: NOT RELEVANT

Effects of Overexposure: HLTH HAZ: PRODUCING NARCOSIS.

CHRONIC:RPTD/PRLNGD CNTCT DEFATS SKIN, RSLTG IN DERM. EYE:IRRIT. ACUTE:DIRECT CNTCT W/LIQ MAY RSLT IN IRRIT, REDNESS, TEARING, & PAIN. VAPS MAY CAUSE IRRIT. CHRONIC: RPTD/ PRLNGD CNTCT MAY CAUSE CONJUNCTIVITIS. INGEST:IRRIT OR NARCOTIC. ACUTE: NUMBNESS, IRRIT OF GI TRACT, NAUS, VOMIT,(ING 7)

Medical Cond Aggravated by Exposure:

NONE SPECIFIED BY MANUFACTURER.

First Aid:INHAL:REMOVE FROM EXPOS AREA TO FRESH AIR IMMED. IF BRTHG HAS STOPPED, GIVE ARTF RESP. MAINTAIN AIRWAY & BLOOD PRESS & ADMIN O*2 IF AVAIL. KEEP AFFECTED PERSON WARM & @ REST. ADMIN OF O*2 SHLD BE PERF ORMED BY QUALIFIED PERSONNEL. GET MED ATTN IMMED. SKIN:REMOVE CONTAM CLTHG & SHOES IMMED. WASH AFFECTED AREA W/SOAP/MILD DETERGENT & LRG AMTS OF WATER UNTIL NO EVIDIE

NCE OF CHEM REMAINS (ING 8) Flash Point:-7F,-22C Lower Limits:1.1% Upper Limits:7.5% Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR FOAM. FOR LARGE FIRES, USE WATER SPRAY, FOG OR ALCOHOL FOAM. Fire Fighting Procedures: MOVE CNTNR FROM FIRE AREA IF POSS. COOL FIRE-EXPOSED CNTNRS W/WATER FROM SIDE UNTIL WELL AFTER FIRE IS OUT. FOR MASSIVE FIRE IN STORAGE AREA, USE (SUPP DATA) Unusual Fire/Explo sion Hazard: DANGER FIRE/SEVERE EXPLOSION HAZ WHEN EXPOSED TO HEAT/FLAME. VAPORS ARE HVR/AIR & MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNIT & FLASH BACK. ======== Accidental Release Measures =========== Spill Release Procedures: SHUT OFF IGNIT SOURCES. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. USE WATER SPRAY TO REMOVE VAPS. FOR SML SPILLS. TAKE UP WITH SAND/OTHER ABSORBENT MATL & PLACE INTO CNTNRS FOR LATER DISP. FOR LRG SPIL LS, DIKE AS CLOSE TO THE SPILL AS IS (ING 11) Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. ============ Handling and Storage =========================== Handling and Storage Precautions: NONE SPECIFIED BY MANUFACTURER. Other Precautions: NONE SPECIFIED BY MANUFACTURER. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: NIOSH/MSHA APPRVD: EXPOSURE LIMT TO 1000 PPM:SUPPLIED-AIR RESP SELF-CONTAINED BRTHG APPARATUS. 5000 PPM:SELF-CONTAINED BRTHG APPARATU S W/A FULL FACEPIECE OPERATED IN

PRESS-DEMAND OR OTHER POSITIVE PRE SS MODE, OR USE EQUIVALENT RESP.(ING 13)

Ventilation: PROVIDE LOC EXHST VENT/GEN DILUTION VENT TO MEET PERMISSIBLE EXPOSURE LIMITS. VENT EQUIPMENT MUST BE EXPLOSION PROOF.

Protective Gloves: IMPERVIOUS GLOVES.

Eve Protection: CHEM WORK GOGG/FULL LENGTH FSHLD.

Other Protective Equipment: EMPLOYER SHALL PROVIDE EYE-WASH FOUNTAIN WITHIN THE IMMEDIATE WORK AREA FOR EMERGENCY USE. EMPLOYEE SHALL WEAR (ING 16)

Wo

Supplemental Safety and Health FIRE FIGHT PROC:UNMANNED HOSE HOLDER/MONITOR NOZZ, ELSE WITHDRAW FROM AREA & LET FIRE BURN. WITHDRAW IMMED IN CASE OF RISING SOUND FROM VENTING SAFETY DEVICE/ANY DISCOLORATION OF STORAGE TANK DUE TO F IRE. EXTING ONLY IF FLOW CAN BE STOPPED; USE WATER IN FLOODING AMTS AS FOG SOLID STREAMS MAY NOT BE EFFECTIVE. (ING 2) ======== Physical/Chemical Properties =========== Boiling Pt:B.P. Text:136F,58C Melt/Freeze Pt:M.P/F.P Text:-139F,-95C Vapor Pres:124 @ 20C Vapor Density:3.0 Spec Gravity:0.7 Solubility in Water: INSOLUBLE Appearance and Odor: COLORLESS LIQUID, FAINT ODOR, VERY VOLATILE ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS: VIOLENT REACTION. DINITROGEN TETRAOXIDE: POSSIBLE EXPLOSION. Stability Condition to Avoid: MAY BE IGNITED BY HEAT, SPARKS, OR FLAMES. VAPS ARE HVR/AIR & MAY TRAVEL TO A SOURCE OF IGNIT & FLASH BACK. (ING 5) Hazardous Decomposition Products: COMBUSTION MAY RELEASE ACRID SMOKE AND IRRITATING FUMES. ======= Disposal Considerations ============ Waste Disposal Methods: DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United State

rk Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

s of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.