

ASPEN PAINTS -- STAIN, OIL, SEMI-TRANSPARENT, WOOD, EXT. DK -- 8010-00-165-8627

=====  
Product Identification  
=====

Product ID:STAIN, OIL, SEMI-TRANSPARENT, WOOD, EXT. DK

MSDS Date:03/01/1993

FSC:8010

NIIN:00-165-8627

MSDS Number: BQYBK

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE ST.

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergency Ph

one Num:800-424-9300(CHEMTREC)

Preparer's Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

=====  
Composition/Information on Ingredients  
=====

Ingred Name:S K SOLVENT, MINERAL SPIRITS MIXTURE, SOLVENT 390

CAS:8052-41-3

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:BENZENE

CAS:71-43-2  
RTECS #:CY1400000  
Other REC Limits:< 10 PPM  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: VAPOR CAUSE NASAL &  
RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA,  
HEADACHE, UNCONSCIOUSNESS, ASPHIXIATION. SKIN: DEFATTING/DRYING  
SKIN RESULT IN DERMAT  
ITIS. EYES: SEVERE IR RITATION, REDNESS,  
TEARING & BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION,  
NAUSEA, VOMITING & DIARRHEA.  
Effects of Overexposure:ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE  
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. REPORTS HAVE ASSOCIATED  
REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENT WITH  
PERMANENT BRAIN & NERVOUS SY STEM DAMAGE. INTENTIONAL MISUSE BY  
DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL  
OR FATAL.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM FROM FUTHER EXPOSURE & RESTORE  
BREATHING, IF REQUIRED. EYE CONTACT: FLUSH EYES WITH WATER FOR AT  
LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN CONTACT: WASH  
CONTAMINATED SKIN WITH MILD SOAP & WATER. INGESTION:DO NOT INDUCE  
VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Poin  
t:112F,44C  
Lower Limits:0.8  
Upper Limits:5.0  
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER FOG.  
Fire Fighting Procedures:DON'T ENTER CONFINED FIRE SPACE W/O ADEQUATE  
PROTECTIVE CLOTHING & APPROVED SCBA. EXCLUDE AIR. DON'T USE WATER  
EXPCEPT AS FOG. USE WATER TO COOL HEATED CONTAIN.  
Unusual Fire/Explosion Hazard:CAUTION-FLAMMABLE. AVOID EXCESSIVE HEAT,  
OPEN FLAMES, & ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE  
MIXTURE WITH AIR BETWEEN UPPER & LOWER FLAMMABLE LIMITS.

=====

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB SPILL WITH ABSORBENT MATERIAL & PLACE IN CLOSED CONTAINER. LARGE SPILL, DIKE AREA TO PREVENT FROM ENTERING WATERWAYS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP. NOTIFY APPROPRIATE ENVIRONMENTAL AGENCY(IES) IF SPILL EXCEEDS 220 LBS.

===== Handling and Storage =====

Handling and Storage Precautions: "FLAMMABLE LIQUID" STORE COOL, DRY, WELL- VENTIL. AREA, AWAY FROM ALL HEAT SOURCES. GROUND CONTAINERS WHEN POURING & LIMIT FREE FALL TO MIN. STATIC.

Other Precautions: DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPOR OR SPRAY MISTS WHEN TLV, PEL IS EXCEEDED.

Ventilation: GENERAL VENTILATION. LOCAL VENTILATION REQUIRED CERTAIN CASE

S TO KEEP EXPOSURE LEVEL BELOW THE LIMITS.

Protective Gloves: CHEMICAL-RESIST. NITRILE, NEOPRENE, RUBBER.

Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. USE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boil

ing Pt: B.P. Text: 301 TO 402F

Vapor Pres: >7.0 @ 38C

Vapor Density: 4.8

Spec Gravity: 0.87

Viscosity: 10"-25" #4FC

Evaporation Rate & Reference: < N-BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: THIN LIQUID, MILD ODOR.

Percent Volatiles by Volume: 65-69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Stability Condition to Avoid: AVOID EXCESSIVE HEAT

, OPEN FLAME AND ALL  
IGNITION SOURCES.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE  
PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods: IF NOT POSSIBLE TO RECLAIM, THEN MATERIAL &  
CONTAINERS TREAT AS HAZARDOUS WASTE BASED ON THE CHARACT. OF  
IGNITABILITY AS DEFINED UNDER FEDERAL RCRA REGULAT. COMPLY WITH  
LOCAL, STATE AND FEDERAL REGULATIONS FOR DISPOSAL.

Disclaimer (provided with this  
information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.