

SENTRY PAINT AND CHEMICAL CO -- OLIVE DRAB S/G ENAMEL X-5039 -- 8010-00-297-2105

=====  
Product Identification  
=====

Product ID:OLIVE DRAB S/G ENAMEL X-5039

MSDS Date:10/21/1992

FSC:8010

NIIN:00-297-2105

MSDS Number: BQYDB

=== Responsible Party ===

Company Name:SENTRY PAINT AND CHEMICAL CO

Address:MILL AND LAWRENCE ST

City:DARBY

State:PA

ZIP:19023

Country:US

Emergency Phone Num:800-424-9300 CHEMTRE

C

CAGE:34346

=== Contractor Identification ===

Company Name:SENTRY PAINT AND CHEMICAL CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:34346

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUENE (FLAMMABLE) (SARA III) (VAPOR PRESSURE 24.00 MM HG  
@ 68F) (LEL 1.00)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 3.1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt

Qty:1000 LBS

Ingred Name:BUTYL ACETATE (FLAMMABLE) (VAPOR PRESSURE 8.4 MM HG @ 20C)  
(LEL 1.69)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 10.3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:RULE 66 VM&P NAPHTHA (FLAMMABLE) (VAPOR PRESSURE 40.00 MM  
HG @ 20C) (LEL 1.00)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 17.9%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:CARBON  
BLACK (IRRITANT)

CAS:1333-86-4

RTECS #:FF5800000

Fraction by Wt: 3.0%

Other REC Limits:NONE SPECIFIED

Ingred Name:LEAD CHROMATE (NEUROTOXIN) (SARA 313)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 12.3%

Other REC Limits:NONE SPECIFIED

OSHA PEL:.05 MG/M3

ACGIH TLV:.05 MG/M3

Ingred Name:LEAD ALKANOATES SOL'N (HIGHLY TOXIC) (SARA III) (VAPOR  
PRESSURE 1.00 MM HG @ 20C) (LEL 1.09)

CAS:7439-92-1

RTECS #:OF7525000

Fraction by Wt: 5.7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:.05 MG/M3

ACGIH TL

V:15 MG/M3  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:N-BUTYL ALCOHOL (FLAMMABLE) (VAPOR PRESSURE 5.9 MM HG @ 20C) (LEL 1.39)

CAS:71-36-3  
RTECS #:EO1400000  
Fraction by Wt: 5.2%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TLV:S, C 50 PPM; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:DOWANOL PM (FLAMMABLE) (VAPOR PRESSURE 12.50 MM HG @ 20C) (LEL 1.50)

CAS:107-98-2  
RTECS #:UB7700000  
Fraction by Wt: 1.9%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:100 PPM  
ACGIH TL  
V:100 PPM

Ingred Name:ZINC COMPOUNDS (SARA III)

CAS:7440-66-6  
RTECS #:ZG8600000  
Fraction by Wt: 3.2%  
Other REC Limits:NONE SPECIFIED  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:YES IARC:YES  
Health Hazards Acute and Chronic:ACUTE;CONSTIPTN,SLEEP DISTURB,FATIGUE,  
HEADACHE,ANOREXIA.INHAL:COLIC,ANEMIA,VOMIT,NEURITIS.CONVULSN,STUPOR  
,COMA, ENCEPHALOPATHY.EYES:IRRIT,RED,TEAR,BLURR  
VISION

.SKIN: DRY, IRRIT, DERMATITIS. INHAL: NASAL, RESP  
IRRIT, DIZZY, WEAK, NAUSEA, HEADACHE. INGEST: NAUSEA, DIARRHEA, ASPIRATN  
HZD. CNS DEPRESS, LIVER, KIDNEY, LUNG, SPLEEN, BLOOD IN  
Explanation of Carcinogenicity: LEAD IS ON ACGIH, IARC, & NTP LIST OF  
INDUSTRIAL SUBSTANCES SUSPECTED OF CARCINOGENIC POTENTIAL FOR MAN.  
Effects of Overexposure: CHRONIC; LEAD HAS CUMULATIVE EFFECT. FATIGUE,  
SLEEP DISTURB, HEADACHE, ACHING BONES/MUSCLES, CONSTIPATN, ABDOM  
PAIN, ANOREXIA. INGEST: INTENSE PERIODIC  
CRAMPS, CON  
STIPTN, NAUSEA, VOMIT. BLOOD, NERVOUS/ DIGESTIVE S YSTEM  
EFFECTS. ANEMIA, APATHY, DEPRESSION, PARALYSIS, ENCEPHALOPATHY. PERM  
BRAIN & NERV SYS DAMAGE.

=====  
===== First Aid Measures =====

First Aid: INHALE: REMOVE TO FRESH AIR IMMED. IF BREATHING STOPPED GIVE  
ARTIF RESPIRATION. KEEP WARM, QUIET. GET MED AID IMMED. EYE: FLUSH  
W/WATER 15 MIN, LIFTING EYELIDS. GET MED AID. SKIN: WASH W/SOAP &  
WATER. REMOVE CONTAMINATED CLOTHING. WASH CONTAM CLOTHING BEFO  
RE  
REUSE. INGEST: DONT INDUCE VOMIT, KEEP PERSON WARM, QUIET & GET MED  
AID. ASPIRATION INTO LUNGS DUE TO VOMITING CAN CAUSE CHEM  
PNEUMONITIS.

=====  
===== Fire Fighting Measures =====

Flash Point Method: CC  
Flash Point: 40.0F, 4.4C  
Lower Limits: 1.00  
Extinguishing Media: CARBON DIOXIDE OR DRY CHEMICAL FOR SMALL FIRES.  
FOAM FOR LARGE FIRES.  
Fire Fighting Procedures: COOL CLOSED CONTAINERS WITH WATER SPRAY.  
CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCTS  
OF COMBUSTION. USE  
APPROPRIATE RESPIRATOR.  
Unusual Fire/Explosion Hazard: CLOSED CNTNR MAY BLD EXPLOSIVE PRESSR  
FROM HEAT. VAPOR HEAVIER THAN AIR, MAY TRAVEL ALONG GROUND IGNITED  
DISTANT FROM HANDLING PT. NEVER WELD/CUT ON/NEAR DRUM.

=====  
===== Accidental Release Measures =====

Spill Release Procedures: KEEP SPECTATORS AWAY. ELIMINATE IGNITION  
SOURCES. DIKE, CONTAIN W/INERT MAT'L. TRANSR LIQ TO COVERED METAL  
CONTAINER/REMOVE W/INERT ABOSRBNT. USE NON SP

ARK TOOL. PLACE ABSORB

DIKING IN CVRD METAL CNTN R. PREVENT CONTAM OF SEWERS, STREAMS,  
GROUNDWATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS WHERE  
CONCENTRATIONS MAY BE ABOVE TLV. BELOW TLV, USE A NIOSH APPROVED  
VAPOR RESPIRATOR.

Ventilation:LOCAL EXHAUST MUST BE SUFFICIENT TO KEEP AIRBORNE VAPOR  
CONCENTRATION BELOW THE TLV.

Protective Gloves:CHEMICAL RESISTANT GLOVES

Eye Protection:SAF

ETY GLASSES WITH SIDE SHIELDS.

Other Protective Equipment:EYE BATH AND SAFETY SHOWER. TO PREVENT  
REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING &  
BOOTS.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:244 TO 380F

Vapor Density:> AIR

Spec Gravity:10.6 LBS/GAL

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:APPEARANCE IS COLOR 24084 OD PAINT

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

REACTS VIOLENTLY WITH HYDROGEN PEROXIDE. AVOID CONTACT WITH STRONG  
OXIDIZING AGENTS.

Stability Condition to Avoid:EXCESS HEAT, SPARKS, OPEN FLAME. DO NOT  
STORE OR HANDLE IN ALUMINUM EQUIPMENT AT TEMPERATURES OVER 120F.

Hazardous Decomposition Products:FUMES MAY CONTAIN CARBON MONOXIDE AND  
CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE

OF IN ACCORDANCE WITH FEDERAL, STATE &  
LOCAL LAWS. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should  
seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.