

HOME OIL COMPANY, INC -- THINNER, PAINT, ODORLESS MINERAL SPIRITS -- 8010-00-837-7969

=====
Product Identification
=====

Product ID:THINNER, PAINT, ODORLESS MINERAL SPIRITS

MSDS Date:01/27/1992

FSC:8010

NIIN:00-837-7969

MSDS Number: BQYHR

=== Responsible Party ===

Company Name:HOME OIL COMPANY, INC

Address:3511 NORTH OHIO

City:WICHITA

State:KS

ZIP:67219

Country:US

Info Phone Num:316-838-4663

Emer

gency Phone Num:800-424-9300

Preparer's Name:BERNARD D. HOFFMAN, JR.

CAGE:0A9L8

=== Contractor Identification ===

Company Name:HOC INDUSTRIES, INC

Address:3511 N. OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67219

Country:US

Phone:316-838-4663

CAGE:0A9L8

=====
Composition/Information on Ingredients
=====

Ingred Name:MIXTURE OF C10 - C13 ISOPARAFFINS

CAS:68551-17-7

Fraction by Wt: 100%

Other REC Limits:400 PPM MANUFACTURER

=====
Hazards Identification
=====

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:MAY BE MILDLY IRRITATING TO EYE AND SKIN. MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, UNCONSCIOUSNESS IF INHALED. MAY IRRITATE STOMACH AND INTESTINES. MAY RESULT IN CHEMICAL PNEUMONITIS IF ASPIRATED.

===== First Aid Measures =====

First Aid:FLUSH EYES WITH WATER FOR 15 MINUTES; WASH SKIN WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE, SEEK MEDICAL ATTENTION. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:135F,57C
Lower Limits:N.I.F.
Upper Limits:N.I.F.
Extinguishing Media:DRY CHEMICAL, FOAM, CARBON DIOXIDE.
Fire Fighting Procedures:WATER FOG OR SPRAY MAY BE USED TO COOL EQUIPMENT AND CONTAINERS. DO NOT SPRAY WATER DIRECTLY ON FIRE.
Unusual Fire/Explosion Hazard:CARBON OXIDES MAY FORM WHEN BURNED.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE AREA OF ALL UNNECESSARY PERSONNEL. SHUT OFF SOURCE AND CONTAIN SPILL. PROTECT FROM SOURCES OF IGNITION. ABSORB IN DRY, INERT MATERIAL (SAND, CLAY, SAWDUST, ETC). TRANSFER TO DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID BREATHING VAPORS. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. USE ADEQUATE VENTILATION.
Other Precautions:STORE IN A COOL, DRY, WELL-VENTILATED AREA. PROTECT FROM SOURCES OF IGNITION. KEEP CONTAINERS CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT GENERALLY REQUIRED.
Ventilation:USE ADEQUATE VENTILATION.
Protective Gloves:RUBBER GLOVES.
Eye Protection:CHEMICAL GOGGLES.
Other Protective Equipment:PROTECTIVE GARMENTS TO PREVENT EXCESSIVE SKIN CONTACT.
Supplemental Safety and Health

===== Physic

al/Chemical Properties =====

Boiling Pt:B.P. Text:357 TO 408F
Vapor Pres:1.55@100F
Vapor Density:1
Spec Gravity:76 @60F
Viscosity:1.55@100F CST
Evaporation Rate & Reference:(BU AC=1) 0.1
Solubility in Water:NEGLIGIBLE
Appearance and Odor:COLORLESS LIQUID. ODOR: MILD.
Percent Volatiles by Volume:100%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXYGEN AND STRONG OXIDIZING MATERIALS.
Hazardous Decomposition Products:CARBON OXIDES MAY FORM WHEN BURNED.

===== Disposal Considerations =====

Waste Disposal Methods:INSURE CONFORMITY WITH ALL APPLICABLE DISPOSAL REGULATIONS INCINERATE OR PLACE IN RCRA PERMITTED WASTE FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.