

ASPEN PAINTS -- STAIN, OIL, SEMI TRANSPARENT, WOOD EXT. DK -- 8010-00-926-9130

=====  
Product Identification  
=====

Product ID:STAIN, OIL, SEMI TRANSPARENT, WOOD EXT. DK

MSDS Date:03/01/1993

FSC:8010

NIIN:00-926-9130

MSDS Number: BQYJG

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE ST.

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergency Phone

Num:800-424-9300(CHEMTREC)

Preparer's Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

=====  
Composition/Information on Ingredients  
=====

Ingred Name:S K SOLVENT, MINERAL SPIRITS MIXTURE, SOLVENT 390

CAS:8052-41-3

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:BENZENE

CA

S:71-43-2  
RTECS #:CY1400000  
Other REC Limits:< 10 PPM  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: VAPOR CAUSE NASAL &  
RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA,  
HEADACHE, UNCONSCIOUSNESS, ASPHIXIATION. SKIN: DEFATTING/DRYING SKIN  
RESULT IN DERMATITIS  
. EYES: SEVERE IRRITATION, REDNESS, TEARING,  
BLURRED VISION. INGESTION: GASTROINTESTINAL IRRITATION, NAUSEA,  
VOMITING, & DIARRHEA.  
Effects of Overexposure:ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE  
CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. REPORTS HAVE ASSOCIATED  
REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENT WITH  
PERMANENT BRAIN & NERVOUS SY STEM DAMAGE. INTENTIONAL MISUSE BY  
DELIBERATELY CONCENTRATING & INHALING THE CONTENTS MAY BE HARMFUL  
OR FATAL.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM FROM FUTHER EXPOSURE & RESTORE  
BREATHING, IF REQUIRED. EYE CONTACT: FLUSH EYES WITH WATER FOR AT  
LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN CONTACT: WASH  
CONTAMINATED SKIN WITH MILD SOAP & WATER. INGESTION: DO NOT  
INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point  
:112F,44C  
Lower Limits:0.8  
Upper Limits:5.0  
Extinguishing Media:DRY CHEMICAL, CO2, FOAM, WATER FOG.  
Fire Fighting Procedures:DON'T ENTER CONFINED FIRE SPACE W/O ADEQUATE  
PROTECTIVE CLOTHING & APPROVED SCBA. EXCLUDE AIR. DO NOT USE WATER  
EXCEPT AS FOG.USE WATER TO COOL HEATED CONTAINER  
Unusual Fire/Explosion Hazard:CAUTION-FLAMMABLE. AVOID EXCESSIVE HEAT,  
OPEN FLAMES & ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE  
MIXTURE WITH AIR BETWEEN UPPER & LOWER FLAMMABLE LIMITS.

=====

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB SPILL WITH ABSORBENT MATERIAL & PLACE MATERIAL INTO A CLOSED CONTAINER. LARGE SPILL, DIKE AREA TO PREVENT THIS MATERIAL FROM ENTERING WATERWAYS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP. NOTIFY APPROP. ENVIRONMENTAL AGENCY(IES) IF OVER 220LBS

===== Handling and Storage =====

Handling and Storage Precautions: "FLAMMABLE LIQUID" STORE IN COOL, DRY, WELL-VENTILATED AREA, & AWAY FROM ALL HEAT SOURCES. GROUND CONTAINERS WHEN POURING & LIMIT STATIC BUILDUP.

Other Precautions: EMPTY CONTAINERS MAY BE HAZARDOUS FROM RESIDUES OF PRODUCT & VAPOR. DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPOR OR SPRAY MISTS WHEN TLV, PEL IS EXCEEDED.

D.

Ventilation: GENERAL VENTILATION. LOCAL VENTIL. REQUIRED CERTAIN CASES TO KEEP EXPOSURE LEVEL BELOW THE LIMITS.

Protective Gloves: CHEMICAL-RESIST. NITRILE, NEOPRENE, RUBBER.

Eye Protection: WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment: WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices: LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. USE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: B.P. Text: 301 TO 402F

Vapor Pres: >70 @ 38 C

Vapor Density: 4.8

Spec Gravity: 0.94

Viscosity: 10"-25" #4FC

Evaporation Rate & Reference: < N-BUTYL ACETATE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: THIN LIQUID, MILD ODOR

Percent Volatiles by Volume: 27-29

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS

OR MINERAL ACIDS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT, OPEN FLAME & ALL  
IGNITION SOURCES.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE ARE  
PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:IF NOT POSSIBLE TO RECLAIM, THEN MATERIAL &  
CONTAINERS SHOULD BE TREATED AS HAZARDOUS WASTE BASED ON THE  
CHARACTERISTIC OF IGNITABILITY AS DEFINED UNDER FEDERAL RCRA  
REGULAT. COMPLY WITH  
LOCAL, STATE AND FEDERAL REGULATIONS FOR  
DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.