View NSN Online: https://aerobasegroup.de/nsn/8040-01-247-9689 NATIONAL DRAEGER INC -- HARDENER T9539 -- 8040-01-247-9689 Product ID:HARDENER T9539 MSDS Date:09/01/1992 FSC:8040

NIIN:01-247-9689

MSDS Number: BQYMS === Responsible Party ===

Company Name: NATIONAL DRAEGER INC

Address:101 TECHNOLOGY DRIVE

City:PITTSBURGH

State:PA ZIP:15275 Country:US

Info Phone Num:412-787-8389

Emergency Phone Num:800-424-9300 CHEMTREC

CAGE:5383

3

=== Contractor Identification ===

Company Name: NATIONAL DRAEGER INC

Address: 101 TECHNOLOGY DRIVE

Box:City:PITTSBURGH

State:PA ZIP:15372 Country:US

Phone:412-787-8383 OR 412-787-8389

CAGE:53833

======= Composition/Information on Ingredients ========

Ingred Name:TRIS (4-ISOCYANATOPHENYL) THIOPHOSPHATE (TT)

CAS:4151-51-3 Fraction by Wt: 20%

Other REC Limits: NONE SPECIFIED

Ingred Name: METHYLENE CHLORIDE (MC) (SARA III)

CAS:75-09-2

RTECS #:PA8050000 Fraction by Wt: 74-79.5%

Other R

EC Limits:NONE SPECIFIED OSHA PEL:500 PPM ACGIH TLV:50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: MONOCHLOROBENZENE (MCB) (SARA III)

CAS:108-90-7

RTECS #:CZ0175000 Fraction by Wt: 0.5-3.0%

Other REC Limits: NONE SPECIFIED

OSHA PEL:75 PPM **ACGIH TLV:75 PPM** EPA Rpt Qty:100 LBS DOT Rpt Qtv:100 LBS

=========== Hazards Identification ==========================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Hea

Ith Hazards Acute and Chronic: NONE UNDER NORMAL CONDITIONS. INHAL: IRRITANT, NARCOTIC & NEUROTOXIN. SKIN: IRRITANT. IRRIT. SCALING, CRACKING, REDDENING, SWELLING, RASH, BLISTERING. CURED MAT'L DIFFICULT TO REMOVE. EYE: IRRITANT, TEAR ING, REDDENING, SWELLING. INGEST: IRRIT, INTERNAL CORROSIVE ACTION (SORE THROAT, ABDOM PAIN, NAUSEA, VOMITING, DIARRHEA.

Explanation of Carcinogenicity: MC CLASSIFIED AS ANTICIPATED HUMAN CARCINOGEN BY NTP. MC IS LISTED IN VOL 41 AS CATEGORY 2B (IA RC).

First Aid:INHAL:REMOVE TO FRESH AIR IMMED. IF BREATH STOPPED, GIVE ARTIF RESP. GET MED AID IMMED. SKIN:REMOVE CONTAM CLOTH IMMED. WASH AREA W/SOAP OR MILD DETERGNT & LRG AMT WATER. GET MED AID IMMED. EYE:WASH E YES IMMED W/LRG AMT WATER OR NORMAL SALINE, LIFTING EYELIDS. GET MED AID IMMED. INGEST:PREVENT ASPIRATION. MAINTAIN AIRWAY, BP. RESPRTN, GET MED AID IMMED, QUALIFIED MED PERSONNEL MUST GIVE

TREATMENT.
======================================
Flash Point:NONE Extinguishing Media:DRY CHEMICAL; CARBON DIOXIDE, FOAM, WATER Fire Fighting Procedures:COOL FIRE EXPOSED CONTAINERS WITH WATER WATER SPRAY. Unusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures ==========
Spill Release Procedures:TAKE UP WITH INERT ABSORBENT AND PLACE IN CONTAINER FOR LATER DISPOSAL.
============ Handling and Storage ====
Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED AND AWAY FROM HEAT AND IGNITION SOURCES, AND DO NOT SMOKE. Other Precautions:WATER POLLUTING LIQUID. THE MATERIAL MUST NOT FLOW INTO WASTE WATER OR SURFACE WATERS.
====== Exposure Controls/Personal Protection ========
Respiratory Protection: SUPPLIED AIR RESPIRATOR OR SELF-CONTAINED BREATHING APPARATUS. Ventilation: PROVIDE LOCAL EXHAUST. SHOULD BE USED TO MAINTAIN LEVELS BELOW EXPOSU RE LIMITS OR GUIDELINES. Protective Gloves: CHEMICAL RESISTANT GLOVES Eye Protection: GOGGLES RECOMM WHEN CONTACT POSSIBLE Other Protective Equipment: CHEM RESISTANT CLOTHING RECOMMENDED WHEN PHYSICAL CONTACT POSSIBLE. SAFETY SHOWER & EYEWASH STATION SHOULD BE AVAILABLE.
Work Hygienic Practices: A SAFETY SHOWER AND EYEWASH STATION SHOULD BE AVAILABLE. IN EVENT CONCENTRATIONS MEET/EXCEED TLVS, USE RESP PROTECTION.
Supplemental Safety and Health
======== Physical/Chemical P

roperties ===========
HCC:T4 Spec Gravity:1.32 G/CM3 @23C Evaporation Rate & Reference:80 (BU AC=1) Solubility in Water:REACT SLOWLY W/WATER Appearance and Odor:YELLOWISH LIQUID TO BROWNISH LIQUID WITH ODOR OF SOLVENTS.
======================================
Stability Indicator/Materials to Avoid:YES WATER,AMINES,ALCOHOL,ACID,& ALKALI.MC REACTS VIOLENTLY W/UNPROTECTED ALUMINUM & ZINC SURFACES,SODIUM,POTSSIUM,MAGNESIUM. Stability Condition to Av
oid:AVOID TEMPERATURES ABOVE 40C., OPEN FLAMES AND WELDING AREAS WHICH CAN CAUSE THERMAL DEGRADATION. Hazardous Decomposition Products:BY HIGH HEAT & FIRE: CO, NOX, POX, SOX, HCL AND SMALL AMOUNTS OF PHOSGENE AND CHLORINE.

======= Disposal Considerations ===========

Conditions to Avoid Polymerization: AVOID TEMPERATURES ABOVE 40C.

Waste Disposal Methods:DISPOSAL MUST BE IN ACCORDANCE WITH STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE. CONTACT LICENSED

CHEMICAL WASTE DISPOSAL AGENCY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this in formation to their particular situation.