

LHB INDUSTRIES -- ECO SURE WHITE 37875 LUSTERLESS VOC-COMPLIA

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-331-6106
MSDS Date: 10/01/1992
MSDS Num: BQYNY
Product ID: ECO SURE WHITE 37875 LUSTERLESS VOC-COMPLIA
MFN: 01
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: S
T. LOUIS MO 63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: RUDOLF OPPENHEIM
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
=

=====
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141
=====

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-2787
Type/Grade/Class: TYPE I
Unit of Issue: PT
UI Container Qty: 0
Type of Container: METAL
=====

=====

Ingredients

=====

Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA III)
% Wt: <19.84
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 110-12-3
RTECS #: MP3850000
Name: METHYL ISOAMYL KETONE
% Wt: 5.83
Other REC Limits: NONE SPECIFIED
OSHA PEL: 100 PPM
ACGIH TLV: 50 PPM; 9293

Cas: 64742
-95-6
RTECS #: SE7546500
Name: AROMATIC 150
% Wt: <2.92
Other REC Limits: NONE SPECIFIED
OSHA PEL: 5 PPM
ACGIH TLV: 5 PPM

Cas: 64742-95-6
RTECS #: SE7546500
Name: AROMATIC 100
% Wt: 5.83
Other REC Limits: NONE SPECIFIED
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 108-10-1
RTECS #: SA9275000
Name: METHYL ISOBUTYL KETONE (SARA III)
% Wt: 2.92
Other REC Limits: NONE SPECIFIED
OSHA PEL: 100 PPM/75 STEL
ACGIH TLV: 50 PPM/75 STEL; 9293
EPA

Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 107-87-9
RTECS #: SA7875000
Name: METHYL PROPYL KETONE
% Wt: 2.92
Other REC Limits: NONE SPECIFIED
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM

Cas: 95-63-5
RTECS #: DC3325000
Name: 1,2,4-TRIMETHYLBENZENE (SARA III)
% Wt: <2.92
Other REC Limits: NONE SPECIFIED
OSHA PEL: 25 PPM
ACGIH TLV: 25 PPM

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 15.12
Other REC Lim
its: NONE SPECIFIED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 75-28-5
RTECS #: TZ4300000
Name: ISOBUTANE
% Wt: 5.95
Other REC Limits: NONE SPECIFIED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 800 PPM

Cas: 106-97-8
RTECS #: EJ4200000
Name: N-BUTANE
% Wt: 3.72
Other REC Limits: NONE SPECIFIED
OSHA PEL: 800 PPM
ACGIH TLV: 800 PPM

RTECS #: 9999999VO
Name: VOC: 548 G/L
Other REC Limits: NONE SPECIFIED

RTECS #: 9999999VO
Name: VOC: 60%
Other REC Limits: NONE RECOMMENDED
=====

Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: ACUTE; CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL. HIGH CONCENTRATIONS ARE ANESTHETIC. IRRITATION TO SKIN & RESPIRATORY TRACT. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES & THROAT. HEADACHES, NAUSEA, & VOMITING.
Signs And Symptoms Of Overexposure: CHRONIC; REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.
Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS.
First Aid: FOR CONTACT WITH SKIN OR CLOTHES WASH WITH SOAP & WATER; WASH CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES & CONTACT A PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR & GIVE ARTIFICIAL RESPIRATION IF NECESSARY & GET MEDICAL AID. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====
Handling and Disposal
=====

=====
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA. MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.
Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS. DO NOT PUNCTURE, BURN OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN IN TRASH PICK-UP. DO NOT PLACE IN HOME TRASH COMPACTOR.
Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN

EN! CAUTION -

CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 F. AVOID BREATHING SPRAY, MIST OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES OR SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====
Fire and Explosion Hazard Information
=====

=====
Flash Point Text: NR

Autoignition Temp Text: 467.8C

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO KEEP FIRE EXPOSED CNTNR COOL. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING OF CNTNR.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEM

PERATURE (OVER 120F) CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL CONTAINER; DO NOT EXPOSE TO TEMPS ABOVE 120 F.

=====
Control Measures
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

HCC: V3

Vapor Pres: 60 @ 68F

Vapor Density: >1.5

Spec Gravity: 0.997 (WATER=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: WHITE/PAINT

Percent Volati

=====
Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: EXTREME HEAT
Hazardous Decomposition Products: CARBON MONOXIDE
Hazardous Polymerization Indicator: NO
=====

Toxicological Information
=====

E
cological Information
=====

MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: 0FTT5
Trans ID NO: 126034
Product ID: ECO SURE WHITE 37875 LUSTERLESS VOC-COMPLIA
MSDS Prepared Date: 10/01/1992
Review Date: 03/23/1993
MFN: 1
Tech Entry NOS Shipping Nm: UN 1950 AEROSOL
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0
Type Of Container: METAL
=====

Detail DO

T Information

=====
DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

Detail IMO Information

=====
IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page
Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

Detail IATA Information

=====
IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant
Cargo: 150KG
Packaging Note Cargo: 203
=====

Detail AFI Information

=====
AFI PSN Code: ALS
AFI Proper Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.
AFI PSN Modifier: CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP I OR II
AFI Hazard Class: FORB
Back Pack Reference: FORBIDDEN
=====

HAZCOM Label

=====

====
Product ID: ECO SURE WHITE 37875 LUSTERLESS VOC-COMPLIA
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 12/16/1998
Status Code: C
Label Date: 12/16/1998
Origination Code: G

Hazard And Precautions: ACUTE; CONCENTRATING & INHALING CONTENTS MAY BE HARMFUL/FATAL. HIGH CONCENTRATIONS ARE ANESTHETIC. IRRITATION TO SKIN & RESPIRATORY TRACT. OVEREXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES & THROAT. HEADACHES, NAUSEA, & VOMITING. CHRONIC; REPORTS HAVE ASSOCIATED REPEATED & PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.