

LOCTITE CORP AUTOMOTIVE & CONS -- 44581 FAST CURE EPOXY 45 PART B

=====  
MSDS Safety Information  
=====

FSC: 8040  
NIIN: 01-046-5061  
MSDS Date: 03/26/1991  
MSDS Num: BRBNN  
Product ID: 44581 FAST CURE EPOXY 45 PART B  
MFN: 02  
Kit Part: Y  
Responsible Party  
Cage: DO429  
Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP  
Address:  
4450 CRANWOOD CT  
City: CLEVELAND OH 44128-4004  
Info Phone Number: 216-663-3011  
Emergency Phone Number: 800-321-9188  
Preparer's Name: KATHRYN A. HOLEN  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: DO429  
Assigned Ind: Y  
Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP  
Address: 4450 CRANWOOD COURT  
City: CLEVELAND OH 44128

=====  
Contractor Summary  
=====

Cage: DO429  
Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP  
Address: 4450 CRANWOOD COURT  
City: CLEVELAND OH 44128  
Phone: (216) 663-3011  
Cage: 62377  
Name: PERMATEX INDUSTRIAL  
Address: HARTFORD SQUARE N 10 COLUMBUS BLVD  
City: HARTFORD CT 06106  
Phone: 877-376-2839

=====  
Item Description Information  
=====

=====

Item Manager: GSA  
Item Name: ADHESIVE  
Unit of Issue: KT  
UI Container Qty: 0

=====

Ingredients

=====

Name: POLYMERCAPTAN  
% Wt: 30-35

-----  
Cas: 1344-28-1  
RTECS #: BD1200000  
Name: ALUMINUM OXIDE, BAUXITE, ALUMINA, DIALUMINUM TRIOXIDE  
% Wt: 45-50  
OSHA PEL: 15 MG/M3 TDUST  
ACGIH TLV: 10 MG/M3 TDUST; 9293

-----  
Name: SUBSTITUTED AMINOPHENOL  
% W  
t: 5-10

-----  
Name: AROMATIC PLASTICIZER  
% Wt: 5-10

-----  
Cas: 100-42-5  
RTECS #: WL3675000  
Name: STYRENE, (MONOMER), SUSPECTED ANIMAL CARCINOGEN BY IARC & ACGIH  
% Wt: <5  
Other REC Limits: 50 PPM  
OSHA PEL: 100 PPM  
ACGIH TLV: S,50PPM/100STEL;9293  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----  
Cas: 7631-86-9  
RTECS #: VV3100000  
Name: SILICON DIOXIDE, CELITE 322  
% Wt: 1-3  
OSHA PEL: 80 MG/CUM  
ACGIH TLV: 0.2 MG/CUM

-----

-----  
Cas: 107-21-1  
RTECS #: KW2975000  
Name: ETHYLENE GLYCOL, GLYCOL  
% Wt: 1-3  
Other REC Limits: 10 MG/CUM  
ACGIH TLV: C 127 MG/CUM  
EPA Rpt Qty: 1 LB  
DOT Rpt Qty: 1 LB

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES  
Skin: YES  
Ingestion: YES  
Carcinogenicity Inds - NTP: NO  
IARC: YES  
OSHA: NO  
Effects of Exposure: EYES: IRRITATION. SKIN: SENSITIZATION OR DERMA  
TITIS.

INHALATION: PULMONARY EFFECTS.

Explanation Of Carcinogenicity: SEE INGREDIENTS

First Aid: INGESTION: DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR.

SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/WATER FOR 15 MIN.

OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====  
Handling and Disposal  
=====

Spill Release Procedures: SOAK UP W/INERT ABSORBENT.

Waste Disposal Methods: LANDFI

LL OR INCINERATE IN ACCORDANCE W/LOCAL, FEDERAL

& STATE REGULATIONS.

Handling And Storage Precautions: STORE &lt;110F TO PRESERVE SHELF LIFE. AVOID

CONTACT W/EYES & SKIN.

=====  
Fire and Explosion Hazard Information  
=====

Flash Point Method: TCC

Flash Point Text: >200F

Extinguishing Media: CO2, FOAM OR DRY CHEMICAL

=====  
Control Meas

ures

=====

Ventilation: SUFFICIENT TO MAINTAIN VAPOR CONCENTRATION BELOW TLV.  
 Protective Gloves: RUBBER OR PLASTIC  
 Eye Protection: SAFETY GLASSES  
 Supplemental Safety and Health: INHALATION OF PURE SILICON DIOXIDE DUST HAS BEEN SHOWN TO CAUSE PULMONARY EFFECTS.

=====

Physical/Chemical Properties

=====

B.P. Text: >300F  
 Vapor Pres: <5  
 Solubi  
 lity in Water: SLIGHT  
 Appearance and Odor: WHITE & BLACK PASTE; SULFUR ODOR.

=====

Reactivity Data

=====

Stability Indicator: YES  
 Hazardous Polymerization Indicator: NO

=====

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

HAZCOM Label

=====

Product ID: 44581 FAST CURE EPOXY 45 PART B  
 Cage: DO429  
 Assigned IND: Y  
 Company Name: LOCTITE CORP AUTOMOTIVE & CONSUMER GROUP  
 Street: 4450 CRANWOOD COURT  
 City: CLEVELAND OH  
 Zipcode: 44128  
 Health Emergency Phone: 800-321-9188  
 Label Required IND: Y  
 Date Of Label Review: 07/01/1993  
 Status Code: C  
 Label Date: 07/01/1993  
 Origination Code: F  
 Eye Protection IND: YES  
 Skin Protection IND: YES  
 Signal Word: CAUTION  
 Health Ha

zard: Slight

Contact Hazard: Slight

Fire Hazard: Slight

Reactivity Hazard: None

Hazard And Precautions: EYES: IRRITATION. SKIN: SENSITIZATION OR DERMATITIS.

INHALATION: PULMONARY EFFECTS. TARGET ORGANS: SKIN, LUNGS. CARCINOGEN:

STYRENE. TH. TARGET ORGANS: CENTRAL NERVOUS SYSTEM, KIDNE

YS, HEART, BRAIN, BLOOD, SKIN. CARCINOGEN: SILICA DIOXIDE.

=====  
Disclaimer (provided with this information by the compiling agencies): This  
informat

ion is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied

warrants, states, or intends said information to have any application, use or

viability by or to any person or persons outside the Department of Defense

nor any person or persons contracting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person

utilizing this instruction who is not a milit

ary or civilian employee of the

United States of America should seek competent professional advice to verify

and assume responsibility for the suitability of this information to their

particular situation regardless of similarity to a corresponding Department

of Defense or other government situation.