

UNION CARBIDE CORP LINDE DIV -- NITROGEN (FOR 41GP-YOOG-F50Y THERMOMETER) --
6685-01-254-0469

===== Product Identification =====

Product ID:NITROGEN (FOR 41GP-YOOG-F50Y THERMOMETER)

MSDS Date:08/01/1985

FSC:6685

NIIN:01-254-0469

MSDS Number: BRDLK

=== Responsible Party ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Pho

ne Num:304-744-3487

Emergency Phone Num:800-822-4357

CAGE:36346

=== Contractor Identification ===

Company Name:DRESSER INDUSTRIES INC, WEKSLER INSTRUMENTS OPN

Address:250 E MAIN ST

Box:City:STRATFORD

State:CT

ZIP:06497-5145

Country:US

Phone:203-385-0490

CAGE:049X3

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

Company Name:WEKSLERIGLASS THERMOMETER CORP

Address:80 MILL ROAD

Box

:City:FREEPORT
State:NY
ZIP:11520
Country:US
Phone:516-623-0100
CAGE:64467

=====
Composition/Information on Ingredients
=====

Ingred Name:NITROGEN
CAS:7727-37-9
RTECS #:QW9700000
Fraction by Wt: 100%
Other REC Limits:NONE RECOMMENDED
ACGIH TLV:ASPHYXIAN; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:
ASPHYXIATION. CHRONIC: NONE.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: SHORTNESS OF BREATH, DIFFICULTY
BREATHING, UNCONSCIOUSNESS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NEEDED.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:USE MEDIA FOR SURROUND
ING FIRE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE GEAR. COOL CONTAINERS WITH FLOODING AMOUNTS OF
WATER UNTIL WELL AFTER FIRE IS OUT.
Unusual Fire/Explosion Hazard:GAS UNDER PRESSURE. CONTAINER MAY EXPLODE
IF EXPOSED TO FIRE OR HIGH TEMPERATURES.

=====
Accidental Release Measures
=====

Spill Release Procedures:TRY TO STOP LEAK IF IT CAN BE DONE AT NO RISK.
VENTILATE AREA. DISPELL VAPORS WITH WATER.

Neutrali

zing Agent:NONE

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN A COOL, DRY AREA.

Other Precautions:NONE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NONE NORMALLY REQUIRED. IF IDLH CONDITIONS ARE PRESENT WEAR SELF-CONTAINED BREATHING APPARATUS.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:LEATHER

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Pro

ective Equipment:NONE

Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:G3

Boiling Pt:B.P. Text:-320F,-196C

Melt/Freeze Pt:M.P/F.P Text:-346F,-210C

Vapor Density:< 1(AIR=1)

Spec Gravity:0.8

Appearance and Odor:COLORLESS, ODORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE

Percent Volatiles by Volume:100

=====
Stability and Reactivity Dat

a
=====

Stability Indicator/Materials to Avoid:YES

UNDER CERTAIN CONDITIONS; LITHIUM, NEODYMIUM, TITANIUM, OZONE.

Stability Condition to Avoid:HIGH TEMPERATURES, OPEN FLAME.

Hazardous Decomposition Products:OXIDES OF NITROGEN

=====
Disposal Considerations
=====

Waste Disposal Methods:CONTACT LOCAL ENVIRONMENTAL MANAGER. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compil

ing agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.