View NSN Online: https://aerobasegroup.de/nsn/6685-01-274-8871

UNION CARBIDE CORP LINDE DIV -- NITROGEN (FOR 41GP-YOOG-F35Y THERMOMETER)

6685-01-274-8871

============= Product Identification ==================

Product ID:NITROGEN (FOR 41GP-YOOG-F35Y THERMOMETER)

MSDS Date: 08/01/1985

FSC:6685

NIIN:01-274-8871

MSDS Number: BRDLN === Responsible Party ===

Company Name: UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

City: DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Pho

ne Num:304-744-3487

Emergency Phone Num:800-822-4357

CAGE:36346

=== Contractor Identification ===

Company Name: UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

Company Name: WEKSLERIGLASS THERMOMETER CORP

Address:80 MILL ROAD Box:City:FREEPORT

State:NY ZIP:11520 Country:US

Phone:516-623-0100

CAGE:64467

======= Composition/Information on Ingredients ========

Ingred Name:NITROGEN

CAS:7727-37-9 RTECS #:QW9700000 Fraction by Wt: 100% Other REC Limits: NONE RECOMMENDED ACGIH TLV:ASPHYXIANT; 9293 ============ Hazards Identification ========================= Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: ASPHYXIATION. CHRONIC: NONE. **Explanation of Carcinogenicity:NONE** Effects of Overexposure: INHALATION: SHORTNESS OF BREATH, DIFFICULTY BREATHING, UNCONSCIOUSNESS. M edical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NEEDED. Flash Point:NONE Extinguishing Media: USE MEDIA FOR SURROUNDING FIRE. Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL CONTAINERS WITH FLOODING AMOUNTS OF WATER UNTIL WELL AFTER FIRE IS OUT. Unusual Fire/Explosion Hazard: GAS UNDER PRESSURE. CONTAINER MAY EXPLODE IF EXPOSED TO FIRE OR HIGH TEMPERATURES. ========= Accidental Release Measures ===============

Spill Release Procedures:TRY TO STOP LEAK IF IT CAN BE DONE AT NO RISK. VENTILATE AREA. DISPELL VAPORS WITH WATER.

Neutralizing Agent:NONE

=========== Handling and Storage =============

Handling and Storage Precautions:STORE IN A COOL, DRY AREA. Other Precautions:NO

====== Exposure Controls/Personal Protection ========
Respiratory Protection:NONE NORMALLY REQUIRED. IF IDLH CONDITIONS ARE PRESENT WEAR SELF-CONTAINED BREATHING APPARATUS. Ventilation:USE ADEQUATE MECHANICAL VENTILATION. Protective Gloves:LEATHER
Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES Other Protective Equipment:NONE
Work Hygienic Practices:WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING.
Supplemental Safety and Health
============= P
hysical/Chemical Properties =========
HCC:G3
Boiling Pt:B.P. Text:-320F,-196C
Melt/Freeze Pt:M.P/F.P Text:-346F,-210C
Vapor Density:< 1(AIR=1) Spec Gravity:0.8
Appearance and Odor:COLORLESS, ODORLESS GAS AT NORMAL TEMPERATURE AND PRESSURE
Percent Volatiles by Volume:100
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES UNDER CERTAIN CONDITIONS; LITHIUM, NEODYMIUM, TITANIUM, OZONE. Stability Condition to Avoid:HIGH TEMP ERATURES. OPEN FLAME

Hazardous Decomposition Products:OXIDES OF NITROGEN

======= Disposal Considerations ===========

Waste Disposal Methods: CONTACT LOCAL ENVIRONMENTAL MANAGER. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or

implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.