

TEXACO INC -- UNLEADED PLUS,00375 -- 9130-00-148-7103

===== Product Identification =====

Product ID:UNLEADED PLUS,00375

MSDS Date:10/24/1990

FSC:9130

NIIN:00-148-7103

MSDS Number: BRFLQ

=== Responsible Party ===

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Info Phone Num:914-831-3400 X 204

Emergency Phone Num:914-831-3400/800-424-9300(CHEMTREC)

Preparer's Name:M.

J. VON ALLMEN

CAGE:7B131

=== Contractor Identification ===

Company Name:SCHULTE OIL CO

Address:1516 S ROCK ISLAND

Box:188

City:EL RENO

State:OK

ZIP:73036

Country:US

Phone:405-262-3120

CAGE:4R019

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

===== Composition/Information on Ingredients =====

Ingred Name:GASOLINE (INCLUDES INGREDIENTS 3, 4, 5 ....)

CAS:8006-61-9

RTECS #:LX3300000

Fraction by Wt: 95-99.9%

Other REC L

imits:NONE RECOMMENDED  
OSHA PEL:300 PPM/500 STEL  
ACGIH TLV:300 PPM/500STEL;9293

Ingred Name:ALIPHATIC PETROLEUM SOLVENT/KEROSENE  
CAS:8008-20-6  
RTECS #:OA5500000  
Fraction by Wt: .01-.09%  
Other REC Limits:NONE RECOMMENDED

Ingred Name:BENZENE (SARA III), 1-3.99%  
CAS:71-43-2  
RTECS #:CY1400000  
Fraction by Wt: SEE # 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1PPM/5STEL;1910.1028  
ACGIH TLV:10 PPM; A2; 9293  
EPA Rpt Qty:10 LBS  
DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE (SARA III), 4-10.99  
CAS:108-88-  
3  
RTECS #:XS5250000  
Fraction by Wt: SEE # 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III), 1-3.99  
CAS:100-41-4  
RTECS #:DA0700000  
Fraction by Wt: SEE # 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/125 STEL  
ACGIH TLV:100 PPM/125STEL 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III), 4-10.99  
CAS:1330-20-7  
RTECS #:ZE2100000  
Fr

action by Wt: SEE # 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:100 PPM/150 STEL  
ACGIH TLV:100 PPM/150STEL;9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE (SARA III), 1-3.99  
CAS:95-63-6  
RTECS #:DC3325000  
Fraction by Wt: SEE # 1%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:25 PPM  
ACGIH TLV:25 PPM; 9293

Ingred Name:METHYL TERT-BUTYL ETHER (SARA III), 0-15%  
CAS:1634-04-4  
RTECS #:KN5250000  
Fraction by Wt: SEE # 1%  
Other REC Limits:NONE RECOMMENDED  
EPA Rpt Qty:1  
LB  
DOT Rpt Qty:1 LB

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS 18.75 ML/KG.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE- INHALATION OF VAPORS MAY CAUSE  
CNS DEPRESSION, CONVULSION, LOSS OF CONSCIOUSNESS. INGESTION HAS  
SYMPTOMS SIMILAR TO INHALATION & ASPIRATION HAZARD. EYE/SKIN  
CONTACT CAUSES IRRITATION. CHRONIC  
- DERMATITIS, NERVOUS SYSTEM,  
KIDNEY, LIVER & BLOOD DISORDERS INCLUDING ANEMIA & LEUKEMIA. KIDNEY  
CANCER IN LAB ANIMALS.  
Explanation of Carcinogenicity:CONTAINS BENZENE. MAY CAUSE BLOOD  
DISEASES INCLUDING LEUKEMIA. VAPORS MAY CAUSE KIDNEY CANCER IN MALE  
RATS.  
Effects of Overexposure:HEADACHE, NASAL & RESPIRATORY IRRITATION,  
NAUSEA, DROWSINESS, FATIGUE, EYE & SKIN IRRITATION, PULMONARY  
EDEMA, CONVULSION & LOSS OF CONSCIOUSNESS  
Medical Cond Aggravated by Exposure:BENZENE-

INDIVIDUALS WITH LIVER,  
KIDNEY AND BLOOD DISEASES. HEXANE- INDIVIDUALS WITH NEUROLOGICAL  
DISEASES. PETROLEUM SOLVENT- THOSE WITH EXISTING DERMATITIS.

=====  
First Aid Measures  
=====

First Aid:CALL A PHYSICIAN IN ALL CASES. EYES:IMMEDIATELY FLUSH WITH  
WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP &  
WATER. INHALED:REMOVE TO FRESH AIR & PROVIDE CPR/OXYGEN IF  
NECESSARY. ORAL: DO NOT INDUCE VOMITING UNLESS INSTRUCTED BY A

PHYSICIAN. CALL A PHYSICIAN IMMEDIATELY. IF VOMITING OCCURS  
SPONTANEOUSLY, KEEP HEAD BELOW HIPS.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC

Flash Point:-40F,-40C

Autoignition Temp:Autoignition Temp Text:850F

Lower Limits:1.4

Upper Limits:7.6

Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL AND  
VAPORIZING LIQUID TYPE EXTINGUISHERS. WATER MAY BE INEFFECTIVE.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT & A

FULL FACED SELF CONTAINED BREATHING APPARATUS/SUPPLIED-AIR  
RESPIRATOR.COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:THE INVISIBLE VAPORS ARE HEAVIER THAN AIR  
AND TRAVEL SOME DISTANCE TO IGNITION SOURCES & FLASH BACK. CAN FORM  
FLAMMABLE MIXTURE WITH AIR & FLASH AT ROOM TEMP.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS.ELIMINATE ALL  
SOURCES OF IGNITION.USE EXPLOSION-PROOF

TOOLS.SHUT OFF FUEL

SOURCE.DIKE SPILL.PREVENT LIQUID FROM ENTERING

SEWERS/WATERWAYS.RECOVER FREE LIQUID.ADD SAND,EARTH OR OTHER  
ABSORBENT MATERIAL.TRANSFER TOCONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:STORE IN ACCORDANCE WITH NATIONAL FIRE  
PROTECTION ASSOCIATION REGULATIONS. KEEP CONTAINERS CLOSED.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUE AND CAN BE  
DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, SOL

DER, DRILL OR EXPOSE

SUCH CONTAINERS TO HEAT, FLAME, SPARKS. THEY MAY EXPLODE AND CAUSE INJURY/DEATH. AVOID REPEATED OR PROLONGED CONTACT WITH SKIN.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS OR ORGANIC VAPOR RESPIRATOR OR SUPPLIED-AIR RESPIRATOR, IF NEEDED.

Ventilation:LOCAL/MECHANICAL (GENERAL) VENTILATION - EXPLOSION PROOF, WELL GROUNDED EQUIPMENTS

Protective Gloves:RUBBER  
RECOMMENDED

Eye Protection:CHEMICAL SPLASH GOGGLES & FACE SHIELD

Other Protective Equipment:IMPERVIOUS CLOTHING TO AVOID SKIN AND EYE CONTACT. EYE WASH STATION & SAFETY SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES, SKIN OR CLOTHING. WASH HANDS AFTER USING PRODUCT. AVOID BREATHING VAPORS OR MISTS.

Supplemental Safety and Health

FORMULA CHANGED. FOR PREVIOUS FORMULATION, SEE PNI A UNDER THE SAME NSN.

=====  
===== Physical/Chemical Properties =====

HCC:

F2

Boiling Pt:B.P. Text:>90F,>32C

Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN

Vapor Pres:465 @ 100F

Vapor Density:3 - 4

Spec Gravity:0.70 - 0.77

Evaporation Rate & Reference:NOT KNOWN

Solubility in Water:SLIGHT

Appearance and Odor:LIGHT STRAW TO LIGHT RED LIQUID - GASOLINE ODOR

Percent Volatiles by Volume:100

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT, SPARKS, OPEN F

LAMES AND OTHER  
SOURCES OF IGNITION

Hazardous Decomposition Products:FUMES, CARBON MONOXIDE, CARBON DIOXIDE  
AND OTHER DECOMPOSITION PRODUCTS

===== Disposal Considerations =====

Waste Disposal Methods:RECYCLE AS MUCH AS POSSIBLE. TREATMENT, STORAGE,  
TRANSPORTATION AND DISPOSAL MUST BE IN ACCORDANCE WITH ALL  
APPLICABLE LOCAL, STATE AND FEDERAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.