

ASPEN PAINTS -- STAIN, OIL TYPE, WOOD INTERIOR, LIGHT OAK -- 8010-00-597-8226

=====  
Product Identification  
=====

Product ID:STAIN, OIL TYPE, WOOD INTERIOR, LIGHT OAK

MSDS Date:03/01/1993

FSC:8010

NIIN:00-597-8226

MSDS Number: BRGKC

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603

Emergency Ph

one Num:800-424-9300 (CHEMTREC)

Preparer's Name:D KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SK SOLVENT

(MINERAL SPIRITS MIXTURE) SOLVENT 390

CAS:8052-41-3

RTECS #:WJ8925000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred Name:BENZENE, < 10 PPM (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:VOC: 494 G/L

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

=====  
===== Hazards Identification =====  
=====

LD50 LC50 Mixture:RAT:ORAL >8 ML/KG. INHAL +71  
400 PPM/4 HR

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE; INHAL: NASAL & RESP IRRIT,  
DIZZY, WEAK, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUS, ASPHYXIATION.  
EYE: SEVERE IRRIT, RED, TEAR, BLURRED VISION. INGEST: GI IRRIT,  
NAUSEA, VOMIT, DIARRHEA. ASPIRATION INTO LUNGS CAN CAUSE CHEMICAL  
PNEUMONITIS (CAN BE FATAL). CONCENTRATING & INHALING PRODUCT MAY BE  
HARMFUL OR FATAL.

Effect

s of Overexposure:CHRONIC; SKIN CONTACT: PROLONGED AND REPEATED  
CONTACT WITH SKIN CAN CAUSE DEFATTING AND DRYING OF THE SKIN  
RESULTING IN SKIN IRRITATION AND DERMATITIS. REPORTS HAVE  
ASSOCIATED REPEATED AND PROLONGED O CCUPATIONAL OVEREXPOSURE TO  
SOLVENT WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

=====  
===== First Aid Measures =====  
=====

First Aid:INHALATION: REMOVE VICTIM FROM FURTHER EXPOSURE AND RESTORE  
BREATHING IF REQUIRED. EYE: FLUSH EY

ES WITH WATER FOR AT LEAST 15

MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH MILD SOAP & WATER.

INGESTION: DONT INDUCE VOMITING. GET MED AID IMMEDIATELY. NOTE TO PHYSICIAN: MAIN HAZARD FOLLOWING INGESTION IS ASPIRATION OF LIQUID TO LUNGS PRODUCING CHEMICAL PNEUMONITIS. CARDIAC ARRYTHMIAS REPORTED.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:112F,44C

Lower Limits:0.8

Upper Limits:5.0

Extinguishing Media:DRY CHEMICA

L, CO2, FOAM, AND WATER FOG

Fire Fighting Procedures:FLAMMABLE. DONT ENTER CONFINED FIRE SPACE W/O PROTECTIVE CLOTH & POS PRESSURE SCBA. EXCLUDE AIR. DONT USE WATER EXCEPT AS FOG (USE TO COOL FIRE EXPOSED CNTNRS).

Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES AND ALL IGNITION SOURCES. VAPOR FORMS AN EXPLOSIVE MIXTURE WITH AIR BETWEEN UPPER AND LOWER FLAMMABLE LIMITS.

===== Accidental Release Measures =====

Spill Release Procedures:E

LIMINATE IGNIT SOURCE. VENT AREA. ABSORB

SPILL W/ABSORBNT (SAWDUST, SAND, VERMICULITE), PLACE IN CLOSD CNTNR. LARGE: DIKE AREA TO PREVENT MATERIAL FROM ENTERING WATER SYSTEMS/SEWERS. WEAR PROTECTIVE CLOTHES. NOTIFY ENVIRONMNTL AGENCIES IF>220 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE LIQUID. STORE IN COOL, DRY, WELL-VENTED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED/REPEATED CONTACT

WITH SKIN. AVOID BREATHING

Other Precautions:WASH CONTAM CLOTHES PRIOR TO REUSE. USE GOOD PERSONAL HYGIENE. GROUND CNTNR WHEN POURING & LIMIT FREE FALL (MINIMIZE STATIC BLDUP). EMPTY CNTNRS HAZARDOUS FROM RESIDUES. DONT TAKE INTERNALLY. CLOSE CN TNR AFTER USE. KEEP AWAY FROM CHILDREN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT THE INHALATION OF VAPOR OR SPRAY MISTS WHEN TLV PEL IS

EXCEEDED.

Ventilation:GENERAL VENT REQUIRED DURING NORMAL USE. LOCAL VENTILATION  
MAY BE REQUIRED TO KEEP EXPOSURE LEVEL BELOW LIMITS LISTED.

Protective Gloves:CHEM RESIST NITRILE, NEOPRENE, RUBBER

Eye Protection:WEAR FACE SHIELDS OR CHEMICAL GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN  
CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pres:>7.0 @ 38C

Vapor Density:4.8

Spec Gravity:0.87 (WATER=1)

Viscosity:10"-25" #4FC

Evaporation Rate & Reference:SLOWER THAN N-BUTYL AC

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THIN LIQUID, MILD ODOR

Percent Volatiles by Volume:65-69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:

CARBON MONOXIDE AND CARBON DIOXIDE ARE  
PRODUCED ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:IF NOT POSSIBLE TO RECLAIM, TREAT AS HAZARDOUS  
WASTE (EPA WASTE #D001) BASED ON IGNITABILITY. ALL DISPOSAL  
PROCEDURES MUST COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.  
REFER TO HAZARD CAUTION INFORMATION IN OTHER SECTIONS OF THIS  
MSDS.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.