

HEXAGON CHEMICAL COMPANY -- HEXAFLOC M-20 -- 6850-01-167-5318

===== Product Identification =====

Product ID:HEXAFLOC M-20

MSDS Date:12/18/1990

FSC:6850

NIIN:01-167-5318

MSDS Number: BRGQT

=== Responsible Party ===

Company Name:HEXAGON CHEMICAL COMPANY

Box:23163

City:LOUISVILLE

State:KY

ZIP:40223

Country:US

Info Phone Num:502-244-1172

Emergency Phone Num:502-244-1172,502-228-4001(AFTER HR)

CAGE:0A6

43

=== Contractor Identification ===

Company Name:HEXAGON CHEMICAL COMPANY

Box:City:LOUISVILLE

State:KY

ZIP:40223

Country:US

Phone:502-244-1172

CAGE:0A643

===== Composition/Information on Ingredients =====

Ingred Name:NONHAZARDOUS INGREDIENT.APPROVED BY EPA FOR CLARIFICATION
OF DRINKING WATER UP TO 50 MG/L.

Other REC Limits:NOT KNOWN

OSHA PEL:NOT KNOWN

ACGIH TLV:NOT KNOWN

===== Hazards Identification =====

LD50 LC50 Mixture:NOT KNOWN

Ro

utes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CONTACT WITH EYES WILL INJURE EYE
TISSUE IF NOT WASHED OFF THOROUGHLY AND PROMPTLY WITH WATER.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:EYES:IRRITATING. SKIN:IRRITATING.LOW ORDER OF
TOXICITY. INGESTION:LOW ORDER OF TOXICITY. INHALATION:NO HAZARD IN
NORMAL INDUSTRIAL USE.VERY LOW VAPOR PRESSURE.
Medical Cond Aggravated by Exposure
:NOT KNOWN

===== First Aid Measures =====

First Aid:EYES:IMMEDIATELY FLUSH WITH LARGE AMOUNTS OF WATER FOR AT
LEAST 15 MIN.GET PROMPT MED ATTN. SKIN:FLUSH WITH LARGE AMOUNTS OF
WATER,USE SOAP IF AVAILABLE.REMOVE GROSSLY CONTAMINATED
CLOTHING,INCLUDING SHOES,LAUNDRER BEFORE REUSE.IF IRRITATION
PERSISTS,SEEK MED ATTN. INGESTION:IF SWALLOWED,DO NOT INDUCE
VOMITING.KEEP AT REST.GET PROMPT MED ATTN. INHALATION:FIRST AID IS
NORMALLY NOT RE
QUIRED.

===== Fire Fighting Measures =====

Flash Point Method:SCC
Flash Point:210F,99C
Extinguishing Media:USE ALCOHOL TYPE FOAM,DRY CHEMICAL OR WATER SPRAY
TO EXTINGUISH FIRE.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA)
AND FULL TURNOUT GEAR .USE WATER SPRAY TO COOL FIRE EXPOSED
SURFACES & TO PROT PERS.ISOLATE "FUEL" SUPPLY.
Unusual Fire/Explosion Hazard:NO UNUSUAL OR TOXIC PRODUCTS.LIQUID CAN
BURN UPON HEATING TO T
EMP AT OR ABOVE THE FLASHPOINT.

===== Accidental Release Measures =====

Spill Release Procedures:LAND SPILL:USE DRY ABSORBENT MATL.DIKE &
ABSORB SPILL WITH INERT MATL,SUCH AS SAND,EARTH,OR VERMICULITE &
TRANSFER TO SUITABLE CONTR FOR DISP.PVNT FROM ENTERING
SEWERS,WATERCOURSES,OR LOW AREAS.RECOVE R BY PUMPING OR WITH
SUITABLE ABSORB.(SEE SUPP)
Neutralizing Agent:NOT KNOWN

===== Handling and Storage =====

Handling

and Storage Precautions:STORAGE/LOADING/UNLOADING
TEMP:AMBIENT.STORAGE PRESSURE:ATMOSPHERIC.
Other Precautions:"EMPTY" CONTR RETAIN PRODUCT RESIDUES.DO NOT
PRESS,CUT,WELD,BRAZE,SOLDER,DRILL,GRIND,OR EXPOSE TO SOURCES OF
IGNITION,THEY MAY EXPLODE.EMPTY DRUMS SHOULD BE COMPLETELY
DRAINED,PROPERLY BUNGED & RETURN ED TO DRUM RECONDITIONER/DISPOSED
OF.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:CONTACT LOCAL SAFETY/INDUSTRIAL HYGIE
NE OFFICE
TO DETERMINE IF RESPIRATORY PROTECTION IS REQUIRED .
Ventilation:NO SERIOUS VAPOR EXPOSURE PROBLEMS UNDER NORMAL CONDITIONS.
Protective Gloves:NOT KNOWN
Eye Protection:CHEMICAL SAFETY GOGGLES .
Other Protective Equipment:WHERE CONTACT MAY OCCUR,WEAR LONG SLEEVES.
Work Hygienic Practices:NOT KNOWN
Supplemental Safety and Health
DENSITY:8.7 LBS/GAL @ 60F,16C.MP:25-30F,77-86C.VISCOSITY AT
LOADING/UNLOADING TEMP:10-100 CPS AT 77F,25C.SPILL PROC:WATER
SPILL:PRVT ADDNL DISCHARGE
OF MATL,IF POSSIBLE TO DO SO WITHOUT
HAZARD.ADVISE AUTHORITIES.CONSULT HEALTH INFO & PROT REGARDING
POSSIBLE HAZARDS.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C
Melt/Freeze Pt:M.P/F.P Text:SEE SUPP
Decomp Temp:Decomp Text:NOT KNOWN
Vapor Pres:SEE SUPP
Vapor Density:>1 (AIR=1)
Spec Gravity:1.02-1.03
Viscosity:10-150CP@77F
Evaporation Rate & Reference:1.5 (BUTYL ACETATE=1)
Solubility in Water:SOLUBLE
Appearance and Odor:LIGHT
AMBER VISCOUS FLUID WITH MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:NONE
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISP MUST BE IAW FED,STATE,& LOC REGS.COORDINATE
W/ SUPPORTING INSTALLATION/MACOM ENVIRON OFFICE PRIOR TO

DISP .

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.