

FARMERS UNION CENTRAL EXCHANGE INC (CENEX) -- KEROSENE -- 9140-00-273-2394

=====
Product Identification
=====

Product ID:KEROSENE

MSDS Date:11/01/1985

FSC:9140

NIIN:00-273-2394

MSDS Number: BRGVJ

=== Responsible Party ===

Company Name:FARMERS UNION CENTRAL EXCHANGE INC (CENEX)

Address:5500 CENEX DR CENEX MS 530

Box:64089

City:ST. PAUL

State:MN

ZIP:55164-0089

Country:US

Info Phone Num:612-451-5151

Emergency Phone Num:800-424-9300

CAGE:5Z134

=== Contractor Identification ===

Company Name:FARMERS UNION CENTRAL EXCHANGE INC

Address:5500 CENEX DR CENEX MS 530

Box:64089

City:ST PAUL

State:MN

ZIP:55164-0089

Country:US

Phone:612-451-5151

CAGE:5Z134

=====
Composition/Information on Ingredients
=====

Ingred Name:COMPLEX MIXTURE OF PARAFFINIC, OLEFINIC, NAPHTHANIC &
AROMATIC HYDROCARBONS

Fraction by Wt: >95%

Other REC Limits:NONE RECOMMENDED

Ingred Name:BENZENE (SARA III)

CAS:71-43-2

RTECS #:CY1400000

Fraction by Wt: 38C

Autoignition Temp:Autoignition Temp Text:>410F

Lower Limits:0.6

Upper Limits:8.0

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM, WATER SPRAY OR FOG. USE A SMOTHERING TECHNIQUE FOR EXTINGUISHING FIRE.

Fire Fighting Procedures:A FORCED STREAM OF WATER COULD SCATTER FLAMES OF BURNING FUELS. FLAMMABLE VAPORS WILL BE EMITTED FROM HEATED LIQUID. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:WATER RUNOFF T

O SEWER MAY CARRY

COMBUSTIBLE FUELS AND CREATE A FIRE OR EXPLOSION HAZARD.

FIREFIGHTERS SHOULD USE SELF- CONTAINED BREATHING APPARATUS.

===== Accidental Release Measures =====

Spill Release Procedures:REPORT SPILLS AS REQUIRED TO AUTHORITIES. REMOVE SOURCES OF HEAT OR IGNITION. PROVIDE OPTIMUM EXPLOSION PROOF VENTILATION. CONTAIN SPILL AND COLLECT LIQUID. DO NOT FLUSH TO SEWER OF SURFACE WATER. USE ABSORBENT MATERIAL TO PICK UP SMALL SPILLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS IN A WELL VENTILATED AREA AWAY FROM SOURCES OF HEAT, IGNITION, AND STRONG OXIDIZING AGENTS. GROUND AND BOND CONTAINERS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC MIST AND VAPOR FILTER.

USE IN ACCORDANCE WITH 29 CFR 1910.134.

Ventilation:GENERAL AND LOCAL EXHAUST VENTILATION.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Other Protective Equipment:EYEWASH STATIONS AND WASHING FACILITIES.

Work Hygienic Practices:WASH HANDS AND EXPOSED SKIN FREQUENTLY DURING WORK DAY.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:>330F,>166C

Spec Gravity:0.80-0.87

Solubility in Water:NEGLIGIBLE

Appearance and Odor:WATER WHITE TO YELLOW COLOR LIQUID WITH MILD
PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, FLAME, AND SPARKS. CONTACT WITH
STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CARBON MONOXIDE AND OTHER TOXIC
MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:MAY BE DI

SPOSED OF THROUGH A LICENSED WASTE

DISPOSAL COMPANY, OR BY CONTROLLED INCINERATION OR ABSORBED
MATERIAL CAN BE BURIED IN AN APPROVED LANDFILL. FOLLOW LOCAL, STATE
AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liabil

ity for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.