

JOHN CRANE INC -- UNKNOWN -- 5330-00-599-9552

=====  
Product Identification  
=====

MSDS Date:08/03/1993

FSC:5330

NIIN:00-599-9552

MSDS Number: BRGXC

=== Responsible Party ===

Company Name:JOHN CRANE INC

Address:6400 OAKTON ST

City:MORTON GROVE

State:IL

ZIP:60053-2725

Country:US

Info Phone Num:708-967-2400

Emergency Phone Num:708-967-2400

Preparer's Name:HMIS TECHNICIAN

CAGE:5F893

=== Contractor Iden

tification ===

Company Name:JOHN CRANE INC.

Address:RT. 51 AND PAYNE DRIVE

Box:City:VANDALIA

State:IL

ZIP:62471-9330

Country:US

Phone:618-283-4700

CAGE:5F893

Company Name:JOHN CRANE-HOUDAILLE INC MARINE & GOVERNMENT GROUP

Address:6400 OAKTON ST ; FORMERLY PACKING CO

Box:City:MORTON GROVE

State:IL

ZIP:60053-2725

Country:US

Phone:708-967-2400/2879

CAGE:71724

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ASBESTOS, CHRYSOTILE

CAS:12001-29-5

RTECS #:CI6478500

Othe

r REC Limits:NONE RECOMMENDED  
OSHA PEL:0.2 FIBERS/CC  
ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:NICKEL (SARA III)  
CAS:7440-02-0  
RTECS #:QR5950000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:1 MG/M3; 9293

Ingred Name:CHROMIUM (SARA III)  
CAS:7440-47-3  
RTECS #:GB4200000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1 MG/M3  
ACGIH TLV:0.5 MG/M3; 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:IRON OXIDE  
CAS:1309-37-1  
RTECS #:NO7400000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:1  
0 MG/M3 (FE)  
ACGIH TLV:5 MG/M3(FE),B2; 9293

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:ACUTE:MINOR EYS/SKIN IRRITATION.  
INGESTION- IRRITATION OF GI TRACT. INHALATION-IRRITATION OF  
RESPIRATORY TRACT. CHRONIC: ASBESTOSIS, LUNG CANCER, &  
MESOTHELIOMA, ALL OF WHICH ARE DISABLING AND FATAL D ISEASES OF THE  
LUNG. I  
NHALATION AND INGESTION OF ASBESTOS FIBERS MAY CAUSE CANCER  
OF THE BOWEL.  
Explanation of Carcinogenicity:CONTAINS ASBESTOS [12001-29-5] WHICH IS  
LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN.  
Effects of Overexposure:INHALATION: FATIGUE AND SHORTNESS OF BREATH  
THAT GETS WORSE WITH TIME AND EVENTUALLY BECOMES DISABLING. EYES:  
IRRITATION. SKIN: IRRITATION. INGESTION: MILD STOMACH DISTRESS.  
DIARRHEA, VOMITING, AND NA USEA.  
Medical Cond Aggravated by Exposure:ASTHMA

, EMPHYSEMA, AND TUBERCULOSIS  
ARE ALL GENERALLY AGGRAVATED BY EXPOSURE TO ASBESTOS FIBERS.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. SEE DOCTOR. EYES: RINSE THOROUGHLY WITH WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEE DOCTOR. INGESTION: DILUTE WITH WATER. DO NOT INDUCE VOMITING.SEE DOCTOR.

=====  
Fire Fighting Measures  
=====

Flash Point:NOT REQUIRED

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VACUUM THE MATERIAL WITH A HEPA FILTERED VACUUM

. THE EQUIPMENT SHALL BE USED & EMPTIED SO AS TO MINIMIZE THE RE-ENTRY OF ASBESTOS INTO THE WORKPLACE. OTHERWISE, WET THE MATERIAL WITH WATER & SURFACTANT AND THEN SHOVEL OR MOP UP CONTAMINATION.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:ITEM IS NONFRIABLE & WILL NOT SHED FIBERS IN NORMAL USE AND STORAGE. USED ITEMS SHALL BE WETTED BEFORE, DURING & AFTER DISASSEMBLY.

Other Precautions:IF IT IS NECESSARY TO CUT OR IMPACT THE ITEM WHILE

INSTALLING IT, WEAR A RESPIRATOR AND PROTECTIVE CLOTHING. USED ITEMS SHALL BE IDENTIFIED AND DISPOSED OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED HEPA RESPIRATOR IF REQUIRED. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST SUFFICIENT TO ENTRAIN ALL PARTIC

ULATE

EMISSIONS. HEPA FILTER REQUIRED. NO LEAKS ON PRESSURE SIDE OF FAN.

Protective Gloves:COTTON OR LEATHER

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:USE COVERALLS OR DISPOSABLE CLOTHING.

Work Hygienic Practices:WET WORK TO THE DEGREE POSSIBLE. WASH HANDS

AFTER HANDLING ITEM. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

MSDS GENERATED BY HMIS TECHNICIAN. WHEN HMIS IS ABLE TO OBTAIN AN MSDS FROM MANUFACTURER, THIS RECORD WILL BE

UPDATED. INGREDIENTS ARE

FROM PARTSMASTER TECHNICAL CHARACTERISTICS. MSDS GENERATED FOR TECHNICAL SUPPORT. DLA CONTRACT: DLA500-83-M-EF17.

===== Physical/Chemical Properties =====

HCC:T6

Solubility in Water:INSOLUBLE

Appearance and Odor:BRAIDED AND SOLID

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG MINERAL ACIDS, AND STRONG ALKALIS

Stability Condition to Avoid:ACCUMULATIONS OF DUST  
Hazardous Decomposition Products:ASBESTOS DUST

===== Disposal Considerations =====

Waste Disposal Methods:WET THE MATERIAL WITH WATER AND SURFACTANT. PLACE IN 6 MIL THICK POLYETHYLENE PLASTIC BAG. PLACE THESE BAGS INTO ANOTHER POLY BAG OR A SAFE PLACE UNTIL IT CAN BE SHIPPED TO AN APPROVED DISPOSAL SITE. IDENTIFY WITH ASBESTOS CANCER WARNING LABEL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.