

TRIANGLE COATINGS, INC. -- VARNISH, INTERIOR, ALKYD RESIN -- 8010-00-168-8810
===== Product Identification =====

Product ID:VARNISH, INTERIOR, ALKYD RESIN
MSDS Date:11/12/1992
FSC:8010
NIIN:00-168-8810
MSDS Number: BRKBM
=== Responsible Party ===
Company Name:TRIANGLE COATINGS, INC.
Address:1930 FAIRWAY DRIVE
City:SAN LEANDRO
State:CA
ZIP:94577-5631
Country:US
Info Phone Num:415-895-8000
Emergency
Phone Num:415-284-9031 800-424-9300(CHEMTREC)
Preparer's Name:NB
CAGE:0GB20
=== Contractor Identification ===
Company Name:TRIANGLE COATINGS INC
Address:1930 FAIRWAY DR
Box:City:SAN LEANDRO
State:CA
ZIP:94577-5631
Country:US
Phone:800-895-8000
CAGE:0GB20

===== Composition/Information on Ingredients =====

Ingred Name:HYDROCARBON MIXTURE (VAPOR PRESSURE 2.0 MM HG @ 20C)
CAS:64741-41-9
Fraction by Wt: 50%
Other REC Limits:NONE SPECIFIED
OSHA PEL:TWA 100 PPM
ACGIH TLV:STEL 200 P

PM

Ingred Name:PROPOXYPROPANOL (VAPOR PRESSURE 1.7 MM HG @ 20C)

CAS:1569-01-3

RTECS #:UB9351000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC 4.16 LB/GAL; 498 G/L

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: PROLONGED & REPEATED LIQUID CONTACT CAN

CAUSE DEFATTING & DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION & DERMATITIS. TESTS SHOW OVERXPO MAY CAUSE BLOOD DISORDERS & NEUROLOGIC DISORDERS . REPORTS HAVE ASSOCIATED REPEATED/PROLONG OCCUPATIONAL OVEREXPO TO SOLVENTS W/PERMANENT BRAIN/NERVOUS SYSTEM DAMAGE.

Effects of Overexposure:EYES: SHORT-TERM CONTACT SLIGHT IRRITATION. PROLONGED & REPEATED CONTACT MAY BE MORE IRRITATING. ACUTE TOXICITY: OVEREXPO CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION PRODUC

ING SUCH EFFECTS AS HEADACHE, DIZZINESS, NAUSEA, & LOSS OF CONSCIOUSNESS. INTENTIONAL MISUSE OF THIS PRODUCT MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYES: FLUSH W/WATER FOR 15 MIN. WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN: WASH W/SOAP & WATER. IF PERSISTENT IRRITATION OCCURS, GET MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR & PROVIDE OXYGEN IF BREA

THING IS DIFFICULT. GIVE CPR IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTION: GET MEDICAL ATTENTION IMMEDIATELY. DON'T GIVE ANYTHING TO UNCONSC.PERSON. DON'T INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:SCC

Flash Point:107F,42C

Autoignition Temp:Autoignition Temp Text:445 F

Lower Limits:1.0 %

Upper Limits:16.9 %

Extinguishing Media:WATER FOG, FOAM, DRY CHEMICAL, CO2.

Fire Fighting Procedures:EVACUATE HAZARD AREA OF UNPR

OTECTED PERSONNEL.

WEAR PROTECTIVE CLOTHING PLUS A NIOSH APPROVED SCBA. COOL CONTAINERS W/WATER. AVOID SPREADING LIQUID WITH WATER.

Unusual Fire/Explosion Hazard:THIS MATERIAL IS FLAMMABLE AND MAY BE IGNITED BY HEAT, SPARKS, FLAME OR STATIC ELECTRICITY.

===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND & AWAY FROM SPILL. KEEP ALL SOURCES OF IGNITION & HOT METAL SURFACES AWAY FROM SPILL. IF SPILL IS INDOORS, VENTILATE AREA OF SPILL. IF LARGE SPILL, CALL SPILL RESPONSE TEAM. NOTIFY APPROPRIATE STATE/LOCAL AGENCIES.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT. KEEP CONTAINERS TIGHTLY CLOSED. STORE IN COOL DRY PLACE W/ADEQUATE EXPLOSION-PROOF VENTILATION. GROUND EQUIPMENT TO PREVENT STATIC CHARGE

Other Precautions:DO NOT WELD, HEAT OR SPILL ON OR NEAR CONTAINER, EVEN EMPTIED CONTAINERS CAN CONTAIN EXPLOSIVE VAPORS. IF POURING OR

TRANSFERRING MATERIALS, CONTAINERS MUST BE BONDED AND GROUNDED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:DEPENDING ON THE NATURE AND CONCENTRATION OF THE AIRBORNE MATERIAL, USE A RESPIRATOR OR GAS MASK WITH APPROPRIATE CARTRIDGES AND CANNISTERS (NIOSH APPROVED, IF AVAILABLE) OR SUPPLIED AIR EQUIPMENT.

Ventilation:EXPLOSION-PROOF VENTILATION REQUIRED TO CONTROL VAPOR CONCENTRATIONS BELOW EXPOSURE LIMITS. EXHAUST SYSTEMS MAY BE REQ'D

Protective Gloves:WEAR IMPERVIOUS GLOVES

Eye Protection:WEAR CHEMICAL GOGGLES

Other Protective Equipment:WEAR PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH W/SOAP & WATER BEFORE EATING, DRINKING, SMOKING, USING RESTROOM FACILITIES. WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:301 TO 395F

Decomp Temp:Decomp Text:

500F,260C

Vapor Density:> AIR

Viscosity:C-F GARDNER

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBER LIQUID WITH MILD AROMATIC SOLVENT

Percent Volatiles by Volume:59.6

Corrosion Rate:NON

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID HEAT, SPARKS, AND OPEN FLAME. AVOID

CONTACT WITH A

LKALIES, AQUEOUS ACIDS, AMINES, AND ACIDIC ALCOHOLS.

Hazardous Decomposition Products:THERMAL DECOMPOSITION IN THE PRESENCE

OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH LOCAL,
STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department

o

f Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.