

SAF-T-LOK CHEMICAL CORPORATION -- ANAEROBIC ADHESIVE/SEALANT R01 -- 8030-00-180-6222

=====
Product Identification
=====

Product ID:ANAEROBIC ADHESIVE/SEALANT R01
MSDS Date:05/01/1993
FSC:8030
NIIN:00-180-6222
MSDS Number: BRKBS
=== Responsible Party ===
Company Name:SAF-T-LOK CHEMICAL CORPORATION
Address:300 EISENHOWER LANE NORTH
City:LOMBARD
State:IL
ZIP:60148
Country:US
Info Phone Num:708-971-2001
001
Emergency Phone Num:708-971-2001
CAGE:4Z400
=== Contractor Identification ===
Company Name:SAF-T-LOK CHEMICAL CORPORATION
Address:300 EISENHOWER LANE NORTH
City:LOMBARD
State:IL
ZIP:60148
Country:US
Phone:708-971-2001
CAGE:4Z400

=====
Composition/Information on Ingredients
=====

Ingred Name:"NOT HAZARDOUS"
Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Repo

Health Hazards Acute and Chronic:ORGANIC PEROXIDE HAS BEEN REPORTED TO CAUSE TUMORS IN EXPERIMENTAL ANIMALS WHEN INJECTED UNDER THE SKIN.
THE LOW CONCENTRATION (250F,>121C
Autoignition Temp:Autoignition Temp Text:> 350F
Extinguishing Media:CO2, FOAM, DRY CHEMICALS
Fire Fighting Procedures:AIR MASK AND PROCEDURES FOR FIGHTING CHEMICAL FIRES.
Unusual Fire/Explosion Hazard:CONTAINS ORGANIC PEROXIDE

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE GOOD VENTILATION. AVOID EYE AND SKIN CONTACT. SOAK UP SPILL WITH EARTH, SAND, OR ABSORBENT PRODUCT (ZORBAL). RECOVER IN CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F FOR PROLONGED SHELF LIFE. STORE IN ORIGINAL CONTAINER.
Other Precautions:AVOID PROLONGED SKIN CONTACT

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY NECESSARY, BUT PRODUCT SHOULD BE USED IN AREAS OF GOOD VENTILATION.
Ventilation:LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>300F,>149C
Decomp Temp:Decomp Text:>350F,>177C
Vapor Pres: