

CON-LUX COATINGS INC -- ENAMEL, ALKYD, GLOSS RED 11105 -- 8010-00-616-7487
===== Product Identification =====

Product ID:ENAMEL, ALKYD, GLOSS RED 11105

MSDS Date:01/13/1984

FSC:8010

NIIN:00-616-7487

MSDS Number: BRKGN

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:908-287-4000 / FAX 908-287-9288

Emergency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 2 MM HG @ 68F) (LEL 1.0)

Fraction by Wt: 49.4%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:500 PPM

Ingred Name:MOLYBDATE ORANGE

CAS:12656-85-8

RTECS #:QA460000

0

Fraction by Wt: 7.8%

Other REC Limits:0.2 MG/M3 AS PB

ACGIH TLV:0.1 MG/M3 AS CRO3

=====
Hazards Identification
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS, IN SOME INSTANCES, MAY IRRITATE RESPIRATORY TRACT AND CAUSE HEADACHE OR DIZZINESS, WHICH IS NORMAL FOR SOLVENT BASE PRODUCTS.

=====
First
Aid Measures
=====

First Aid:FLUSH SKIN AND EYE CONTACT WITH PLENTY OF WATER. IF INHALED, REMOVE TO FRESH AIR. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:105F,41C
Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER MIST.
Fire Fighting Procedures:SMOTHER FLAMES WITH ONE OF THE ABOVE EXTINGUISHING MEDIA. WATER MAY BE USED TO COOL DOWN CLOSED CONTAINERS IN VICINITY.
Unusual Fire/Explosion Hazard:CONTAINS FLAMMABLE SOLVENT. DO NOT USE IN AREAS WHERE SPARKS OR OPEN FLAMES ARE PRESENT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID PROLONGED BREATHING OF VAPORS. VENTILATE AREA. CLEAN UP WITH ABSORBENT MATERIAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED AND PROTECTED F

OR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS

Other Precautions:COMBUSTIBLE LIQUID

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OPEN AREAS, USE NIOSH APPROVED FILTER RESPIRATOR TO REMOVE SOLID AIR-BORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION. IN RESTRICTED AREAS USE NIOSH APPROVED CHEMICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICULATE & VAPOR.

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves:REQUIRE

D FOR LONG OR REPEATED EXPOSURE

Eye Protection:USE SAFETY EYEWEAR/FULL-FACE SHIELD

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT WITH CONTAMINATED CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:323F,162C

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:63

===== Stability and Reactivity Data =====

Stability Indic

ator/Materials to Avoid:YES

Hazardous Decomposition Products:CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. DO NOT INCINERATE UNOPENED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or impl

ied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.