

CON-LUX COATINGS, INC. -- ENAMEL, ODORLESS, ALKYD, INTERIOR, SEMI-GLO --  
8010-00-935-3995

=====  
===== Product Identification =====

Product ID:ENAMEL, ODORLESS, ALKYD, INTERIOR, SEMI-GLO

MSDS Date:05/01/1993

FSC:8010

NIIN:00-935-3995

MSDS Number: BRKJP

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-

287-4000

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name:ED DOENGES

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====  
===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS (STODDARD SOLVENT)

CAS:8052-41-3

Fraction by Wt: 28.8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred

Name:CALCIUM CARBONATE (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 14.1%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 18.8%

Other REC Limits:NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ALUMINUM SILICATE (KAOLIN)

CAS:1318-74-7

Fraction by Wt: 9.4%

Other REC Limits:NONE SPECIFIED

OSHA PEL:10 MG/M3

ACGIH TLV:10 MG/M3

=====  
Hazard Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE; IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT.  
CHRONIC; REPORTS HAVE ASSOCIATED PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.  
Effects of Overexposure:HEADACHE, NAUSEA, AND DIZZINESS.

=====  
==== First Aid Measures =====

First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE RESPIRATION, IF NECESSARY, TREAT SYMPTOMATICALLY. EYE CONTACT: FLUSH IMMEDIATELY WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY.

=====  
==== Fire Fighting Measures =====

Flash Point:120F,49C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:CO2, DRY CHEMICAL

Fire Fighting Procedures:USE SCBA. WATER SPRAY MAY BE USEFUL IN

MINIMIZING VAPORS & COOLING CONTAINERS EXPOSED TO HEAT AND FLAMES.

Unusual Fire/Explosion Hazard:NO INFORMATION FOUND.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR

APPROPRIATE PERSONAL PROTECTION EQUIPMENT AND APPROVED RESPIRATOR.

CONTAIN SPILL

& PUT IN VAPOR TIGHT CONTAINERS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN AREAS TO COMPLY WITH

ANSI-NFPA 30 FLAMMABLE AND COMBUSTIBLE LIQUIDS CODE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPROVED NIOSH/MSHA ORGANIC VAPOR  
RESPIRATOR.

Ventilation:SUFFICIENT VENT TO KEEP HAZARDOUS MATERIALS BELOW  
APPLICABLE EXPOSURE LEVELS.

Protective Gloves:NEOPRENE

Eye Prot

ection:SPLASH SHIELDS

Work Hygienic Practices:WASH HANDS PROPERLY BEFORE EATING, DRINKING, OR  
USING WASHROOM FACILITIES.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:346F,174C

Vapor Pres:2

Vapor Density:>1

Spec Gravity:1.274

Viscosity:67 - 77 KU

Solubility in Water:N/L

Appearance and Odor:LIQUID, ALIPHATIC ODOR

Percent Volatiles by Volume:49.4

===== Stability and Reactivity Data =====

St

ability Indicator/Materials to Avoid: YES  
STRONG OXIDIZERS  
Stability Condition to Avoid: HEAT, OPEN FLAME  
Hazardous Decomposition Products: CO, CO2

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,  
AND LOCAL REGULATIONS. EPA HAZARDOUS WASTE NUMBER: D001.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense.

The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.