View NSN Online: https://aerobasegroup.de/nsn/8010-00-935-3995

CON-LUX COATINGS, INC. -- ENAMEL, ODORLESS, ALKYD, INTERIOR, SEMI-GLO 8010-00-935-3995

============= Product Identification =================

Product ID:ENAMEL, ODORLESS, ALKYD, INTERIOR, SEMI-GLO

MSDS Date:05/01/1993

FSC:8010

NIIN:00-935-3995

MSDS Number: BRKJP === Responsible Party ===

Company Name: CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

City:EDISON State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-

287-4000

Emergency Phone Num:800-424-9300 CHEMTREC

Preparer's Name: ED DOENGES

CAGE:60189

=== Contractor Identification ===

Company Name: CON-LUX COATINGS INC

Address: 226 TALMADGE RD

Box:847 City:EDISON State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS (STODDARD SOLVENT)

CAS:8052-41-3

Fraction by Wt: 28.8%

Other REC Limits: NONE SPECIFIED

OSHA PEL:500 PPM

ACGIH TLV:100 PPM; 9293

Ingred

Name:CALCIUM CARBONATE (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 14.1% Other REC Limits:NONE SPECIFIED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3
Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 18.8% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293
Ingred Name:ALUMINUM SILICATE (KAOLIN) CAS:1318-74-7 Fraction by Wt: 9.4% Other REC Limits:NONE SPECIFIED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3
======================================
azards Identification ====================================
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE; IRRITATION OF EYES AND SKIN MAY OCCUR WITH OVEREXPOSURE. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT. CHRONI C; REPORTS HAVE ASSOCIATED PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. Effects of Overexposure:HEADACHE, NAUSEA, AND DIZZINESS.
=======================================
==== First Aid Measures ==================
First Aid:INHALATION: REMOVE VICTIM TO FRESH AIR. RESTORE RESPIRATION, IF NECESSARY, TREAT SYMPTOMATICALLY. EYE CONTACT: FLUSH IMMEDIATELY WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. CONSULT A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY.

Lower Limits: 1.0
Upper Limits:6.0
Extinguishing Media:CO2, DRY CHEMICAL
Fire Fighting Procedures: USE SCBA. WATER SPRAY MAY BE USEFUL IN
MINIMIZING VAPORS & COOLING CONTAINERS EXPOSED TO HEAT AND FLAMES. Unusual Fire/Explosion Hazard:NO INFORMATION FOUND.
Unusual File/Explosion Hazard:NO INFORMATION FOUND.
======== Accidental Release Measures =========
Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. WEAR APPROPRIATE PERSONAL PROTECTION EQUIPMENT AND APPROVED RESPIRATOR CONTAIN SPILL & PUT IN VAPOR TIGHT CONTAINERS.
CTOTIN VIII ON HOITI CONTINUENCE.
========== Handling and Storage ============
Handling and Storage Precautions:STORE IN AREAS TO COMPLY WITH ANSI-NFPA 30 FLAMMABLE AND COMBUSTIBLE LIQUIDS CODE.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:USE APPROVED NIOSH/MSHA ORGANIC VAPOR RESPIRATOR.
Ventilation:SUFFICIENT VENT TO KEEP HAZARDOUS MATERIALS BELOW APPLICABLE EXPOSURE LEVELS. Protective Gloves:NEOPRENE
Eye Prot
ection:SPLASH SHIELDS
Work Hygienic Practices:WASH HANDS PROPERLY BEFORE EATING, DRINKING, OR USING WASHROOM FACILITIES. Supplemental Safety and Health
Supplemental Salety and Health
========= Physical/Chemical Properties ==========
Boiling Pt:B.P. Text:346F,174C
Vapor Pres:2 Vapor Density:>1
Spec Gravity:1.274
Viscosity:67 - 77 KU
Solubility in Water:N/L
Appearance and Odor:LIQUID, ALIPHATIC ODOR Percent Volatiles by Volume:49.4
========= Stability and Reactivity Data =========

St

====== Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS. EPA HAZARDOUS WASTE NUMBER: D001.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense.

The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.