View NSN Online: https://aerobasegroup.de/nsn/9140-00-286-5294

Product ID: DIESEL FUEL NO.2 GRADE MSDS Date:09/01/1992 FSC:9140 NIIN:00-286-5294 MSDS Number: BRLXH === Responsible Party === Company Name: DREYFUS LOUIS ENERGY CORP Address:8800 ROSWELL ROAD SUITE 200 City:ATLANTA State:GA ZIP:30350 Country:US Info Phone Num:404-594-3500 **Emergency Phone Num:4** 04-594-3500 CAGE:OGYU1 === Contractor Identification === Company Name: DREYFUS LOUIS ENERGY CORP (404-594-3500 Address:8800 ROSWELL RD SUITE 200 Box:City:ATLANTA Phone:404-594-3500 CAGE:OGYU1 Company Name: LOUIS DREYFUS ENERGY CORP Address:8800 ROSWELL RD SUITE 200 Box:City:ATLANTA State:GA ZIP:30350 Country:US Phone:404-594-3500 CAGE:0GYU1 Company Name: TERRELL OIL CO Address:3804 COCONUT PALM DR SUITE 185 Box:City:TAMPA State:FL ZIP:33619-1352 Country:US Phone:813-626-2842 CAGE:0A777

==========

Ingred Name: ALIPHATIC PETROLEUM DISTILLATES CAS:68476-30-2 Other REC Limits:NONE RECOMMENDED LD50 LC50 Mixture:ORAL LD50 (RAT) IS > 5 ML/KG Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYE-NOT EXPECTED TO CAUSE PROLONGED EYE IRRITATION. SKIN-MODERATE SKIN IRRITANT. IN HALATION-PROLONGED BREATHING OF VAPORS CAN CAUSE CENTRAL NERVOUS SYSTEM EFFECTS. INGESTION-IF SWALLOWED, THIS SUBSTAN CE IS CONSIDERED PRACTICALLY NON-TOXIC TO INTERNAL ORGANS. Explanation of Carcinogenicity:NOT CARCINOGENIC. Effects of Overexposure: SKIN-PAIN OR A FEELING OF HEAT, DISCOLORATION, SWELLING AND BLISTERING. INHALATION-HEADACHE, DIZZINESS, LOSS OF APPETITE, WEAKNESS AND LOSS OF COORDINATION. INGESTION-ASPIRATION HAZARD. ONCE IN THE LU NGS, THE SUBSTANCE IS VER **Y DIFFICULT** TOREMOVE & CAN CAUSE SEVERE INJURY & DEATH. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE-NO FIRST AID REQUIRED. FLUSH EYES WITH FRESH WATER. SKIN-WASH SKIN THOROUGHLY WITH SOAP & WATER. INHALATION-MOVE THE PERSON TO FRESH AIR. SEE DOCTOR. INGESTION-GIVE ATER OR MILK TO DRINK & CALL FO R MEDICAL ADVICE. DO NOT MAKE PERSON VOMIT UNLESS DIRECTED BY MEDICAL PERS ONNEL. TAKE PERSON TO NEAREST MEDICAL

EMERGENCY TREATMENT CENTER OR HOSPITAL.

Flash Point Method:PMCC Flash Point:130F,54C Autoignition Temp:Autoignition Temp Text:NDA Lower Limits:0.6 Upper Limits:4.7 Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND WATER FOG. Fire Fighting Procedures:FOR FIRES INVOLVING THIS MATERIAL, DO NOT ENTER ANY ENCLOSED OR CONFINED FIRE SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT (SELF-CONTAINED BREATHING APPARATUS). Unusual Fire/Explosion Hazard:LIQUID EVAPORATES & FORMS VAPOR WHICH CAN CATCH FIRE & BURN WITH EXPLOSIVE VIOLENCE. INVISIBLE VAPOR SPREADS EASILY & CAN BE SET ON FIRE BY MANY SOURCES.

Spill Release Procedures: ELIMINATE ALL SOURCES OF IGNITION. CLEANUP SPILL IMMEDIATELY. THIS MATERIAL IS CONSIDERED TO BE A WATER POLLUTANT. RELEASE OF THIS PRODUCT SHOULD BE PREVENTED FROM

CONTAMINATING SOIL & WATER & FROM EN TERING DRAINAGE & SEWER SYSTEMS.

Handling and Storage Precautions:DO NOT USE OR STORE NEAR FLAME, SPARKS OR HOT SURFACES. USE ONLY IN WELL VENTILATED AREA. KEEP CONTAINER CLOSED.

Other Precautions:DO NOT WELD, HEAT OR DRILL CONTAINER. REPLACE CAP OR BUNG. EMPTIES CONTAINER STILL CONTAINS HAZARDOUS OR EXPLOSIVE VAPOR OR LIQUID. CAUTION! DO NOT USE PRESSURE TO EMPTY DRUM OR DRUM MAY

RUPTURE WITH EXPLOSIVE FORCE.

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NO SPECIAL RESPIRATORY PROTECTION IS NORMALLY REQUIRED. HOWEVER, IF OPERATING CONDITIONS CREATE HIGH AIRBORNE CONCENTRATIONS, THE USE OF AN APRROVED RESPIRATOR IS RECOMMENDED. Ventilation:USE THIS MATERIAL ONLY IN WELL VENTILATED AREAS. Protective Gloves:WEAR PROTECTIVE GLOVES. Eye Protection:NO SPECIAL PROTECTION USUALLY NEEDED. Other Protective Eq uipment:AVOID CONTACT WITH SKIN OR CLOTHING. SKIN CONTACT SHOULD BE MINIMIZED BY WEARING PROTECTIVE CLOTHING. Work Hygienic Practices:DISCARD CONTAMINATED NON-WATER PROOF SHOES AND BOOTS. WASH CONTAMINATED CLOTHING. Supplemental Safety and Health NOTE TP PHYSICIAN: INGESTION OF THIS PRODUCT OR SUBSEQUENT VOMITING CAN RESULT IN ASPIRATION OF LIGHT HYDROCARBON LIQUID, WHICH CAN CAUSE PNEUMONITIS.

HCC:F4 Boiling Pt:B.P. Text:304-574F Vapor Pres:0.40 Vapor Density:4.7 Spec Gravity:0.84-0.89 Viscosity:1.9-4.1 CST Evaporation Rate & amp; Reference:0.04 BUTYL ACETATE=1 Solubility in Water:INSOLUBLE Appearance and Odor:WATER WHITE TO CLEAR YELLOW OILY LIQUID WITH MILD PETROLEUM ODOR. Percent Volatiles by Volume:NEGL

Stability Indicator/Materials to Avoid:YES

MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, NITRATES, PEROXI

DES, ETC.

Stability Condition to Avoid:FIRE HAZARD IS GREATER AS LIQUID TEMPERATURES RISES ABOVE 85F.

Hazardous Decomposition Products:NORMAL COMBUSTION FORMS CARBON DIOXIDE & WATER VAPOR; INCOMPLETE COMBUSTION CAN PRODUCE CARBON MONOXIDE.

Waste Disposal Methods:CLEAN UP SPILL USING APPROPRIATE TECHNIQUE SUCH AS SORBENT MATERIAL OR PUMPING. WHERE FEASIBLE & APPROPIATE, REMOVE CONTAMINATED SOIL. PLACE CONTAMINAT ED MATERIAL IN DISPOSABLE CONTAINERS & DISPOSE OF IN A MANNER CONSISTENT WITH APPLICABLEREGULATION

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional adv ice to verify and assume responsibility for the suitability of this information to their particular situation.