

ROSES QUALITY PAINT, DBA ROSE TALBERT PAINT CO. -- PREMIUM VELVET VINYL LATEX FLAT-LTB -- 8010-00-579-9533

===== Product Identification =====

Product ID:PREMIUM VELVET VINYL LATEX FLAT-LTB

MSDS Date:10/30/1992

FSC:8010

NIIN:00-579-9533

MSDS Number: BRLYF

==== Responsible Party ===

Company Name:ROSES QUALITY PAINT, DBA ROSE TALBERT PAINT CO.

Address:901 FRINK STREET

City:CAYCE

State:SC

ZIP:29033

Cou

ntry:US

Info Phone Num:803-796-0324

Emergency Phone Num:803-796-0324

Preparer's Name:DOD/HMIS (DGSC-SSH)

CAGE:GO531

==== Contractor Identification ===

Company Name:ROSE TALBERT PAINT CO

Address:901 FRINK ST

Box:City:CAYCE

State:SC

ZIP:29033

Country:US

Phone:803-796-0324

CAGE:0CUY5

Company Name:ROSES QUALITY PAINT INC DBA ROSE TALBERT PAINT CO

Address:901 FRINK ST

City:CAYCE

State:SC

ZIP:29033-5000

Country:US

Phone:803-796-0324

CAGE:GO531

===== Composition/Information on Ingredients ===

=====

Ingred Name:TITANIUM DIOXIDE  
CAS:13463-67-7  
RTECS #:XR2275000  
Fraction by Wt: 15.42%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:15 MG/M3 TDUST  
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ETHYLENE GLYCOL (SARA III)  
CAS:107-21-1  
RTECS #:KW2975000  
Fraction by Wt: 1.82%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:C 50 PPM  
ACGIH TLV:C 50 PPM,VAPOR; 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:LEAD (SARA III)  
CAS:7439-92-1  
RTECS #:OF7525000  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:  
0.05 MG/M3;1910.1025  
ACGIH TLV:0.15 MG/M3;DUST 9293  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:CHROMATES  
Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: PULMONARY EDEMA MAY  
DEVELOPE WITH INHALATION OF HIGH CONCENTRATIONS. THIS MATE

RIAL MAY

CAUSE NOSE AND THROAT IRRITATION. EYES: THIS PRODUCT CAN BE IRRITATING TO THE EYES. SKIN: MAY CAUSE SKIN IRRITATION AND DRYING/DEFATTING OR CRACKING AND DERMATITIS ON REPEATED OR PROLONGED EXPOSURE TO THE SKIN.

Explanation of Carcinogenicity: MANUFACTURER STATE THIS PRODUCT CONTAINS NO REPORTED CARCINOGENS OR SUSPECTED CARCINOGENS.

Effects of Overexposure: EYE, SKIN AND LUNG IRRITATION. CONTINUED BREATHING OF VAPORS MAY IRRITATE RESPIRATORY TRACT CAUSING HEADACHE.

CHE, NAUSEA AND DIZZINESS. THIS PRODUCT MAY BE FATAL FROM SWALLOWING LARGE AMOUNTS. MAY CAUSE NAUSEA, VOMITING, HEADACHES, DIZZINESS, STUPOR, AND KIDNEY DAMAGE. INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure: PERSONS WITH A HISTORY OF AILMENTS OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, RESPIRATORY TRACT OR KIDNEY MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

Firs

t Aid: INHALATION: REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING. CONTACT A PHYSICIAN IMMEDIATELY. EYES: IMMEDIATELY FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. CONTACT A PHYSICIAN IMMEDIATELY. INGESTION: DO NOT INDUCE VOMITING. RINSE MOUTH IMMEDIATELY. GIVE 6 TO 8 OUNCES OF WATER IF CONSCIOUS. GET PHYSICIAN IMMEDIATE

===== Fire Fighting Measures =====

=

Flash Point Method: TCC

Flash Point: 241F, 116C

Lower Limits: 3.2

Upper Limits: 15.3

Extinguishing Media: CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION. USE FOG NOZZLES WITH WATER.

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN HEATED.

EN EXPOSED TO EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND AND AWAY FROM SPILL UNLESS WEARING APPROPRIATE PROTECTIVE EQUIPMENT. STOP AND/OR CONTAIN DISCHARGE IF IT MAY BE DONE SAFELY. KEEP ALL SOURCES OF IGNITION AWAY. VENTILATE AREA OF SPILL. USE NON-SPARKING TOOLS FOR CLEANUP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling an

d Storage Precautions:KEEP PRODUCT CONTAINERS COOL, DRY AND AWAY FROM SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE VENTILATION. DO NOT SMOKE IN STORAGE AREA.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. NOTICE: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIO

SH/MSHA APPROVED RESPIRATORS TO REMOVE SOLID AIRBORNE PARTICLES OF OVER SPRAY DURING SPRAY APPLICATIONS. IN RESTRICTED VENTILATION AREAS USE NIOSH/MSHA APPROVED RESPIRATOR DESIGNED TO REMOVE BOTH PARTICLES AND VAPOR.

Ventilation:SUFFICIENT VENTILATION IN VOLUME AND PATTERN SHOULD BE PROVIDED TO KEEP AIR CONTAMINATION BELOW OSHA'S CURRENT PELS.

Protective Gloves:NATURAL RUBBER, NEOPRENE, NITRILE

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:PR

EVENT PROLONGED SKIN CONTACT BY USING AN APRON.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING WASHROOM FACILITIES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

THIS PRODUCT CONTAINS THE FOLLOWING TOXIC CHEMICAL SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372. ETHYLENE GL YCOL, CAS NUMBER 107-21-1, % BY WEIGHT=1.82%. \*\*THIS MSDS COPIED

FROM ONE OF A SIMILAR PRODUCT FROM THE SAME MFR.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:379F,193C

Vapor Pres:10 @68F

Appearance and Odor:LIQUID

Percent Volatiles by Volume:47

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS

Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES AND OTHER SOURCES  
OF IGNITION

Hazardous Decomposition Products:MAY PRODUCE HAZA

RDOUS FUMES, INCLUDING

CARBON DIOXIDE, CARBON MONOXIDE AND OXIDES OF NITROGEN.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS. DO NOT INCINERATE  
CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in n

o manner whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.