View NSN Online: https://aerobasegroup.de/nsn/6850-01-353-4464

CANON USA INC -- TONER CYAN FOR CLC 200/300, F41-6811-100 -- 6850-01-353-4464

Product ID:TONER CYAN FOR CLC 200/300, F41-6811-100

MSDS Date:12/01/1991

FSC:6850

NIIN:01-353-4464

MSDS Number: BRMCQ === Responsible Party ===

Company Name: CANON USA INC Address: ONE CANON PLAZA

City:LAKE SUCCESS

State:NY ZIP:11042 Country:US

Info Phone Num:516-488-6700

Emergency Phone

Num:800-424-9300 (CHEMTREC)

CAGE:1BA63

=== Contractor Identification ===

Company Name: AUTOMATION AIDS INC (800-234-2790)

Address: 420 BABYLON RD, SUITE B

Box:UNKNOW City:HORSHAM State:PA

State:PA ZIP:19044 Country:US

Phone:800-817-4448

CAGE:01QM9

Company Name: CANON USA INC

Address:ONE CANON PLZ Box:City:NEW HYDE PARK

State:NY ZIP:11042 Country:US

Phone:516-328-5000; 5600

CAGE:08YZ7

Company Name: CANON USA INC Address: ONE CANON PLAZA Box: City: LAKE SUCCESS

State:NY ZIP:11042

Country:US

Phone:516-328-5600

CAG

E:1BA63
======= Composition/Information on Ingredients ========
Ingred Name:POLYESTER RESIN CAS:39382-25-7 Fraction by Wt: 85-95% OSHA PEL:N/K ACGIH TLV:N/K
Ingred Name:PIGMENTS Fraction by Wt: 3-10% OSHA PEL:N/K ACGIH TLV:N/K
Ingred Name:SALICYLIC ACID CHELATE; (SALICYLIC ACID CHROMIUM (III) CHELATE) CAS:72869-85-3 Fraction by Wt: 1-5% OSHA PEL:N/K ACGIH TLV:N/K
======================================
LD50 LC50 Mixture:>5.0 G/KG (ORAL, R AT) Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INHAL: TONER IS FINELY DIVIDED SOLID. DO NOT BREATHE DUST. EYES: NO SPECIFIC HAZARD IS KNOWN TO CANON HOWEVER, ANY MATERIAL THAT CONTACTS THE EYE MAY BE IRRITATING. SKIN: LOW HAZARD FOR INDUSTRIAL HA NDLING. MUTAGENICITY: NEGATIVE (TEST SPECIES S. TYPHIMURIUM). Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:SEE HEA LTH HAZARDS. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.
======================================

First Aid:INHAL: REMOVE FROM EXPOSURE TO FRESH AIR. EYE: OPEN EYE & FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MIN. IF IRRITATION PERSISTS, GET MED ATTN. SKIN: WASH WITH SOAP & WATER. INGEST: DRINK SEVERAL GLAS SES OF WATER. CALL MD.

Extinguishing Media:CARBON DIOX

IDE, WATER, DRY CHEMICALS. Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard: THIS MATERIAL, LIKE MOST ORGANIC MATERIAL IN POWDER FORM, IS CAPABLE OF CREATING A DUST EXPLOSION. ========= Accidental Release Measures ============= Spill Release Procedures: SWEEP MATERIAL ONTO PAPER AND PLACE IN FIBER CARTON. Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. _____ Handling and Storage Precautions: STORE IN ROOM BELOW 40C. Other Precautions: KEEP OUT OF REACH OF CHILDREN. KEEP AWAY FROM CONTACT WITH OXIDIZING MATERIALS. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN. Ventilation: GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT. Protective Gloves: NONE REQUIRED. Eye Protection: NONE REQUIRED. Other Protective Equipment:NOT REQUIRED. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health REGULATORY INFORMATION: CHROMIUM (III) AND COMPOUND (S): 5.0 WT% MAX, (CHROMIUM METAL: 0.5 WT% MAX). COPPER AND COMPOUND: 5/0 WT% MAX, (AS COPPER METAL 1.0 WT% MAX).

========= Physical/Chemical Properties ===========

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:>212F,>100C

Vapor Pres:NEG

Spec Gravity:1.0-1.2(H20=1)

Evaporation Rate & Reference: NEGLIGIBLE.

Solubility in Water:NEG

IGIBLE. Appearance and Odor:TONER IS FINE POWDER, WITH SLIGHT ODOR.	
Stability and Reactivity Data	
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER. Hazardous Decomposition Products:AS WITH ANY OTHER ORGANIC MATERIAL DECOMPOSITION WILL PRODUCE CARBON DIOXIDE & CARBON MONOXIDE.	
======== Disposal Considerations =============	

Waste Disposal Methods:THE WASTE TON ER COULD BE CONSIDERED AS PLASTIC

WASTE. FOR INCINERATION, PACKAGE TONER ADEQUATELY. DO NOT DISPERSE THE TONER INTO FIRE. DISPOSE IN ACCORDANCE WITH FEDERAL, STATE &/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.