View NSN Online: https://aerobasegroup.de/nsn/3439-00-015-5327

ALPHAMETALS INC. -- SOLDER OF ALLOYS OF LEAD, TIN, SILVER, BISMUTH -- 3439-00-015-5327

Product ID:SOLDER OF ALLOYS OF LEAD, TIN, SILVER, BISMUTH MSDS Date:08/13/1987 FSC:3439 NIIN:00-015-5327 MSDS Number: BRNGN === Responsible Party === Company Name: ALPHAMETALS INC. Address:600 RT 440 City: JERSEY CITY State:NJ ZIP:07304-1027 Country:US Info Phone Num:201-434-6778 Emerg ency Phone Num:201-434-6778 CAGE:96913 === Contractor Identification === **Company Name: DEANCO INC** Address:7933 QUEENAIR DR Box:City:GAITHERSBURG State:MD ZIP:20879-4137 Country:US Phone:301-948-5444 CAGE:9K946 Company Name: KINDEL R E AND CO Address:326 E 3RD Box:City:CINCINNATI State:OH ZIP:45202-3510 Country:US CAGE:96913

Ingred Name:LEAD (SARA III) CAS:7439-92-1 RTECS #:OF7525000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0 .05 MG/M3;1910.1025 ACGIH TLV:0.15 MG/M3;DUST 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:TIN CAS:7440-31-5 RTECS #:XP7320000 Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 ACGIH TLV:2 MG/M3; 9293

Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:BISMUTH CAS:7440-69-9 RTECS #:EB2600000 Other REC Limits:NONE RECOMMENDED

Ingred Name:ANTIMONY (SA RA III) CAS:7440-36-0 RTECS #:CC4025000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.5 MG/M3 ACGIH TLV:0.5 MG SB/M3; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:INDIUM CAS:7440-74-6 RTECS #:NL1050000 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.1 MG/M3 ACGIH TLV:0.1 MG/M3; 9293

LD50 LC50 Mixture:TLV LEAD=0.05 MG/M3 Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC :YES OSHA:NO Health Hazards Acute and Chronic: MOLTEN SOLDER DOES NOT PRODUCE SIGNIFICANT QUANTITIES OF FUME BELOW 900F.TIN:DUST/FUMES MAY IRRITATE SKIN AND MUCOUS MEMBRANES, POSSIBLE LUNG DAMAGE. SILVER: MAY DISCOLOR SKIN, EYES. BISMUTH: GUM DISCOLORAT ION/INFLAMATION.ANTIMONY:GI UPSET,INDIUM:MAY CAUSE BLOOD DAMAGE, LIVER AND KIDNEY DAMAGE. LEAD: LIVE AND CNS DAMAGE. Explanation of Carcinogenicity: LEAD COMPOUNDS ARE CONSIDERED TO BE A CANCER RISK BY IARC. Effects of Overexposure: ANTIMONY:SLEEPLESSNESS, IRITABILITY, MUSCLE PAIN.INDIUM:WEIGHT LOSS.BISMUTH:BAD BREATH.SILVER:DISCOLORATION OF EYES AND SKIN.TIN:IRRITATION.LEAD:ANEMIA,INSOMNIA,WEAKNESS,CONSTIPATION,NAUS EA, ABDONIMAL PA IN. Medical Cond Aggravated by Exposure:WOMEN OF CHILD BEARING AGE SHOULD AVOID CONTACT WITH LEAD. First Aid:INHAL:REMOVE FROM EXPOSURE.CALL PHYSICIAN.INGEST:CALL PHYSICIAN OR POISON CONTROL CENTER.SKIN: HOT MEATL BURNS SHOULD BE COOLED WITH WATER; CALL PHYSICIAN. EYES: FLUSH WITH WATER; CAONTACT PHYSICIAN. Flash Point:NONE Extinguishing Media: USE MEDIA APPROPRAITE FOR SURROUNDING FIRE. Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard: THIS PRODUCT IN DUST FORM IS AN EXPLOSION HAZARD.LEAD FUMES ARE TOXIC.

========== Accidental Re

lease Measures ================

Spill Release Procedures: AVOID INHALING FUMES OR DUST. VACUUMING IS RECOMMENDED. PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL. Neutralizing Agent: NONE

Handling and Storage Precautions:DO NOT USE OR CONSUME
FOOD,DRINK,TOBACCO OR COSMETICS IN WORK AREA.
Other Precautions:EMPTY PRODUCT CONTAINERS RETAIN RESIDUE AND MUST BE
LABELED"FOR INDUSTRIAL USE ONLY.KEEP OUT OF REACH OF CHILDRE

N.DO NOT TAKE INTERNALLY".

Respiratory Protection: USE A NIOSH APPROVED DUST/FUME RESPIRATOR WHEN TLV IS EXCEEDED. Ventilation: USE MECHANICAL (GENERAL) OR LOCAL EXHAUST. Protective Gloves: TO AVOID BURNS. Eye Protection: SAFETY OR WELDING GLASSES/HOOD. Other Protective Equipment: WORK CLOTHES SHOULD BE WORN. Work Hygienic Practices: WASH HANDS.SEPERATE WORK CLOTHES FROM STREET CLOTHES.LAUNDER WORK CLOTHES BEFORE REUSE.KE EP FOOD OUT OF THE WORK AREA. Supplemental Safety and Health NONE HCC:N1 NRC/State Lic Num:NONE Solubility in Water: INSOLUBLE Appearance and Odor:METAL;SILVER-GRAY;ODORLESS Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIELS, ACIDS, HYDROGEN PEROXIDE. Stability Condition to Avoid:NONE Hazardous Decomposition Products: LEAD FUMES AND LEAD PARTICU LATES.

Waste Disposal Methods:RECYLCLE OR DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.