View NSN Online: https://aerobasegroup.de/nsn/9150-00-189-6730

Product ID:OE-40 MIL-L-2104D MC-1115 MC-2879 MSDS Date:09/01/1986 FSC:9150 NIIN:00-189-6730 MSDS Number: BRPBW === Responsible Party === Company Name: IMPERIAL OIL CO., INC. Address:ORCHARD PLACE Box:279 City:MORGANVILLE State:NJ ZIP:07751 Country:US Info Phone Num:201-591-9400 - RICHARD ROBINSON Emergency Phone Num:908-591-9400/FAX -8825 CAGE:58563 === Contractor Identification === Company Name: IMPERIAL OIL CO INC Address: FOOT OF ORCHARD PL Box:279 City:MORGANVILLE State:NJ ZIP:07751 Country:US Phone:732-591-9400/FAX: 732-591-8825 CAGE:58563

Ingred Name:LUBE OIL BASE STOCK Fraction by Wt: >99% Other REC Limits:NONE RECOMMENDED

Ingred Name:ZINC AS ZINC ADDITIVE CAS:7440-66-6 RTECS #:ZG8600000 Fraction by W t: 0.2-0.3% Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG ZNO/M3 ACGIH TLV:10 MG ZNO/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:PROPRIETARY ADDITIVES Fraction by Wt: 0.6-0.7% Other REC Limits:NONE RECOMMENDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:WHILE THIS PRODUCT MAY IRRIATTE THE SKIN FROM PROLONGED SKIN CONTACT THERE IS NO MEDICAL OR TOXICOLOGI
CAL EVIDENCE THAT THIS IS AN IRRITANT, A CORROSIVE OR CARCINOGEN. IR HAS A LOW ODOER OF ORAL & DER MAL TOXICITY. INHALATION OF PRODUCT MIST MAY CAUSE PULMONARY PROBLEMS.
Explanation of Carcinogenicity:NONE SPECIFIED BY MANUFACTURER.
Effects of Overexposure:FROM HUMAN EXP. & THE AVAILABLE TECHNICAL DATA CONCERNING THSI PRODUCT & DUE TO ITS LOW ORDER OF DERMAL, ORAL &

INGESTIVE TOXICITY, THE SIGNS & SYMPTOMS OF OVER EXPOSURE ARE UNKNOWN.

Medical Cond Aggravated by Exposure:DIRE

CT CONTACT WITH THE EYS MAY

CAUSE EYE IRRITATION, PROLONGED SKIN CONTACT MAY CAUSE SKIN IRRITATION.

First Aid:IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN. CALL A PHYSICIAN IMMEDIATELY. IF SPLASHED INTO THE EYES, PURGE WITH COPIOUS AMOUNTS OF WATER. IN CASE OF SKIN CONTACT CLEANSE WITH WATERLESS SOA P FOLLOWED BY THOROUGH WASHING WITH SOAPS & WATER.

Flash Point:446F,230C Extinguishing Media:CARBON DIOXIDE, WATER FPG, FOAM OR DRY CHEMICAL. Fire Fighting Procedures:WEAR MESA/NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS (SCHEDULE 13) USE WATER TO COOL FIRE EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:DIKE & CONTAIN SPILL WITH INERT MATERIAL (SAND, FULLER EARTH ETC.) TRANSFER LIQUID TO DRUMS OR OTHER CONTAINERS FOR RECOVERY OR DISPOSAL. AREA MAY BE SLIPPERY. CARE SHOULD BE TAKEN TO AVOID FALLS. PRE VENT MATERIAL FROM GETTING INTO SEWERS & WATER.

Handling and Storage Precautions: THESE LUBRICANTS BECOME VERY VISCOUS WHEN STORED AT LOW TEMPERATURES - THEY CONGEAL AT TEMP. FROM -12 TO -32 C.

Other Precautions: USE PRODUCT WITH CAUTION AROUND OPEN FLAMES, HEAT, SPARKS, PILOT LIGHTS & STATIC ELECTRICITY.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:USE SUPPLIED AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED. Protective Gloves:IMPERVIOUS.

Eye Protection:SPLASH GOGGLES.

Other Protective Equipment: EYE WASH FACILITY.

Work Hygienic Practices: MINIMIZE BREATHING VAPOR, MIST OR FUMES. REMOVE CONTAMINATED CLOTHING & LAUNDER OR DRY CLEAN BEFORE RE-USE.

Supplemental Safety and Health

OIL SOAKED SHOES SHOULD BE DISCARDED.

HCC:V6 Boiling Pt:B.P. Text:600F,316C Melt/Freeze Pt:M.P/F.P Text:0F,-18C Vapor Pres:1MM Vapor Density:1 Spec Gravity:1 Evaporation Rate & amp; Reference: