View NSN Online: https://aerobasegroup.de/nsn/6810-00-978-1878 ABSOLUTE STANDARDS INC -- BENZENE, 9156 -- 6810-00-978-1878 ============= Product Identification ======================== Product ID:BENZENE, 9156 MSDS Date:11/02/1992 FSC:6810 NIIN:00-978-1878 MSDS Number: BRQFH === Responsible Party === Company Name: ABSOLUTE STANDARDS INC Address:498 RUSSELL ST City:NEW HAVEN State:CT ZIP:06513 Country:US Info Phone Num:800-368-1131 Emergency Phone Num:800-368-1131 CAGE:0TZV1 === Contract or Identification === Company Name: ABSOLUTE STANDARDS INC Address:44 ROSSOTTO DR Box:5585 City:HAMDEN State:CT ZIP:06518 Country:US Phone:203-281-2917 CAGE:0TZV1 ======= Composition/Information on Ingredients ======== Ingred Name:BENZENE (SARA III) CAS:71-43-2

RTECS #:CY1400000 Fraction by Wt: 99-100% OSHA PEL:10 PPM

ACGIH TLV:10 PPM EPA Rpt Qty:10 LBS DOT Rpt Qty:10 LBS

LD50 LC50 Mixture:LD50:(ORAL RAT)4894 M

G/KG.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Health Hazards Acute and Chronic: INHALATION MAY CAUSE HEADACHE, NAUSEA, VOMITING, DIZZINESS, NARCOSIS, SUFFOCATION, LOWER BLOOD PRESSURE, CENTRAL NERVOUS SYSTEM DEPRESSION. INHALATION OF VAPORS MAY CAUSE SEVERE IRRITATION OR BURNS OF RESPIRATORY SYSTEM, PULMONARY EDEMA, OR LUNG INFLAMMATION. CONTACT WITH SKIN OR EYES MAY CAUSE IRRIT. (EFTS OF OVEREXP)

Expla

nation of Carcinogenicity:BENZENE:GRP1(IARC VOL SUPP 7,P.120,'87); CARCIN(NTP 6'TH ANN RPT ON CARCIN, '91) OSHA REGULATD, 29 CFR 1910.1028,J-1 02,92.

Effects of Overexposure: HLTH HAZ: PRLNGD SKIN CNTCT MAY RSLT IN DERM. EYE CNTCT MAY RSLT IN TEMPORARY CORNEAL DMG. INGEST MAY CAUSE HDCH. NAUS, VOMIT, DIZZ, GI IRRIT, BLURRED VISION, & LOW BLOOD PRESS. IRREVERSIBLE INJURY TO BLOOD FORMING TISS MAY RSLT FROM CHRONIC EXPOS. TARGET ORGANS:BLOOD, CNS, EYES, SKIN, BONE MARROW, RESP SYS,

LUNGS.

Medical Cond Aggravated by Exposure: NONE IDENTIFIED.

First Aid:INGEST:DO NOT INDUCE VOMITING. INHAL:REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. EYE/SKIN:IMMEDIATELY FLUSH WITH WATER FOR AT LEAST 15 M INUTES.

Flash Point Method:CC Flash Point:12F,-11C Lower Limits:1.

3%

**Upper Limits:8%** 

Extinguishing Media: USE ALCOHOL FOAM, DRY CHEMICAL OR CARBON DIOXIDE. WATER MAY BE INEFFECTIVE.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROT EQUIP. MOVE CNTNRS FROM FIRE AREA IF IT CAN BE DONE W/OUT RISK. USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard: VAPORS MAY FLOW ALONG SURFS TO DISTANT IGNIT SOURCES & FLASH BACK. CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE. CONTACT WITH STRONG OXIDIZERS MAY CAUSE FI

