View NSN Online: https://aerobasegroup.de/nsn/2530-01-068-6451

Product ID:BENDIX FRICTION MATERIAL MSDS Date:03/01/1988 FSC:2530 NIIN:01-068-6451 **MSDS Number: BRTCD** === Responsible Party === Company Name: BENDIX CORP THE FRICTION MATERIALS DIV Address:GREEN ISLAND Box:238 City:TROY State:NY ZIP:12181 Country:US Info Phone Num:518-270-0200 Е mergency Phone Num:518-270-0200 Preparer's Name: E.L. ROGERS CAGE:76126 === Contractor Identification === Company Name: BENDIX CORP THE FRICTION MATERIALS DIV-ALLIED CORP Address:GREEN ISLAND Box:238 City:TROY State:NY ZIP:12181 Country:US Phone:518-273-6550/518-270-0200 CAGE:76126 Company Name: KALMAR AC HANDLING SYSTEMS INC Address:777 MANOR PARK DR Box:City:COLUMBUS State:OH ZIP:43228 Country:US CAGE:0AHU0

Ingred Name: ASBESTO

S, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Other REC Limits:NONE RECOMMENDED OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9293

Ingred Name:SILICA, ALPHA QUARTZ CAS:14808-60-7 RTECS #:VV7330000 Other REC Limits:NONE RECOMMENDED OSHA PEL:SEE TABLE Z3 ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:SILICATE(S) CAS:14407-96-6 Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 Other REC Limits:NONE RECOMMENDED OSHA PEL :3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9293

Ingred Name:COKE-PETROLEUM DERIVED Other REC Limits:NONE RECOMMENDED

Ingred Name:PHENOLIC AND CASHEW RESINS,CURED Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:GRAPHITE CAS:7782-42-5 RTECS #:MD9659600 Other REC Limits:NONE RECOMMENDED OSHA PEL:15 MPPCF RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name:IRON CAS:7439-86-6 RTECS #:NO6925000 Other REC Limits:NONE RECOMMENDED

Ingred Name:IRON OXIDE CAS:1309-37-1 RTECS #:NO74 00000 Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:ZINC (SARA III) CAS:7440-66-6 RTECS #:ZG8600000 Other REC Limits:NONE RECOMMENDED OSHA PEL:10 MG ZNO/M3 ACGIH TLV:10 MG ZNO/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:ZINC OXIDE CAS:1314-13-2 RTECS #:ZH4810000 Other REC Limits:NONE RECOMMENDED OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:ALUMINUM (SARA III) CAS:7429-90-5 RTECS #:BD0330000 Oth er REC Limits:NONE RECOMMENDED OSHA PEL:15MG/M3 DUST/5 FUME ACGIH TLV:10MG/M3 DUST; 9293

Ingred Name:ALUMINUM OXIDE CAS:1302-74-5 RTECS #:GN0231000 Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES Health Hazards Acute and Chronic:SKIN:PARTIALLY CURED PHENOLIC OR CASHEW RESIN MAY CAUSE DERMATITIS.INHAL:SILICA DUST MAY CAUSE

SILICOSIS.ASBESTOS CAN CAUSE ASBESTOSIS,LUNG CANCER,MESOTHELIOMA. METAL DUST MAY CAUSE IRRITATION.EYES:MA Y CAUSE IRRITATION.INGEST:MAY CAUSE GASTROINTESTINAL DISTURBANCES. PEOPLE WHO SMOKE ARE AT INCREASED RISK FROM ASBESTOS. Explanation of Carcinogenicity:CONTAINS A [1332-21-4] WHICH IS LISTED BY NTP AND IARC AND REGULATED BY OSHA AS A CARCINOGEN. Effects of Overexposure:PARTIALLY CURED CASHEW RESINS-SKIN ERUPTIONS RESEMBLING POISON IVY.ASBESTOS/SILICA-COUGHING,WHEEZI NG,SHORTNESS
OF BREATH, IMPAIRED PULMONARY FUNCTION. DUSTS IN EYE MAY CAUSE IRRITATION. G/I DISTURBANCE S ARE POSSIBLE FROM INGESTION. Medical Cond Aggravated by Exposure:SMOKERS ARE AT INCREASED RISK IN WORKING WITH AIRBORNE ASBESTOS FIBERS.
======================================
First Aid:MANUFACTURER STATES THAT NONE SHOULD BE NESCESSARY WITH THE PROPER HANDLING OF THIS MATERIAL.
======================================
Extinguishing Media:WATER(TYPE A,B,C EXTINGUISHER),FOG,FOAM. Fire Fighting Procedures:"N/A" (NONE SPECIFIED BY MANUFACTURER.) Unusual Fire/Explosion Hazard:"N/A" (ONE SPECIFIED BY MANUFACTURER.)
======================================
Spill Release Procedures:HMIS: PICK UP PIECES. IF ASBESTOS DUST HAS BEEN PRODUCED, WEAR HEPA FILTERED RESPIRATOR AND FOLLOW REGULATION 29CFR1900.1001, ASBESTOS STANDARD. CLEAN BY WET METHODS AND/OR HEPA VACUUM.
Neutr alizing Agent:NO INFORMATION GIVEN ON MSDS BY MFR.
======================================
Handling and Storage Precautions:DO NOT BREATH ASBESTOS DUST! Other Precautions:NONE
======================================
Respiratory Protection:NOT NORMALLY NEEDED. IF AIRBORNE ASBESTOS DUSTS ARE BEING PRODUCED, WEAR NIOSH APPROVED HEPA RESPIRATOR OR SUPPLIED AIR RESPIRATOR. Ventilation:LOCAL EXHAUST IS PREFERRED. Protective Gloves:COT

Appea

rance and Odor:SOLID,ODORLESS,LIGHT TAN TO DARK GREY COLOR. Corrosion Rate:UNKNOWNN

Stability Indicator/Materials to Avoid:YES NONE KNOWN Stability Condition to Avoid:NONE KNOWN Hazardous Decomposition Products:INCOMPLETE COMBUSTION WILL RESULT IN CARBON MONOXIDE AND CARBON DIOXIDE. Conditions to Avoid Polymerization:WILL NOT OCCUR NONE KNOWN

Waste Dis

posal Methods:PLACE IN PROPER RECEPTACLES.DISPOSE OF IN AUTHORIZED LANDFILLS IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document shoul d seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.