

CONOCO INC -- DIESEL FUEL NO. 2, LOW/HIGH SULFUR; 3502;3504;3510;4152. -- 9140-00-000-0184
===== Product Identification =====

Product ID:DIESEL FUEL NO. 2, LOW/HIGH SULFUR; 3502;3504;3510;4152.

MSDS Date:01/10/1994

FSC:9140

NIIN:00-000-0184

MSDS Number: BRTDK

=== Responsible Party ===

Company Name:CONOCO INC

Box:2197

City:HOUSTON

State:TX

ZIP:77252

Country:US

Info Phone Num:713-293-5550

Emergency

Phone Num:800-441-3637/800-424-9300(CHEMTREC)

Preparer's Name:MSDS ADMINISTRATOR

CAGE:5R396

=== Contractor Identification ===

Company Name:CONOCO INC

Address:5 GREENWAY PLAZA E

Box:2197

City:HOUSTON

State:TX

ZIP:77252

Country:US

Phone:713-293-5550PRODUCT/ 800-4413637MED

CAGE:5R396

===== Composition/Information on Ingredients =====

Ingred Name:DIESEL FUEL, NO. 2 (PETROLEUM MID-DISTILLATE).

CAS:68476-34-6

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

=====

==== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL RAT = 9ML/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MAY CAUSE IRRIT TO EYES/LUNGS/SKIN AFT
PROLONG/REPEAT EXPOSURE. ASPIRATION INTO LUNGS MAY CAUSE LUNG
DAMAGE & DEATH.

Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.

Effects of

Overexposure:OVEREXPOSURE MAY CAUSE WEAKNESS,HEADACHE,
NAUSEA,CONFUSION,BLURRED VISION,DROWSINESS,UNSPECIFIED CNS
EFFECTS.LARGE EXPOSURE MAY CAUSE DIZZINESS,SLURRED SPEECH,FLUSHED
FACE,UNCONSCIOUSNESS, CONVULSIONS .STUDIES IN MICE/RATS W/CHRONIC
EXPOUSRE HAVE SHOWN DIESEL EXHAUST MAY PRODUCE LUNG TUMORS AND
LYMPHOMAS.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MFG.

==== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRE

SH AIR.GIVE OXYGEN IF BREATH DIFFI OR ARTI

RESP IF NOT BRETH.CALL PHYSICIAN.SKIN:WASH W/SOAP & WATER.IF IRRIT
DEVELOP/PERSIST,CALL PHYSICIAN.EYES:IMMED FLUSH W/PLENTY OF WATER
FOR @ 15MINS.CALL PHYSICIAN.INGEST:DO NOT INDUCE VOMITING.IF
CONSCIOUS GIVE 2 GLASSES OF WATER.PHYSICIAN:GIVE 5ML/KG (OR 350ML)
OF CHARCOAL SOLUTION (50GMS CHARCOAL IN 400ML WATER).

==== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:130F,54C

Lower

Limits:0.4

Upper Limits:6

Extinguishing Media:WATER SPRAY, FOAM, DRY CHEMICAL, CARBON DIOXIDE.

NFPA CLASSIFICATION:CLASS II COMBUSTIBLE LIQUID.

Fire Fighting Procedures:DON'T ENTER ENCLOSE/CONFINE SPACE W/O PROPER
PROT EQPMT INCLUDING RESP PROT.W/WATER SPRAY COOL FIRE EXPOSED
CNTNRS & DISPERSE/FLUSH VAP/PROTECT FROM SPILL/LEAK.

Unusual Fire/Explosion Hazard:PRODUCTS OF COMBUSTION MAY CONTAIN CARBON
MONOXIDE, CARBON DIOXIDE & OTHER TOXIC MATERIALS.

==== Accidental

Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES.USE EXPLOSION-PROOF EQPMT & APPROPRIATE PPE.DIKE & PREVENT FROM ENTERING SEWERS/WATERWAYS.SOAK UP W/ABSORBENT MATL.(SAWDUST,SAND,OIL DRY).IF SPILLED INTO NAVIGABLE WATERS REPOR T TO NAT RESP CNTR 800-424-8802.READ MSDS.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN WELL-VENTILATED AREA.KEEP CONTAINER T

IGHTLY CLOSED.STORE IAW NAT FIRE PROTECTION ASSOC

RECOMMENDATIONS.STORE AWAY FROM HEAT/SPARKS/FLAME/OXID

Other Precautions:DO NOT BREATH VAPORS/MISTS.GROUND CONTAINERS WHEN TRANSFERRING LIQUID (FLOWING FUEL GENERATES STATIC ELECTRICITY).

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELECT APPROPRIATE NIOSH-APPROVED RESP PROTECTION WHEN NEEDED TO AVOID INHAL OF MIST/VAPORS AND TO MAINTAIN EXPOSURES BELOW ACCEPTABLE LIMITS.

Ventilatio

n:USE ONLY WITH ADEQUATE VENTILATION. MECHANICAL (GENERAL) VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves:NEOPRENE, NBR GLOVES.

Eye Protection:SAFETY GLASSES W/SIDE SHIELDS, CHEM GOGG

Other Protective Equipment:COVERALLS IF SPLASHING IS PROBABLE.

Work Hygienic Practices:WASH HANDS AFTER HANDLING. LAUNDER CONTAMIN CLOTHES PRIOR TO REUSE.

Supplemental Safety and Health

NOT SUBJECT TO CA PROP 65. CONTAINS DIESEL FUEL OIL SUBJECT TO PEN WORKER/COMM RIGHT TO KNOW.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:350F,177C

Vapor Pres:1MM@68F

Vapor Density:>1

Spec Gravity:0.84-0.88 @60C

Viscosity:1.9CAT@40C

Solubility in Water:INSOLUBLE

Appearance and Odor:AROMATIC ODOR;LIQUID;HIGH SULFUR-GREEN;LOW SULFUR-RED OR UNDYED(CLEAR OR STRAW)

Percent Volatiles by Volume:NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

INCMPATIBLE OR CAN REAC WTIH STRONG OXIDIZERS.

Stability Condition to Avoid:AVOID HEAT, SPARKS, FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER TOXIC MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:TREATMENT/STORAGE/TRANSP/DISPOSAL MUST BE IAW APPLICABLE FED/STATE/PROVINCIAL/LOC REGS.DO NOT FLUSH TO SURFACE WATER/SANITARY SEWER SYS.BY ITSELF LIQ IS EXPECTED TO BE RCRA IGNITABLE HAZ WASTE.CONTAIN S PETRO HYDROCARBONS-RQ(FILM/SHEEN/DI SCOLO WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.