

BENZ OIL INC -- UCF-1 CALIBRATING FLUID -- 6850-00-779-6851

=====
Product Identification
=====

Product ID:UCF-1 CALIBRATING FLUID

MSDS Date:09/23/1993

FSC:6850

NIIN:00-779-6851

MSDS Number: BSCWX

=== Responsible Party ===

Company Name:BENZ OIL INC

Address:2724 HAMPTON

City:MILWAUKEE

State:WI

ZIP:53209-5401

Country:US

Info Phone Num:414-442-9450

Emergency Phone Num:414-442-9450

Preparer's Name:NOT

PROVIDED

CAGE:8F260

=== Contractor Identification ===

Company Name:BENZ OIL INC

Address:2724 W HAMPTON AVE

Box:City:MILWAUKEE

State:WI

ZIP:53209-5401

Country:US

Phone:414-442-2900

CAGE:8F260

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

State:LA

ZIP:70058

Country:US

Phone:504-366-4542

Contract Num:SP0450-00-M-D805

CAGE:0T5C6

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL

Fraction by Wt: >45%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)
ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name:ALIPHATIC PETROLEUM DISTILLATE
> Wt:45.
ACGIH TLV:500 PPM/100 MG/M3

Ingred Name:PROPRIETARY ADDITIVE

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EXCESSIVE INHALATION OF VAPORS CAN
CAUSE NASAL & RESPIRATORY IRRITATION, HEADACHE, DIZZINESS,
WEAKNESS,
FATIGUE, NAUSEA & POSSIBLE ASPHYXIATION. REPEATED SKIN
CONTACT MAY CAUSE SKIN IRRITATION OR DERM ATITIS. SWALLOWING CAN
CAUSE NAUSEA, VOMITING & DIARRHEA. EYE CONTACT CAN CAUSE SEVERE EYE
IRRITATION, REDNESS, TEARING & BLURRED VISION.
Explanation of Carcinogenicity:THIS PRODUCT IS NOT LISTED AS A
CARCINOGEN BY NTP, IARC, OR OSHA.
Effects of Overexposure:REDDENING & IRRITATION OF EYES OR SKIN.
Medical Cond Aggravated by Exposure:PRE-EXISTING DERMATITIS OR SKIN
DISEASES.

=====
===== First Aid Measures =====

First Aid:SKIN CONTACT: WASH WITH A MILD SOAP CONTAINING LANOLIN OR
OTHER EMOLLIENTS. EYE CONTACT: FLUSH EYES WITH CLEAR WATER FOR 15
MINUTES AND CONTACT PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING.
ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO VOMITING CAN CAUSE
CHEMICAL PNEUMONIA WHICH CAN BE FATAL. CONTACT A PHYSICIAN
IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measure
s =====

Flash Point Method:COC
Flash Point:>73.9C, 165.F
Lower Limits:1
Upper Limits:7
Extinguishing Media:FOAM, WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE.
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE
WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS,AND TO REDUCE VAPORS OF
SPILLS WHICH HAVE NOT IGNITED.
Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY
MIGRATE TO A DISTANT IGNITION SOURCE. SPRAYING WATER STREAM
DIRECTLY ON BUR

NING MATERIAL MAY CAUSE FROTHING & SPREAD FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND, EARTH, OR OTHER ABSORBENT TO SPIL. MINIMIZE SKIN CONTACT. KEEP PRODUCT OUT OF SEWERS & WATERWAYS. ADVISE AUTHORITIES OF LARGE SPILLS.

Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT, SPARKS & OTHER IGNITION SOURCES.

Other Precautions:"EMPTY" CONTAINERS RETAIN RESIDUAL OIL. DO NOT PRESSURIZE, CUT, WELD, SOLDER, DRILL, GRIND, OR EXPOSE DRUMS TO OTHER IGNITION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AN ORGANIC VAPOR MASK IF TLV IS EXCEEDED.

Ventilation:UNDER NORMAL CONDITIONS OF USE, LOCAL EXHAUST PROVIDES SUFFICIENT VENTILLATION.

Protective Gloves:OIL RESISTANT

Eye Protection:SPLASH GOGGLES

Other Prote

ctive Equipment:FUEL RESISTANT APRON.

Work Hygienic Practices:IN MOST CASES GOOD PERSONAL HYGIENE IS ALL THAT IS NEEDED FOR SAFE USE OF THIS PRODUCT.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V4

NRC/State Lic Num:NONE

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:2.0

Vapor Density:5

Spec Gravity:0.8

Evaporation Rate & Reference:0.01 (N-BUTYL ACETATE=1)

Solubility in Water:VERY SLIGHT @ RM TMP

Appearance and Odor:CLEAR MOBIL

E LIQUID WITH A MILD SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT W/STRONG OXIDANTS SUCH AS CHLORINE GAS.

Stability Condition to Avoid: MFR GAVE NO INFORMATION ON MSDS.

Hazardous Decomposition Products: FUMES, SMOKE, OXIDES OF CARBON, SULFUR AND NITROGEN WHEN COMBUSTED.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Toxicological Information =====

Toxicologica

I Information: NOT PROVIDED

===== Ecological Information =====

Ecological: NOT PROVIDED

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF MATERIAL IN A LICENSED LANDFILL OR INCINERATION FACILITY I/A/W FEDERAL, STATE & LOCAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information: NOT PROVIDED

===== Regulatory Information =====

=====

SARA Title III Information: NOT PROVIDED

Federal Regulatory Information: NOT PROVIDED

State Regulatory Information: NOT PROVIDED

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabi

lity for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.