View NSN Online: https://aerobasegroup.de/nsn/5970-00-186-6529

MINNESOTA MINING AND MFG CO -- SCOTCHCAST ELECTRICAL RESIN 10 (5241),PART B. --5970-00-186-6529

Product ID:SCOTCHCAST ELECTRICAL RESIN 10 (5241), PART B. MSDS Date:07/20/1993 FSC:5970 NIIN:00-186-6529 Kit Part:Y MSDS Number: BSDQT === Responsible Party === Company Name: MINNESOTA MINING AND MFG CO Address:3M CTR 224-2S-25 City:ST. PAUL State:MN ZIP:55144-1000 Coun try:US Info Phone Num:612-733-1341/612-733-1110 Emergency Phone Num:612-733-1341 CAGE:76381 === Contractor Identification === Company Name: GENERAL TOOL & SUPPLY CO. Address:5614 7TH AVENUE SOUTH Box:80904 City:SEATTLE State:WA ZIP:98108-3317 Country:US Phone:206-762-1500 CAGE:3Z323 Company Name: MINNESOTA MINING AND MFG CO, DBA 3M Address:3M CENTER BLDG 224-5S-04 Box:City:SAINT PAUL State:MN ZIP:55144-1000 Country:US Phone:866-556 5712 / 612-733-1110 CAGE:76381

======= Composition/Inform

ation on Ingredients =========

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 Fraction by Wt: 45-50% Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 RESP DUST ACGIH TLV:2 MG/M3 RESP DUST

Ingred Name:FATTY ACID IMIDE CAS:68541-13-9 Fraction by Wt: 35-40% Other REC Limits:NONE RECOMMENDED

Ingred Name:POLYSTYRENE CAS:9003-53-6 Fraction by Wt: 5-10% Other REC Limits:NONE RECOMMENDED

Ingred Name:DIETHYLENE TRIAMINE CAS:111-40-0 RTECS #:IE1225000 Fraction by Wt: 1.0-5.0% Other REC Limits:NONE RECOMMENDED OSHA PEL:1 PPM ACGIH TLV:S, 1 PPM; 9293

Ingred Name:TREATED CLAY CAS:71011-27-3 Fraction by Wt: 1.0-5.0% Other REC Limits:NONE RECOMMENDED

Ingred Name:NONYLPHENOL CAS:25154-52-3 RTECS #:SM5600000 Fraction by Wt: 1.0-2.0% Other REC Limits:NONE RECOMMENDED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acu

te and Chronic:ACUTE-EYE/SKIN AND RESPIRATORY IRRITATION. CARBON BLACK IS A POTENTIAL CANCER HAZARD CAUSING STOMACH AND SKIN CANCER BY THE DIETARY ROUTE OF EXPOSURE IN LAB ANIMAL STUDIES. EXPOSURE UNDER NORMAL USE I S CONSIDERED VERY REMOTE.
Effects of Overexposure:EYE: IRRITATION, REDNESS. SKIN:IRRITATION, POSSIBLE SENSITIZATION. INHALATION:DIFFICULTY IN BREATHING, WHEEZING, TIGHNESS OF CHEST, RESPIRATORY FAILURE. INGEST:VOMITING, NAUSEA, ABDOMINAL TENDERNESS, BLOOD IN VOMITOUS AND FECES.
Medical Cond Aggravated by Exposure:ANY PRE-EXISTING ALLERGY OR SENSITIVITY.
======================================
First Aid:INHALATION:REMOVE TO FRESH AIR, PROVIDE CPR/OXYGEN IF NEEDED. EYE CONTACT:FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL HELP. SKIN CONTACT:WASH WITH SOAP AND WATER. GET MED ATTENTION IF SYMPTOMS PERSIS T. INGESTION:DO NOT INDUCE VOMITING, DRINK 1-2 GLASSES OF WATER. GET MEDICAL HELP IMMEDIATELY.
= ====================================
Flash Point Method:CC Flash Point:>450F/>232C Extinguishing Media:CO2, FOAM, DRY CHEMICAL Fire Fighting Procedures:FIRE FIGHTERS SHOULD WEAR PROTECTIVE CLOTHING AND SELF-CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.
======================================
Spill Release Procedures:OBSERVE ALL PREC AUTIONS LISTED. COLLECT SPILL WITH ABSORBENT, PLACE IN CONTAINERS WITH LID.
======================================
<ul> <li>Handling and Storage Precautions: USE IN WELL VENTILATED AREA FOR MIXING, CURING, POURING. VENTILATE COOL-DOWN AREAS.</li> <li>Other Precautions: USE IN A WELL VENTILATED AREA. DO NOT INHALE DUST OR VAPORS.</li> </ul>
======================================
Respiratory Protection: USE NIOSH APPROVED RESPIRATOR SUITABLE FOR ORGANI

C VAPORS, OR SELF CONTAINED BREATHING APPARATUS WHEN WELDING IN CONFINED SPACES OR WHERE LOCAL EXHAUST OR VENTILATION DOES NOT KEEP EXPOSURE BELOW TLV. SELECT PER OSHA 29 CFR 1910.134 Ventilation:LOCAL EXHAUST PREFERRED Protective Gloves: IMPERVIOUS Eye Protection:SAFETY GOGGLES Other Protective Equipment: APRON, SLEEVES OF IMPERVIOUS MATERIAL, EYEWASH STATION. Work Hygienic Practices: DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH THIS PRODUCT. Supplemental Safety and Health THIS I S PART B OF TWO-PART A/B KIT, SAME NSN. HCC:N1 Spec Gravity:1.44 Solubility in Water: INSOLUBLE Appearance and Odor: BROWN VISCOUS LIQUID, AMINE ODOR. Percent Volatiles by Volume:00 Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:OXIDES OF CARBON & NITROGEN. ====== Disposal Con 

Waste Disposal Methods:LANDFILL ABSORBENT MATERIAL OR INCINERATE IN ACCORDANCE WITH ALL LOCAL, FEDERAL AND STATE LAWS & REGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utiliz

ing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.