

FARWEST PAINT MFG CO -- EXTERIOR TRIM ENAMEL GREEN 14052 -- 8010-01-333-9439

=====
Product Identification
=====

Product ID:EXTERIOR TRIM ENAMEL GREEN 14052

MSDS Date:03/23/1992

FSC:8010

NIIN:01-333-9439

MSDS Number: BSHPK

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

City:TUKWILA

State:WA

ZIP:98168

Country:US

Info Phone Num:206-244-8844

Emergency Phone Num:206-9

41-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====
Composition/Information on Ingredients
=====

Ingred Name:TEXANOL (ESTER ALCOHOL) (TEXANOL IS AN EASTMAN CHEMICAL
PRODUCT)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 4.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 GRAM

S/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN
CONFINED AREA MAY LEAD TO MUCOUS MEMBRANE IRRITATION, DIZZINESS,
HEADACHE. SKIN: IRRITATION. EYE: IRRITATION. INGESTION: AMOUNTS
INGESTED INCIDENTAL TO CONSUMER AND INDUSTRIAL HAN
DLING ARE NOT
LIKELY TO CAUSE INJURY, HOWEVER, INGESTION OF LARGER AMOUNTS COULD
CAUSE SERIOUS INJURY.
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH
SAFE HANDLING INSTRUCTIONS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS
DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN CONTACT: WASH OFF
QUICKLY WITH PLENTY OF WATER, THEN SOAP AND WATER. REMOVE AND WASH
CONTA
MINATED CLOTHING BEFORE REUSE. EYE CONTACT: FLUSH IMMEDIATELY
WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER LIDS, FOR AT LEAST 15
MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: OBTAIN MED
AID IMMED.

===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER, OR WATER FOG
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINER
S MAY
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED
WITH ABSORBENT MATERIALS.

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY WITH ADEQUATE VENTILATION.
AVOID BREATHING VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND
E

YES. AVOID TEMPERATURES BELOW 40 F.

Other Precautions:KEEP FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND APPROPRIATELY LABELED. THIS PRODUCT CONTAINS NO MERCURY IN REPORTABLE QUANTITIES AS DEFINED BY OSHA AND EPA. KEEP OUT OF REACH OF CHILDREN.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE

LATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS LISTED IN INGREDIENTS.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:IMPERVIOUS GLOVES RECOMMENDED BY GLOVE MANUFACTURER

Eye Protection:SAFETY GLASSES WITH UNFRACTURED SIDELIDS, GOGGLES

Other Protective Equipment:EYE WASH AND SAFETY SHOWERS.

Work Hygienic Practices:KEEP WORK AREA CLEAN & FREE FROM SPILLS & LEAKS. WASH HANDS WITH SOAP AND WATER BEFORE HANDLING FOOD, DRINK, OR SMOKING.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pressure:23.8 @ 25C

Vapor Density:> AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT

Percent Volatiles by Volume:7.5

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials

to Avoid:YES

OXIDIZER AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

Conditions to Avoid Polymerization:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer

(provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.