

PROGRESS PAINT MFG CO -- TT-P-19D EXT FLAT LATEX, GRAY 36595 -- 8010-00-055-5183

=====  
Product Identification  
=====

Product ID:TT-P-19D EXT FLAT LATEX, GRAY 36595

MSDS Date:09/21/1992

FSC:8010

NIIN:00-055-5183

MSDS Number: BSHQZ

=== Responsible Party ===

Company Name:PROGRESS PAINT MFG CO

Address:826 W MAIN STREET

Box:33188

City:LOU

State:KY

ZIP:40232

Country:US

Info Phone Num:502-587-8685

Emergen

cy Phone Num:800-424-9300 CHEMTREC

Preparer's Name:B LAMAR

CAGE:69510

=== Contractor Identification ===

Company Name:PROGRESS PAINT MFG CO

Box:City:LOU

State:KY

ZIP:40232

Country:US

Phone:502-587-8685

CAGE:69510

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYLENE GLYCOL (SARA III) (VAPOR PRESSURE 0.1 MM HG @  
64F)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: 2%

Other REC Limits:NONE SPECIFIED

ACGIH TLV:50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred

Name:TEXANOL ESTER ALCOHOL (VAPOR PRESSURE 125.0 MM HG @ 64F)

Fraction by Wt: 250F,>121C

Lower Limits:0.6

Upper Limits:15.3

Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:MATERIAL CAN SPLATTER ABOUT 100C/212F,  
PAINT FILM CAN BURN.

===== Accidental Release Measures =====

Spill Release Procedures:RECOVER WITH ABSORBENTS, VERMICULITE OR OTHER  
ABSORBENT MATERIAL. PLACE IN APPROPRI  
ATE CONTAINERS FOR DISPOSAL.

DO NOT FLUSH INTO SEWERS OR STREAMS. WATER APPROPRIATE PROTECTIVE  
EQUIPMENT.

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. KEEP  
CONTAINERS CLOSED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKPLACE LIMITS ARE EXCEEDED, A NIOSH/MSHA  
APPROVED AIR SUPPLY RESPIRATOR IS ADVISED.

Ventilation:USE WITH ADEQUATE VENTILA  
TION, TO MAINTAIN EXPOSURE LIMITS  
BELOW TLV'S.

Protective Gloves:RESISTANT GLOVES-NEOPRENE,NITRILE RUBBER

Eye Protection:CHEMICAL SPLASH GOGGLES, SAFETY GLASSES

Other Protective Equipment:USE APRON TO AVOID CONTAMINATION OF  
CLOTHING. TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR  
IMPERVIOUS CLOTHING.

Work Hygienic Practices:PERSONS WITH PRE-EXISTING SKIN DISORDERS MAY BE  
MORE SUSCEPTIBLE TO THE EFFECTS OF THIS PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:387 TO 490F

Vapor Density:> AIR

Spec Gravity:1.3 (WATER=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SOLUBLE

Appearance and Odor:VISCOUS LIQUID, SLIGHT SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD  
ACRYLIC MONOMER.

===== Disposal C

considerations =====

Waste Disposal Methods:1.RECYCLE IF FEASIBLE. 2.INCINERATE AT AUTHORIZED FACILITY. 3.TREAT AT INDUSTRIAL/LIQUID WASTE FACILITY. 4.LANDFILL AFTER SOLIDIFICATION IN AUTHORIZED FACILITY. MATERIAL CLASSIFIED HAZARDOUS WASTE & S HOULD BE DISPOSED IN ACCORDANCE WITH REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.