

FARWEST PAINT MFG CO -- EXTERIOR TRIM ENAMEL GRAY 16492 -- 8010-01-336-0528

=====  
Product Identification  
=====

Product ID:EXTERIOR TRIM ENAMEL GRAY 16492

MSDS Date:03/23/1992

FSC:8010

NIIN:01-336-0528

MSDS Number: BSHYL

=== Responsible Party ===

Company Name:FARWEST PAINT MFG CO

Address:4522 S 133 ST

Box:68726

City:TUKWILA

State:WA

ZIP:98168-3251

Country:US

Info Phone Num:206-244-8844

Emergency Ph

one Num:206-941-1619

CAGE:6F266

=== Contractor Identification ===

Company Name:FARWEST PAINT MANUFACTURING CO

Address:4522 SOUTH 133RD ST

Box:City:TUKWILA

State:WA

ZIP:98168

Country:US

Phone:206-244-8844

CAGE:6F266

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 4.5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:VOC: 62 G/L

RTECS #:9999999VO

Other REC Limi

ts:NONE SPECIFIED

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: PROLONGED INHALATION IN  
CONFINED AREAS, MAY LEAD TO MUCUS MEMBRANE IRRITATION, DIZZINESS,  
HEADACHE. SKIN: IRRITATION. EYES: IRRITATION. INGESTION: AMOUNTS  
INGESTED INCIDENTAL TO CONSUMER & INDUSTRIAL HANDLING AREN'T  
LIKELY TO CAUSE INJURY,  
HOWEVER, INGESTION OF LARGER AMOUNTS COULD  
CAUSE SERIOUS INJURY.  
Medical Cond Aggravated by Exposure:NONE, WHEN USED IN ACCORDANCE WITH  
SAFE HANDLING INSTRUCTIONS.

=====  
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF RESPIRATORY SYMPTOMS  
DEVELOP, SEEK MEDICAL ATTENTION AT ONCE. SKIN: WASH OFF QUICKLY  
WITH PLENTY OF WATER, THEN SOAP & WATER. EYES: FLUSH IMMEDIATELY  
WITH LARGE AMOUNTS OF WATER, ESPECIALLY UNDER L  
IDS, FOR AT LEAST  
15 MINUTES. OBTAIN EMERGENCY MEDICAL TREATMENT. INGESTION: IF  
SWALLOWED, OBTAIN MEDICAL TREATMENT IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Extinguishing Media:FOAM, DRY CHEMICAL, WATER FOG OR WATER  
Fire Fighting Procedures:WATER MAY BE USED TO COOL AND PROTECT EXPOSED  
CONTAINERS  
Unusual Fire/Explosion Hazard:WILL NOT BURN, CLOSED CONTAINERS MAY  
BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:COMPLY WITH ALL APPLICABLE HEALTH AND  
ENVIRONMENTAL REGULATIONS. VENTILATE AREA. SPILLS MAY BE COLLECTED  
WITH ABSORBENT MATERIALS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:AVOID TEMPERATURES BELOW 40F. KEEP  
FROM FREEZING. STORE CONTAINERS WITH LIDS TIGHTLY CLOSED AND  
APPROPRIATELY LABELED.  
Other Precautions:USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING

VAPOR AND SPRAY MIST. AVOID CONTACT WITH SKIN AND EYES. REMOVE & WASH CONTAMINATED CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/OSHA FOR PROTECTION AGAINST MATERIALS.

Ventilation:LOCAL EXHAUST PREFERABLE, GENERAL EXHAUST ACCEPTABLE.

Protective Glove

s:IMPERVIOUS GLOVES

Eye Protection:SAFETY SPECTACLES W/UNPERF SIDE SHIELDS

Other Protective Equipment:EYE WASH, SAFETY SHOWERS, GOGGLES

Work Hygienic Practices:KEEP WORK AREA CLEAN & FREE FROM SPILLS OR LEAKS. ALWAYS WASH HANDS THOROUGHLY WITH SOAP & WATER BEFORE HANDLING FOOD,

Supplemental Safety and Health

DRINK, OR SMOKING. SMOKE IN DESIGNATED AREAS ONLY.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:23.8 @ 25C

Vapor D

ensity:> AIR

pH:7-8

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:INFINITE

Appearance and Odor:THIXOTROPIC LIQUID WITH SLIGHT ODOR; COLOR OF TINT

Percent Volatiles by Volume:7.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS AND/OR HYDROFLUORIC ACID

Stability Condition to Avoid:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE

Conditions to Avoid Polymerization:ELEVATED TEMPERATURES, CONTACT WITH OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE & FEDERAL REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.