

HOME OIL CO -- PAINT THINNER -- 8010-00-558-7026

===== Product Identification =====

Product ID:PAINT THINNER

MSDS Date:01/27/1992

FSC:8010

NIIN:00-558-7026

MSDS Number: BSRYC

=== Responsible Party ===

Company Name:HOME OIL CO

Address:3511 N OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-838-4663

Emergency Phone Num:316-838-4663

Preparer's Name:BERNARD D HOFFMAN, JR

CA

GE:0A9L8

=== Contractor Identification ===

Company Name:HOC INDUSTRIES, INC

Address:3511 N. OHIO

Box:2609

City:WICHITA

State:KS

ZIP:67219

Country:US

Phone:316-838-4663

CAGE:0A9L8

===== Composition/Information on Ingredients =====

Ingred Name:MIXTURE OF ALIPHATIC C9 AND C10 HYDROCARBONS AND AROMATICS
(C8 & HIGHER)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:BENZENE (SARA III)

CAS:71-

43-2
RTECS #:CY1400000
Fraction by Wt: .01-.09%
Other REC Limits:NONE SPECIFIED
OSHA PEL:1 PPM; STEL 5 PPM
ACGIH TLV:10 PPM
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:VOC = 778G/L
RTECS #:9999999VO
Other REC Limits:NONE RECOMMENDED
OSHA PEL:NOT RELEVANT
ACGIH TLV:NOT RELEVANT

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO
Health Hazards Acute and Chronic:BELIEVED TO CAUSE MODERATE EYE
IRRITATION.
BELIEVED TO BE MODERATELY IRRITATING TO SKIN & TO CAUSE
REDNESS, EDEMA, OR DRYING.

=====
===== First Aid Measures =====

First Aid:FLUSH EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES.
WASH EXPOSED SKIN WITH SOAP AND WATER. IF INGESTED, DO NOT INDUCE
VOMITING. CALL A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:105F,41C
Autoignition Temp:Autoig
nition Temp Text:450 F
Lower Limits:1.0
Upper Limits:5.0
Extinguishing Media:DRY CHEMICAL, FOAM OR CARBON DIOXIDE
Fire Fighting Procedures:IF A LEAK OR SPILL HAS NOT IGNITED, USE WATER
SPRAY TO DISPERSE VAPOR & PROTECT CLEAN UP CREW.
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB
ON SUITABLE MATERIAL AND SHOVEL UP.

=====
===== Handling and Storage =

=====

Handling and Storage Precautions:STORE AWAY FROM HEAT OR OPEN FLAME.
TRANSPORT, HANDLE, AND STORE IN ACCORDANCE WITH OSHA REGULATIONS
1910.106 AND APPLICABLE DOT REGULATIONS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED
Ventilation:LOCAL EXHAUST VENTILATION RECOMMENDED
Protective Gloves:CHEMICAL RESISTANT
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:PROTECTIVE CLOTHIN
G SUCH AS UNIFORMS,
OVERALLS, OR LAB COATS
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315 TO 385F
Vapor Pres:2.7 @ 68F
Vapor Density:4.83
Spec Gravity:0.78 (WATER=1)
Viscosity:1.55 CST@100F
Evaporation Rate & Reference:0.2 (BU AC=1)
Solubility in Water:NEG.
Appearance and Odor:CLEAR, COLORLESS LIQUID; PETROLEUM ODOR
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====
=====

Stability Indicator/Materials to Avoid:YES
NONE KNOWN
Stability Condition to Avoid:NONE KNOWN
Hazardous Decomposition Products:CARBON MONOXIDE & CARBON DIOXIDE MAY
BE FORMED ON BURNING IN LIMITED AIR SUPPLY.

===== Disposal Considerations =====

Waste Disposal Methods:RE-EVALUATION OF THE PRODUCT MAY BE REQUIRED BY
THE USER AT THE TIME OF DISPOSAL.

=====

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.