

PRATT & LAMBERT, INC; INDUSTRIAL COATINGS DIV -- COATING, ALIPH. POLYUR. SAND, 33303 ID 705210 -- 8010-01-234-2935

===== Product Identification =====

Product ID:COATING, ALIPH. POLYUR. SAND, 33303 ID 705210

MSDS Date:11/01/1993

FSC:8010

NIIN:01-234-2935

MSDS Number: BSSCD

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC; INDUSTRIAL COATINGS DIV

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000/DOT: 800-255-3924

Preparer's Name:W A ELLISON

CAGE:FO127

=== Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SOLVENT) (SARA III) (VAPOR PRESSURE 16 MM HG @ 20C) (LFL 1.0; UFL 8.0)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:75 PPM;STEL 100 PPM

ACGIH TLV:50 PPM;STEL 75 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SOLVENT) (SARA III) (VAPOR PRESSURE 5 MM HG @ 20C) (LFL 1.0; UFL 7.0)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM;STEL 150 PPM

ACGIH TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qt

y:1000 LBS

Ingred Name:N-BUTYL ACETATE (SOLVENT) (VAPOR PRESSURE 10 MM HG @ 20C)
(LFL 1.7; UFL 7.6)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM;STEL 200 PPM

ACGIH TLV:150 PPM;STEL 200 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SOLVENT) (SARA III) (VAPOR PRESSURE 22 MM HG @
20C) (LFL 1.7; UFL 7.1)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 5%

Other REC Limits:* SKIN

OSHA PEL:100 PPM;STEL *150 PPM

ACGIH

TLV:100 PPM;STEL 150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:SILICA, CRYSTALLINE - CRISTOBALITE (PIGMENT)

CAS:14464-46-1

RTECS #:VV7325000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:0.05000 MG/M3

ACGIH TLV:0.05000 MG/M3

Ingred Name:SILICA, AMORPHOUS - DIATOMACEOUS EARTH (PIGMENT)

CAS:68855-54-9

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:6 MG/M3; 20 MPPCF

ACGIH TLV:10 MG/M3

Ingred Name:SILICA, CRYSTALLINE - QUARTZ (PIGMENT)

CAS:14808-60-7

RT

ECS #:VV7330000

Fraction by Wt: