

CASTROL INC, SPECIALTY PRODUCTS DIV. -- BRAYCO 300, PN:03005 -- 9150-00-273-2389

=====  
Product Identification  
=====

Product ID:BRAYCO 300, PN:03005

MSDS Date:07/26/1991

FSC:9150

NIIN:00-273-2389

MSDS Number: BSYYB

=== Responsible Party ===

Company Name:CASTROL INC, SPECIALTY PRODUCTS DIV.

Address:16715 VON KARMAN AVE.,SUITE230

City:IRVINE

State:CA

ZIP:92714

Country:US

Info Phone Num:714-660-9414

Emergency Phone Num:714-660-9414/800-424-9300(CHEMTREC)

Preparer's Name:RICHARD DE VICARIIS

CAGE:EO453

=== Contractor Identification ===

Company Name:CASTROL INC, SPECIALTY PRODUCTS DIVISION

Address:16715 VON KARMAN AVE SUITE 230

City:IRVINE

State:CA

ZIP:92714

Country:US

Phone:714-660-9414

CAGE:EO453

Company Name:CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS  
DIV

Address:1001 WEST 31ST STREET

Box:City:DOWNERS GROVE

State:IL

ZIP:60515-1280

Country:US

Phone:800-621-2661/ FAX: 630-241-  
4140

CAGE:2R128

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:64742-46-7

RTECS #:JN9379645

Fraction by Wt: 70-100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL MIST)

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chroni

c:ACUTE:EYE/SKIN:IRRIT. INGEST:GI IRRIT.

CHRONIC:EXCESSIVE INHAL OF VAPORS MAY CAUSE NASAL/RESPIRATORY IRRIT.

Effects of Overexposure:EYE:REDNESS, TEARIANG, BLURRED VISION.

SKIN:DEFATTING, DERMATITUS. INHAL:DIZZINESS, NAUSEA, HEADACHE, POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION.

Medical Cond Aggravated by Exposure:NONE KNOWN PER MANUFACTURER'S MSDS.

=====  
===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING. WIPE MATERIAL FROM SKIN.

WASH THOROUGHLY W/SOAP & WATER. EYE:FLUSH W/LG AMTS OF CLEAN WATER FOR LEAST 15MINS. CONTACT DOCTOR IF IRRIT PERSISTS. INGEST:DO NOT INDUCE VOMITING; ASPIRATION HAZARD. SEE DOCTOR IMMED. INHAL:REMOVE FROM AREA OF EXPOSURE. ADMINISTER OXYGEN IF DEEMED NECESSARY. IF BREATHING HAS STOPPED, ADMINISTER CPR. CONTACT DOCTOR.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:>275F,>135C

Extinguishing Media:DRY CHEMICAL, CARBON DIOXIDE, FOAM.

Fire Fighting Procedures:USE WATER AS FOG OR SPRAY TO COOL FIRE EXPOSED CONTAINERS. WEAR SELF-CONTAINER BREATHING APPARATUS IN POSITIVE PRESSURE MODE IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUE OR VAPORS WHICH CAN IGNITE EXPLOSIVELY.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:DO NOT PERMIT PRODUCT TO ENTER STREAMS, SEWERS OR OTHER WATERWAYS. DIKE SPILL AND ELIMINATE LEAK. ABSORB W/INERT

MATERIAL AND STORE IN CLOSED CONTAINERS TIL DISPOSAL.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:MAINTAIN AMBIENT TEMPERATURES. AVOID PROLONGED/REPEATED BREATHING OF VAPORS/MISTS/FUMES. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:DO NOT STORE NEAR HEAT, FLAME, STRONG OXIDANTS. MAINTAIN ADEQUATE VENTILATION.

=====  
===== Exposure Contr

ols/Personal Protection =====

Respiratory Protection:NIOSH/MSHA-APPROVED ORGANIC VAPOR RESPIRATOR OR SUPPLIED AIR RESPIRATORY EQUIPMENT AS REQUIRED.

Ventilation:PROVIDE SUFFICIENT MECHANICAL,GENERAL &/OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.GREATER THAN 60 F3/MIN RECOMMEND

Protective Gloves:NEOPRENE

Eye Protection:CHEM SPLASH GOGGLES &/OR SAFETY GLASSES

Other Protective Equipment:IMPERVIOUS GARMENTS AS REQUIRED. EYEWASH, SAFETY SHOWER.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING. LAUNDDRY CONTAMINATED CLOTHING PRIOR TO REUSE.

Supplemental Safety and Health

BURMAH-CASTROL INC IS OLD NAME FOR CASTROL INC. BRAY PRODUCT DIV BECAME SPECIALTIES PRODUCT DIV. SEE PNIND A FOR EARLIER MSDS UNDER THESE COMPANIES' NAMES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>500F,>260C

Spec Gravity:0.88

Evaporation Rate & Reference: