

LHB INDUSTRIES -- SO-SURE GLOSS BLACK SPRAY PAINT 17038 (14-190)

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 00-290-6984
MSDS Date: 03/25/1993
MSDS Num: BSYYF
Product ID: SO-SURE GLOSS BLACK SPRAY PAINT 17038 (14-190)
MFN: 03
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City
: SAINT LOUIS MO 63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 314-522-3141 OR 800-424-9300
Preparer's Name: RUDOLF OPPENHEIM
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
==

=====
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-665D
Unit of Issue: PT
UI Container Qty: 0

=====
Ingredients
=====

=====
Cas: 8030-30-6
RTECS #: DE3030000
Name: VM&P NAPHTHA
% Wt: 9.06
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 300 PPM
ACGIH TLV: 300 PPM

Cas: 108-88-3
RTECS #: XS5250000
Name: TOLUENE (SARA III)
% Wt: 23.17
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 200 PPM
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 67-64-1
RTECS #: AL3150000
Name: ACETONE (SARA III)
% Wt: 25.25
Other R
EC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV: 750 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 16.72
Other REC Limits: NONE RECOMMENDED
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

Cas: 75-28-5
RTECS #: TZ4300000
Name: ISOBUTANE
% Wt: 4.11
Other REC Limits: NONE RECOMMENDED
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 800 PPM

Cas: 106-97-8
RTECS #: EJ4

200000

Name: N-BUTANE

% Wt: 6.58

Other REC Limits: NONE RECOMMENDED

OSHA PEL: 800 PPM

ACGIH TLV: 800 PPM

RTECS #: 9999999VO

Name: VOC: 85%

Other REC Limits: NONE RECOMMENDED

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALING

HARMFUL OR FATAL. REPEATED OR

PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN & NERVOUS SYSTEM
DAMAGE. IN CONFINED AREA, HIGH CONCENTRATIONS ARE ANESTHETIC. SKIN & RESP
IRATORY TRACT IRRITATION. LIGHT HEADEDNESS, STAGGERING, GIDDINESS, NAUSEA.
HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs And Symptoms Of Overexposure: IRRITATION TO EYES, THROAT, AND
RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMEN

TS.

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH SOAP & WATER; WASH
CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES
& CONTACT PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWE D, DO NOT
INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR.
GIVE ARTIFICIAL RESPIRATION IF NECESSARY & GET MEDICAL AID. NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

=====
Handlin
g and Disposal
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE IN ACCORD WITH FEDERAL, STATE, LOCAL
REGULATIONS. DO NOT PUNCTURE, INCINERATE OR STORE ABOVE 120F. EXPOSURE TO
HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN
IN TRASH PICK-UP. DO NOT PLACE IN HOME TRASHCOMPACTOR.

Handling And

Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER PRESSURE. DO NOT STORE WHERE TEMPERATURE MAY EXCEED 120F. AVOID BREATHING SPRAY, MIST, OR VAPORS.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION. READ ENTIRE LABEL BEFORE USING. FOLLOW ALL LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING OR SWALLOWING CO NTENTS MAY BE HARMFUL OR FATAL.

=====
Fire and Explosi
on Hazard Information
=====

Flash Point Text: NR

Autoignition Temp Text: 874 F

Lower Limits: 1.8

Upper Limits: 9.5

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY. AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED CONTAINERS. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL FROM BURSTING, RUPTURING OR VENTING OF CONTAINERS.

Unusual Fire/

Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED TEMPERATURE (>120F) CONTAINERS MAY VENT, RUPTURE OR BURST. AEROSOL CONTAINER; DO NOT EXPOSE TO TEMPERATURE ABOVE 120F.

=====
Control Measures
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT POINT OF MIST OR SPRAY RELE ASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

HCC: V3

Vapor Pres: 60 @ 68F

Vapor Density: >1.5

Spec Gravity: 0.867 (WATER=1)

Solubilit

y in Water: INSOLUBLE

Appearance and Odor: GLOSS BLACK / PAINT

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT

Hazardous Decomposition Products: CARBON MONOXIDE AND POSSIBLE HYDROGEN
CHLORIDE

Hazardous Polymerization Indicator: NO
=====

Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Infor
mation
=====

=====
Transportation Information
=====

Responsible Party Cage: 0FTT5

Trans ID NO: 67800

Product ID: SO-SURE GLOSS BLACK SPRAY PAINT 17038 (14-190)

MSDS Prepared Date: 03/25/1993

Review Date: 03/31/1994

MFN: 3

Multiple KIT Number: 0

Review IND: Y

Unit Of Issue: PT

Container QTY: 0
=====

=

Detail DOT Information

=====
DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

Detail IMO Information

=====
IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT
?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

Detail IATA Information

=====
IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG

Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====

Detail AFI Information

=====
AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

HAZCOM Label
=====

=====
Product ID: SO-SURE GLOSS BLACK SPRAY PAINT 17038 (14-190)

Cage: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING HARMFUL OR FATAL. REPEATED
OR PROLONGED OVEREXPOSURE ASSOCIATED WI

TH PERMANENT BRAIN & NERVOUS

SYSTEM DAMAGE. IN CONFINED AREA, HIGH CONCENTRATIONS ARE ANESTHETIC. SKIN
& RESP IRATORY TRACT IRRITATION. LIGHT HEADEDNESS, STAGGERING, GIDDINESS,
NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES,
THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

=====
Disclaimer (provided with this information by the compiling agencies): This
information is formulated

for use by elements of the Department of Defense.

The United States of America in no manner whatsoever expressly or implied
warrants, states, or intends said information to have any application, use or
viability by or to any person or persons outside the Department of Defense
nor any person or persons contracting with any instrumentality of the United
States of America and disclaims all liability for such use. Any person
utilizing this instruction who is not a military or civilian e

mployee of the

United States of America should seek competent professional advice to verify
and assume responsibility for the suitability of this information to their
particular situation regardless of similarity to a corresponding Department
of Defense or other government situation.