View NSN Online: https://aerobasegroup.de/nsn/6850-01-005-2035

SYNFAX MFG INC DBA COPYGRAPHICS -- DISPERSANT -- 6850-01-005-2035

Product ID:DISPERSANT MSDS Date:04/14/1994

FSC:6850

NIIN:01-005-2035

Kit Part:Y

MSDS Number: BSYZD === Responsible Party ===

Company Name: SYNFAX MFG INC DBA COPYGRAPHICS

Address:134 CLINTON RD

City:FAIRFIELD

State:NJ

ZIP:07006-2914

Country:US

Info Phone Num:201-882-0690 Emergency Phone Num:201-882-

0690

Preparer's Name: DGSC-SHH

CAGE:6Z787

=== Contractor Identification ===
Company Name:COPYSTATICS INC
Address:5773 MIAMI LAKES DR E

Box:City:MIAMI

State:FL

ZIP:33014-2417 Country:US CAGE:33770

Company Name: SYNFAX MFG INC DBA COPYGRAPHICS

Address:134 CLINTON RD

Box:City:FAIRFIELD

State:NJ

ZIP:07006-2914 Country:US

Phone:201-882-0690

CAGE:6Z787

======= Composition/Information on Ingredients ========

Ingred Name: HYDROTREATED HEAVY NAPHTHA

CAS:64742-48-9 Fraction by Wt: 100%

Other R

EC Limits:NONE RECOMMENDED

========= Hazards Identification ================

LD50 LC50 Mixture:LD50 (ORAL, RAT) IS UNKNOWN. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: ACUTE- EYE CONTACT MAY CAUSE

IRRITATION. REPEATED/PROLONGED SKIN CONTACT MAY CAUSE DEFATTING. MAY CAUSE RESPIRATORY & GI TRACT IRRITATION & VOMITING. CHRONIC-

STUDIES HAVE SHOWN THAT MANY PETROLEUM HY D

ROCARBONS & SYNTHETIC

HYDROCARBONS POSE POTENTIAL HUMAN HEALTH RISKS WHICH MAY VARY FROM ONE PERSON TO ANOTHER.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HIGH VAPOR CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHE AND DIZZINESS, ARE ANESTHETIC, AND MAY HAVE OTHER CENTRAL NERVO US SYSTEM EFFECTS.

Medical Cond Aggravated by Exposure: NOT KNOWN

==:	 First A	Aid M	easur
es	 ===		

First Aid:GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. SKIN:REMOVE CONTAMINATED CLOTHING. FLUSH SKIN WITH WATER, THEN WASH WITH SOAP & WATER. EYE:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. INHALED:REM OVE TO FRESH AIR. PROVIDE OXYGEN/CPR IFNEEDED. ORAL:DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. GET MEDICAL ATTENTION.


	Fire Fighting
Moscuroc	

Flash Point Method:TCC Flash Point:120F,49C Lower Limits:0.7 Upper Limits:6.5

Extinguishing Media:CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures:WEAR NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. IF A LEAK HAS IGNITED, USE WATER SPRAY TO DISPERSE VAPORS AND PROTECT FIRE FIGHTERS.

Unusual Fire/Explosion Hazard: CONTAINERS MAY RUPTURE DUE TO INTERNAL PRESSURE BUI



lubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR LIQUID, FAINT PETROLEUM HYDROCARBON ODOR
Percent Volatiles by Volume:100

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE OR CONCENTRATED OXYGEN
Stability Condition to Avoid:EXCESSIVE HEAT, FLAME, SPARKS
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER DECOMPOSITION PRODUCTS

	≔=== Disp
osal Considerations	=======================================

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person u tilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.