View NSN Online: https://aerobasegroup.de/nsn/6850-01-387-6591

EASTMAN KODAK CO -- 828 8581 KODAK HX TONER, BLACK -900 GRAMS -- 6850-01-387-6591

============= Product Identification ========================

Product ID:828 8581 KODAK HX TONER, BLACK -900 GRAMS

MSDS Date:08/22/1992

FSC:6850

NIIN:01-387-6591

MSDS Number: BSZKJ === Responsible Party ===

Company Name: EASTMAN KODAK CO

Address:343 STATE ST City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Info Phone Num:800-242-2424

Emergency

Phone Num:716-722-5151/716-724-4501

CAGE:19139

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST Box:City:ROCHESTER

State:NY

ZIP:14650-1115 Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

======= Composition/Information on Ingredients ========

Ingred Name:BUTYL ACRYLATE-P-DIVINYLBENZENE-STYRENE \*93-4\*

CAS:57516-68-4

Fraction by Wt: 90-95%

Ingred Name: COLUMBIA CARBON, CARBON BLACK, LAMPBLACK, BLACK PEARLS

С

AS:1333-86-4

RTECS #:FF5800000 Fraction by Wt: 5-10%

Other REC Limits:3.5 MG/CUM (NIOSH)

OSHA PEL:3.5 MG/CUM ACGIH TLV:3.5 MG/CUM

Ingred Name:BENZYLDIMETHYLOCTADECYLAMMONIUM 3-NITRO-BENZENESULFONATE

\*93-4\*

CAS:124088-59-1 Fraction by Wt: < 2%

========= Hazards Identification =============

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: IRRITATION OF THE

RESPIR

ATORY TRACT & PNEUMOCONIOSIS (W/CHRONIC EXPOSURE). LOW HAZARD FOR ACUTE INHALATION/INGESTION. EYES: IRRITATION. Explanation of Carcinogenicity:NONE
======================================
First Aid:INHALATION: MOVE TO FRESH AIR. EYES: WASH IMMEDIATELY W/WATER. SKIN: WASH W/SOAP & WATER. INGESTION: DRINK 1-2 GLASSES OF WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Extinguishing Media: WATER SPRAY, CO2, DRY CHEMICAL Unusual Fire/Explosion Hazard:POWDERED MATERIAL MAY FORM EXPLOSIVE DUST-AIR MIXTURES.
========= Accidental Release Measures ==========
Spill Release Procedures:DON'T USE A VACUUM CLEANER TO CLEAN UP SPILLS OF POWDERED TONERS. THE VERY FINE PARTICIES CAN CAUSE A FIRE/EXPLOSION. SWEEP MATERIAL ONTO PAPAER & PLACE IN A FIBER CARTON.
=========== Handling and Storage ============
Handling and Storage Precautio ns:KEEP CONTAINER CLOSED. Other Precautions:AVOID BREATHING DUST. USE W/ADEQUATE VENTILATION. KEEP FROM CONTACT W/OXIDIZING MATERIALS.
====== Exposure Controls/Personal Protection ========
Ventilation:RECOMMENDED Protective Gloves:IMPERVIOUS Eye Protection:RECOMMENDED Work Hygienic Practices:WASH THOROUGHTLY AFTER HANDLING. Supplemental Safety and Health
======== Physical/Chemical Properties =========
Vapor Pres:NEGLIGIBLE Vapor Density:NEGLIGIBLE Evapo

======= S	tability and Reactivity Data	=======================================
Percent Volatiles by Volu	me:NEGL	
Appearance and Odor:BL	_ACK POWDER W/SLIGHT	ODOR.
Solubility in Water:ISOLU	JBLE	
ration Rate & Refere	ince:NEGLIGIBLE	

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Hazardous Decomposition Products:CO2, CARBON MONOXIDE

======= Disposal Considerations ============

Waste Disposal Methods:INCINERATE/LANDFILL. CAN BE INCINERATED WHEN IN COMPLIANCE W/LO
CAL REGULATIONS. DISCHARGE, TREATMENT, OR DISPOSAL
MAY BE SUBJECT TO NATIONAL, STATE, OR LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.