

LHB INDUSTRIES -- ECO-SURE GREEN 14062 (674-140) P/N 672C840

=====
MSDS Safety Information
=====

FSC: 8010
NIIN: 01-336-3980
MSDS Date: 01/01/1993
MSDS Num: BTGML
Product ID: ECO-SURE GREEN 14062 (674-140) P/N 672C840
MFN: 02
Responsible Party
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST.
LOUIS MO 63134
Info Phone Number: 314-522-3141
Emergency Phone Number: 800-424-9300 CHEMTREC/ 314-522-3141
Preparer's Name: RUDOLF OPPENHEIM
Review Ind: Y
Published: Y

=====
Preparer Co. when other than Responsible Party Co.
=====

Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134

=====
Contractor Summary
===

=====
Cage: 0FTT5
Name: LHB INDUSTRIES
Address: 8833 FLEISCHER PLACE
City: ST. LOUIS MO 63134
Phone: 314-522-3141

=====
Item Description Information
=====

Item Manager: GSA
Item Name: ENAMEL
Specification Number: A-A-2787
Unit of Issue: PT
UI Container Qty: 0

=====
Ingredients
=====

=====
Cas: 1330-20-7
RTECS #: ZE2100000
Name: XYLENE (SARA III)
% Wt: <20.27
Other REC Limits: NONE RECOMME
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: 100 PPM
EPA Rpt Qty: 1000 LBS
DOT Rpt Qty: 1000 LBS

Cas: 110-12-3
RTECS #: MP3850000
Name: METHYL ISOAMYL KETONE
% Wt: 6.02
Other REC Limits: NONE RECOMME
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 64742-95-6
RTECS #: SE7546500
Name: AROMATIC 150
% Wt: <3.01
Othe
r REC Limits: NONE RECOMME
OSHA PEL: 5 PPM
ACGIH TLV: 5 PPM

Cas: 64742-95-6
RTECS #: SE7546500
Name: AROMATIC 100
% Wt: 6.02
Other REC Limits: NONE RECOMME
OSHA PEL: 50 PPM
ACGIH TLV: 50 PPM

Cas: 108-10-1
RTECS #: SA9275000
Name: METHYL ISOBUTYL KETONE (SARA III)
% Wt: <3.01
Other REC Limits: NONE RECOMME
OSHA PEL: 100 PPM
ACGIH TLV: 50 PPM
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 107-87-9
RT

ECS #: SA7875000
Name: METHYL PROPYL KETONE
% Wt: <3.01
Other REC Limits: NONE RECOMME
OSHA PEL: 200 PPM
ACGIH TLV: 200 PPM

Cas: 95-63-6
RTECS #: DC3325000
Name: 1,2,4-TRIMETHYLBENZENE (SARA III)
% Wt: <3.01
Other REC Limits: NONE RECOMME
OSHA PEL: 25 PPM
ACGIH TLV: 25 PPM

Cas: 71-36-3
RTECS #: EO1400000
Name: N-BUTYL ALCOHOL (SARA III)
% Wt: <3.01
Other REC Limits: NONE RECOMME
OSHA PEL: 50 PPM
ACGIH TLV: 100 PPM
EPA Rpt Q
ty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Cas: 115-10-6
RTECS #: PM4780000
Name: DIMETHYL ETHER
% Wt: 8.06
Other REC Limits: NONE RECOMME
OSHA PEL: NOT ESTABLISHED
ACGIH TLV: NOT ESTABLISHED

Cas: 74-98-6
RTECS #: TX2275000
Name: PROPANE
% Wt: 14.52
Other REC Limits: NONE RECOMME
OSHA PEL: 1000 PPM
ACGIH TLV: 1000 PPM

RTECS #: 9999999VO
Name: VOC: 65%
Other REC Limits: NONE RECOMME
=====

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENTRATING & INHALING CONTENTS HARMFUL/FATAL.

REPEATED/PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN &
NERVOUS

SYSTEM DAMAGE. IN CONFINED AREA, HIGH CONCENTRATIONS ARE ANESTHETIC. SKIN
& RESPIRATORY TRACT IRRITATION. LIGHT HEADED, ST
AGGERING, GIDDINESS,

NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs And Symptoms Of Overexposure: IRRITATION TO EYES, THROAT, AND
RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

Medical Cond Aggravated By Exposure: RESPIRATORY AILMENTS

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH WATER; WASH CLOTHES
BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES &
CONTACT A PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE

VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR. GIVE
ARTIFICIAL RESPIRATION IF NECESSARY. GET MEDICAL AID. NEVER GIVE ANYTHING BY
MOUTH TO AN UNCONSCIOUS PERSON.

=====
Handling and Disposal
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.

MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE IN ACCORD

WITH FEDERAL, STATE, LOCAL

REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR STORE ABOVE 120F. EXPOSURE TO
HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN
IN T RASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

Handling And Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER
PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F. AVOID BREATHING
SPRAY, MIST, OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION

READ ENTIRE LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING & INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

=====
Fire and Explosion Hazard Information
=====

Flash Point Text: NR

Autoignition Temp Text: 662 F

Lower Limits: 2.2

Upper Limits: 18.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.
AVOID SPREADING ANY BURNING LIQUID
WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED
CONTAINER. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING,
RUPTURING OR VENTING OF CONTAINER.

Unusual Fire/Explosion Hazard: DO NOT SPRAY NEAR OPEN FLAME. AT ELEVATED
TEMPERATURE (>120F) CONTAINER MAY VENT, RUPTURE, OR BURST. AEROSOL
CONTAINER; DO NOT EXPOSE TO TEMPERATURE ABOVE 120F.

=====
Control Measures
=====

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT
POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO PROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH
STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE
WHILE USING PRODUCT.

=====
Physical/Chemical Properties
=====

HCC: V3

Vapor Pres: 70 @ 68F

Vapor Density: >1.522

Spec Gravity: 1.063 (WATER=1)

Solubility in Water: INSOLUBLE

Appearance and Odor: GREEN / PAINT

=====
Reactivity Data
=====

Stability Indicator: YES

Stability Condition To Avoid: EXTREME HEAT

Hazardous Decompositio

n Products: CARBON MONOXIDE
Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
Transportation Information
=====

Responsible Party Cage: 0FTT5
Trans ID NO: 126892
Product ID: ECO-SURE GREEN 14062 (674-140) P/N 672C840
MSDS P
repared Date: 01/01/1993
Review Date: 01/05/1993
MFN: 2
Multiple KIT Number: 0
Review IND: Y
Unit Of Issue: PT
Container QTY: 0

=====
Detail DOT Information
=====

DOT PSN Code: DTJ
Symbols: D
DOT Proper Shipping Name: CONSUMER COMMODITY
Hazard Class: ORM-D
Label: NONE
Non Bulk Pack: 156,306
Bulk Pack: NONE
Max Qty Pass: 30KGGROSS
Max Qty Cargo: 30KGGROSS
Vessel Stow Req: A
=====

=====
Detail IMO Information
=====

IMO PSN Code: AKH
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?
IMDG Page Number: SEE 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13
=====

=====
Detail IATA Information
=====

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper
Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203
=====

=====
Detail AFI Information
=====

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPA
CITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3
=====

=====
HAZCOM Label
=====

Product ID: ECO-SURE GREEN 14062 (674-140) P/N 672C840
Cage: 0FTT5
Company Name: LHB INDUSTRIES
Street: 8833 FLEISCHER PLACE
City: ST. LOUIS MO
Zipcode: 63134
Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141
Label Required IND: Y
Date Of Label Review: 12/16/1998
S

tatus Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING CONTENTS HARMFUL/FATAL.

REPEATED/PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN & NERVOUS

SYSTEM DAMAGE. IN CONFINED AREA, HIGH CONCENTRATIONS ARE ANESTHETIC. SKIN & RESPIRATORY TRACT IRRITATION. LIGHT HEADED, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.