

LHB INDUSTRIES -- ECO-SURE GRAY 36118 (674-380) P/N 672C887

=====  
MSDS Safety Information  
=====

FSC: 8010  
NIIN: 01-348-3060  
MSDS Date: 02/22/1993  
MSDS Num: BTGMS  
Product ID: ECO-SURE GRAY 36118 (674-380) P/N 672C887  
MFN: 02  
Responsible Party  
Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST.  
LOUIS MO 63134  
Info Phone Number: 314-522-3141  
Emergency Phone Number: 314-522-3141 OR 800-424-9300  
Preparer's Name: RUDOLF OPPENHEIM  
Review Ind: Y  
Published: Y

=====  
Preparer Co. when other than Responsible Party Co.  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134

=====  
Contractor Summary  
=====

Cage: 0FTT5  
Name: LHB INDUSTRIES  
Address: 8833 FLEISCHER PLACE  
City: ST. LOUIS MO 63134  
Phone: 314-522-3141

=====  
Item Description Information  
=====

Item Manager: GSA  
Item Name: ENAMEL  
Specification Number: A-A-2787  
Type/Grade/Class: TYPE 1  
Unit of Issue: PT  
UI Container Qty: 0  
Type of Container: METAL  
=====

=====

Ingredients

=====

Cas: 1330-20-7  
RTECS #: ZE2100000  
Name: XYLENE (SARA III)  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----

Cas: 108-88-3  
RTECS #: XS5250000  
Name: TOLUENE (SARA III)  
% Wt: 15.06  
Other REC Limits: NONE RECOMME  
OSHA PEL: 200 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 1000 LBS  
DOT Rpt Qty: 1000 LBS

-----

-----

Cas: 110-12-3  
RTECS #: MP3850000  
Name: METHYL ISOAMYL KETONE  
% Wt: 6.52  
Other REC Limits: NONE RECOMME  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM

-----

Cas: 64742-95-6  
RTECS #: SE7546500  
Name: AROMATIC 150  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: 5 PPM  
ACGIH TLV: 5 PPM

-----

Cas: 64742-95-6  
RTECS #: SE7546500  
Name: AROMATIC 100  
% Wt: 6.52  
Other REC Limits: NONE RECOMME  
OSHA PEL: 50 PPM  
ACGIH TLV: 50 PPM

-----

-----  
Cas: 108-10-1  
RTECS #: SA9275000  
Name: METHYL ISOBUTYL KETONE (SARA III)  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: 100 PPM  
ACGIH TLV: 50 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

Cas: 107-87-9  
RTECS #: SA7875000  
Name: METHYL PROPYL KETONE  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: 200 PPM  
ACGIH TLV: 200 PPM  
-----

Cas: 95-63-6  
RTECS #: DC3325000  
Name: 1,2,4-TRIMETHYLBENZENE (SARA III)  
% Wt: &lt;3.  
26  
Other REC Limits: NONE RECOMME  
OSHA PEL: 25 PPM  
ACGIH TLV: 25 PPM  
-----

Cas: 71-36-3  
RTECS #: EO1400000  
Name: N-BUTYL ALCOHOL (SARA III)  
% Wt: &lt;3.26  
Other REC Limits: NONE RECOMME  
OSHA PEL: 50 PPM  
ACGIH TLV: 100 PPM  
EPA Rpt Qty: 5000 LBS  
DOT Rpt Qty: 5000 LBS  
-----

Cas: 115-10-6  
RTECS #: PM4780000  
Name: DIMETHYL ETHER  
% Wt: 7.04  
Other REC Limits: NONE RECOMME  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED  
-----

--

Cas: 74-98-6

RTECS #: TX2275000

Name: PROPANE

% Wt: 12.67

Other REC Limits: NONE RECOMME

OSHA PEL: 1000 PPM

ACGIH TLV: 1000 PPM

-----  
RTECS #: 9999999VO

Name: VOC: 60%

Other REC Limits: NONE RECOMME

=====  
Health Hazards Data  
=====

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: YES

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Effects of Exposure: CONCENT

RATING & INHALING CONTENTS HARMFUL/FATAL.

REPEATED/PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN & NERVOUS

SYSTEM DAMAGE. IN CONFINED AREA, HIGH CONCENTRATIONS ARE ANESTHETIC. SKIN & RESPIRATORY TRACT IRRITATION. LIGHT HEADED, STAGGERING, GIDDINESS, NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION.

Signs And Symptions Of Overexposure: IRRITATION TO EYES, THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

Medical Cond Aggravated By Exposur

e: RESPIRATORY AILMENTS

First Aid: FOR CONTACT WITH SKIN OR CLOTHES, WASH WITH WATER; WASH CLOTHES BEFORE REUSE. FOR CONTACT WITH EYES, FLUSH WITH WATER FOR 15 MINUTES. CONTACT PHYSICIAN/OPHTHALMOLOGIST IMMEDIATELY. IF SWALLOWED, DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL AID. IF INHALED, REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NECESSARY. GET MEDICAL AID. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====  
Handl

## ing and Disposal

=====  
Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION AND VENTILATE AREA.  
MOP SPILLS WITH INERT ABSORBENT. AVOID BREATHING VAPORS.

Waste Disposal Methods: DISPOSE IN ACCORD WITH FEDERAL, STATE, LOCAL  
REGULATIONS. DO NOT PUNCTURE, INCINERATE, OR STORE ABOVE 120F. EXPOSURE TO  
HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE CAN TO BURST. DISCARD EMPTY CAN  
IN T RASH PICK-UP. DON'T PLACE IN HOME TRASHCOMPACTOR.

## Handling A

nd Storage Precautions: KEEP OUT OF REACH OF CHILDREN. CONTENTS UNDER  
PRESSURE. DO NOT STORE WHERE TEMPERATURES MAY EXCEED 120F. AVOID BREATHING  
SPRAY, MIST, OR VAPOR.

Other Precautions: AVOID CONTACT WITH EYES AND SKIN. USE WITH GOOD VENTILATION.  
READ ENTIRE LABEL DIRECTIONS. INTENTIONAL MISUSE BY DELIBERATELY  
CONCENTRATING & INHALING OR SWALLOWING CONTENTS MAY BE HARMFUL OR FATAL.

## ===== Fire and Explosion Hazard Information

=====  
Flash Point Text: NR

Autoignition Temp Text: 662 F

Lower Limits: 2.2

Upper Limits: 18.0

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, SAND, WATER SPRAY.  
AVOID SPREADING ANY BURNING LIQUID WITH WATER SPRAY.

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE, USE TO COOL FIRE EXPOSED  
CONTAINER. WEAR SCBA. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING,  
RUPTURING OR VENTING OF CONTAINER.

Unusual Fire/Explosion Hazard: DO NOT SPR  
AY NEAR OPEN FLAME. AT ELEVATED

TEMPERATURE (>120F) CONTAINER MAY VENT, RUPTURE, OR BURST. AEROSOL  
CONTAINER; DO NOT EXPOSE TO TEMPERATURE ABOVE 120F.

## ===== Control Measures

Respiratory Protection: NONE BELOW TLV. USE NIOSH/MSHA APPROVED MASK ABOVE TLV.

Ventilation: LOCAL EXHAUST: PREFERRED. MECHANICAL (GENERAL): ACCEPTABLE AT  
POINT OF MIST OR SPRAY RELEASE.

Protective Gloves: TO P

ROTECT SKIN

Eye Protection: CHEMICAL SPLASH GOGGLES

Other Protective Equipment: IMPERVIOUS CLOTHES TO PROTECT SKIN. EYE WASH  
STATION.

Work Hygienic Practices: USE GOOD PERSONAL HYGIENE. DO NOT EAT, DRINK, OR SMOKE  
WHILE USING PRODUCT.

## ===== Physical/Chemical Properties

HCC: N1

Vapor Pres: 70 @ 68F

Vapor Density: >1.522

Spec Gravity: 1.190 (WATER=1)

Solubility in Water: INSOLUBLE

Appe

arance and Odor: GRAY / PAINT

=====  
Reactivity Data  
=====

Stability Indicator: YES  
Stability Condition To Avoid: EXTREME HEAT  
Hazardous Decomposition Products: CARBON MONOXIDE  
Hazardous Polymerization Indicator: NO  
=====

Toxicological Information  
=====

=====  
Ecological Information  
=====

MSDS Transport Information  
=====

Regulatory Information  
=====

Other Information  
=====

=====  
Transportation Information  
=====

Responsible Party Cage: 0FTT5  
Trans ID NO: 128010  
Product ID: ECO-SURE GRAY 36118 (674-380) P/N 672C887  
MSDS Prepared Date: 02/22/1993  
Review Date: 01/05/1993  
MFN: 2  
Multiple KIT Number: 0  
Review IND: Y  
Unit Of Issue: PT  
Container QTY: 0  
Type Of Container: METAL  
=====

Detail DOT Information  
=====

=====  
DOT PSN Code: DTJ  
Symbols: D  
DOT Proper Shipping Name: CONSUMER COMMODITY  
Hazard Class: ORM-D  
Label: NONE  
Non Bulk Pack: 156,306  
Bulk Pack: NONE  
Max Qty Pass: 30KGGROSS  
Max Qty Cargo: 30KGGROSS  
Vessel Stow Req: A  
=====

=====  
Detail IMO Information  
=====

IMO PSN Code: AKH  
IMO Proper Shipping Name: AEROSOLS/AEROSOL PRODUCT ?  
IMDG Page Number: SEE 9022  
UN Number: 1950  
UN Hazard Class: 9?  
IMO Packaging Group: -  
Subsidiary Risk Label: -  
EMS Number: 2-13  
=====

=====  
Detail IATA Information  
=====

IATA PSN Code: ALS  
IATA UN ID Num: 1950  
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE  
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)  
IATA UN Class: 2.1  
IATA Label: FLAMMABLE GAS  
Packing Note Passenger: 203  
Max Quant Pass: 75KG  
Max Quant Cargo: 150KG  
Packaging Note Cargo:  
203  
=====

=====  
Detail AFI Information  
=====

AFI PSN Code: ALR  
AFI Symbols: \*  
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.  
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)  
AFI Hazard Class: 2.1  
AFI UN ID NUM: UN1950  
Special Provisions: P4  
Back Pack Reference: A6.3  
=====

=====  
HAZCOM Label  
=====

Pr

Product ID: ECO-SURE GRAY 36118 (674-380) P/N 672C887

Cage: 0FTT5

Company Name: LHB INDUSTRIES

Street: 8833 FLEISCHER PLACE

City: ST. LOUIS MO

Zipcode: 63134

Health Emergency Phone: 800-424-9300 CHEMTREC/ 314-522-3141

Label Required IND: Y

Date Of Label Review: 12/16/1998

Status Code: C

Label Date: 12/16/1998

Origination Code: G

Hazard And Precautions: CONCENTRATING & INHALING CONTENTS HARMFUL/FATAL.

REPEATED/PROLONGED OVEREXPOSURE ASSOCIATED WITH PERMANENT BRAIN &

NERVOUS

SYSTEM DAMAG

E. IN CONFINED AREA, HIGH CONCENTRATIONS ARE ANESTHETIC. SKIN

& R ESPIRATORY TRACT IRRITATION. LIGHT HEADED, STAGGERING, GIDDINESS,

NAUSEA. HARMFUL IF SWALLOWED. SEVERE EYE IRRITATION. IRRITATION TO EYES,

THROAT, AND RESPIRATORY TRACT. MAY CAUSE HEADACHES, NAUSEA, AND VOMITING.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should se

ek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.