

BAKER SEALANTS AND COATINGS CO. -- FILLER, WOOD, PLASTIC -- 8010-00-664-7088

=====
Product Identification
=====

Product ID:FILLER, WOOD, PLASTIC

MSDS Date:03/19/1991

FSC:8010

NIIN:00-664-7088

MSDS Number: BTKRK

=== Responsible Party ===

Company Name:BAKER SEALANTS AND COATINGS CO.

Address:234 SUYDAM AVENUE

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Info Phone Num:201-333-6986

Emergency P

hone Num:201-333-6986

CAGE:34094

=== Contractor Identification ===

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fr

action by Wt: 6-3%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:400 PPM
ACGIH TLV:400 PPM/500STEL;9394

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 19-22%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:1000 PPM
ACGIH TLV:750PPM/1000STEL;9294
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25-35%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/30
OSTEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES-SEVERELY IRRITATION. IF NOT
REMOVE PROPERLY WILL INJURE EYE TISSUE, WHICH MAY RESULT IN
PERMANENT DAMAGE. SKIN-PROLONGED CONTACT MAY IRRITATE & CAUSE
DERMATITIS. INGESTIONLOW ORDER OF TOXICITY. SMALL AMOUNTS
ASP
IRATED INTO THE LUNGS MAY CAUSE BRONCHIOPHEUMONIA OR PULMONARY
EDEMA.
Explanation of Carcinogenicity:NOT CARCINOGENIC.
Effects of Overexposure:INHALATION-HIGH VAPOR CONCENTRATIONS CAUSES
IRRITATION TO THE EYES AND THE UPPER RESPIRATORY TRACT, MAY CAUSE
HEADACHE AND DIZZINESS, ARE ANESTHETIC AND MAY HAVE OTHER CENTRAL
NERVOUS SYSTEM EFFECTS.
Medical Cond Aggravated by Exposure:REPEATED SKIN CONTACT MAY CAUSE
CHAPPING.

===== First Aid Measures =====

=====

First Aid:EYE-IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MIN. GET PROMPT MEDICAL ATTENTION. SKIN-IMMEDIATELY WASH WITH LARGE AMOUNTS OF WATER, USE SOAP IF AVAILABLE. INHALATION-REMOVE VICTIM FROM EXPOSURE. ADMINISTER ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED. KEEP AT REST. CALL PHYSICIAN. INGESTION-DO NOT INDUCE VOMITING. KEEP AT REST. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:T
OC

Flash Point:-4F,-20C

Lower Limits:2.6

Upper Limits:12.8

Extinguishing Media:ALCOHOL FOAM, CARBON DIOXIDE FOAM.

Fire Fighting Procedures:AVOID UNNECESSARY EXPOSURE TO HEAT.

Unusual Fire/Explosion Hazard:INTENSE HEAT MAY CAUSE EXPLOSION OF CONTAINERS AND OR FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. PREVENT ADDITIONAL DISCHARGE OF MATERIAL. KEEP PUBLIC AWAY. KEEP AWAY FROM WATER SOURCES. CONTAIN SPILLED LIQUID WITH SAND OR EARTH.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP LIQUID & VAPOR AWAY FROM HEAT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. GROUND FIXED EQUIPMENT.

Other Precautions:FLAMMABLE LIQUID. PAINT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH-APPROVED SELF CONTAINED BREATHING APPARATUS.

Ventilation:USE EXPLOSION PROOF VENTILATION AS REQUIRED.

Prote

ctive Gloves:CHEMICAL RESISTANT GLOVES.
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
NONE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175F,79C

Melt/Freeze Pt:M.P/F.P Text: