View NSN Online: https://aerobasegroup.de/nsn/9135-00-985-7080 LIQUID CARBONIC CORP -- LIQUID NITROGEN -- 9135-00-985-7080 ============= Product Identification ======================== Product ID:LIQUID NITROGEN MSDS Date:07/01/1990 FSC:9135 NIIN:00-985-7080 MSDS Number: BTKSP === Responsible Party === Company Name:LIQUID CARBONIC CORP Address:135 S LA SALLE STREET City:CHICAGO State:IL ZIP:60603-4101 Country:US Info Phone Num:312-855-2500 Emergency Phone Num:312-855-2500 CAGE:36517 == = Contractor Identification === Company Name:LIQUID CARBONIC CORP Address:135 S LA SALLE STREET Box:City:CHICAGO State:IL ZIP:60603-4101 Country:US Phone:312-855-2500 CAGE:36517 ======= Composition/Information on Ingredients ======== Ingred Name:NITROGEN CAS:7727-37-9 RTECS #:QW9700000

RTECS #:QW9700000 Fraction by Wt: 99.9%

ACGIH TLV:ASPHYXIANT; 9192

========= Hazards Identification ==============

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogeni

First Aid:INHALE:REMOVE TO FRESH AIR. RESTORE OR SUPPORT BREATHING IF NECESSARY. KEEP WARM & AT REST. USE CAUTION WHEN ENTERING CONTAMINATED AREAS TO VENTILATE TO ACCEPTABLE OXYGEN LEVELS. FROST BITE:FLUSH AFFE CTED AREAS W/LUKE WARM WATER. **DO NOT USE HOT WATER** FOR SERIOUS CRYOGENIC FREEZING BURN,SEE PHYSICIAN IMMEDIATELY.

Extinguishing Media:NON-FLAMMABLE INERT GAS AND LIQUID Unu

sual Fire/Explosion Hazard:IF CONTAINERS ARE INVOLVED IN A FIRE, SAFELY RELOCATE OR COOL WITH WATER SPRAY.

======== Accidental Release Measures ============

Spill Release Procedures:FOLLOW SUPPLIER"S INSTRUCTIONS. LIQUID NITROGEN IS HANDLED IN VACUUM JACKETED VESSELS. IF THERE IS A MAL-FUNCTION, CONTACT THE CLOSEST SUPPLIER LOCATION IMMEDIATELY. USE IN A WELL VENTILATED AREA AND USE A "FIRST IN/FIRST OUT" INVENTORY SYSTEM.

Neutralizing Agent:NO INFORMATIO N GIVEN ON MSDS BY MFR.

========== Handling and Storage ==============

Handling and Storage Precautions:PROTECT CONTAINERS FROM PHYSICIAL DAMAGE. STORE IN COOL, DRY WELL VENTILATED AREA AWAY FROM HEAT(ABOVE 130F) & DIRECT SUNLIGHT.

Other Precautions:REFER TO CGA SAFETY BULLETIN SB-2 & PHAMPHLETS P-1,P-9,P-12 & P-14. STORE CYLINDERS UPRIGHT AND FIRMLY SECURED. USE CHECKVALVE IN LINE TO PREVENT BACK FLOW. USE ONLY DOT OR ASME CODED CYLINDERS. DO NO T REFI

LL CYLINDERS, RETURN TO SUPPLIER.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:IN IVENT OF A MAJOR LEAK, A SELF CONTAINED BREATHING APPARATUS MAY BE REQUIRED. Ventilation:LOCAL EXHAUST OR MECHANICAL GENERAL VENTILATION TO PREVENT ACCUMULATION SO AS TO EXCLUDE AND ADEQUATE OXYGEN SUPPLY. Protective Gloves:LOOSE FITTING,INSULATED Eye Protection:SAFETY GOGGLES/GLASSES PLUS FACE SHIELD Other Protective Equipment:SAFETY SHOES Work Hygienic Pract
ices:MFR: ? HMIS:USE GOOD INDUSTRIAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT. WASH THOROUGHLY BEFORE EATING OR DRINKING.
Supplemental Safety and Health NONE
========= Physical/Chemical Properties ==========
HCC:G3 NRC/State Lic Num:NONE Boiling Pt:B.P. Text:-320F,-196C Vapor Pres:760 @BP Vapor Density:0.97 Spec Gravity:0.81 @BP Solubility in Water:VAPOR - VERY SLIGHT Appearance and Odor:COLORLESS,ODORLESS GAS - LIQUID IS WATER WHITE Percent Volatiles by Volume:10 0
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES NONE Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE
======== Disposal Considerations ===========
Waste Disposal Methods:MFR GAVE NO DISPOSAL INFORMATION. HMIS:NO DISPOSAL PROBLEM. GAS WILL DIFFUSE INTO ATMOSPHERE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by

elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.