

TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO) -- VV-L-800C AM1;A9952 --
9150-00-231-6689

===== Product Identification =====

Product ID:VV-L-800C AM1;A9952

MSDS Date:05/26/1993

FSC:9150

NIIN:00-231-6689

MSDS Number: BTRTS

=== Responsible Party ===

Company Name:TECHNOLUBE PRODUCTS DIV (LUBRICATING SPECIALTY CO)

Address:8015 PARAMOUNT BLVD.

City:PICO RIVER

State:CA

ZIP:90660-4888

Country:US

Inf

o Phone Num:310-928-3311, FAX:310-928-1428

Emergency Phone Num:310-928-3311, CHEMTREC 800-424-9300

Preparer's Name:RICHARD J.EBERHARDT

CAGE:8Y842

=== Contractor Identification ===

Company Name:LUBRICATING SPECIALTIES CO. TECHNOLUBE PRODUCTS DIV

Address:3365 E. SLAUSON AVE

Box:City:LOS ANGELES

State:CA

ZIP:90058

Country:US

Phone:562-776-4033; FAX:562-776-4003

CAGE:8Y842

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED MIDDLE PETROLEUM DISTILLATE

CAS:

64742-46-7

RTECS #:JN9379645

Fraction by Wt: 212F,>100C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL. WATER OR FOAM MAY CAUSE FROTHING.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED
CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:EXPLOSION HAZARD IF IN CONFINED SPACE
WITH SOURCE OF IGNITION.COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSIT

ION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE PERSONNEL. ELIMINATE IGNITION SOURCES. VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND EQUIPMENT. DIKE AND CONTAIN. ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER AND COVER. WASH AREA WITH SOAP AND WATER.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, OPEN FLAMES AND STRONG OXIDANTS. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID EYE AND SKIN CONTACT. DO NOT BREATHE VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED. NIOSH/MSHA-APPROVED RESPIRATOR OR SCBA AS APPROPRIATE FOR EXPOSURE OF CONCERN.

Ventilation:USE GENERAL DILUTION VENTILATION.

Protective Gloves:NITRILE GLOVES.

Eye Protection

:SPLASH GOGGLES IF MISTING.

Other Protective Equipment:PROTECTIVE CLOTHING AS REQUIRED TO MINIMIZE EXPOSURE FROM PROLONGED OR REPEATED CONTACT. EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES

Supplemental Safety and Health

USED GASOLINE MOTOR OILS HAVE BEEN SHOWN TO CAUSE SKIN CANCER WHEN REPEATEDLY APPLIED TO MOUSE SKIN WITHOUT ANY EFFORT TO REMOVE THE

MATERIAL BETWEEN APPLICATIONS. THERE IS NO EVIDENCE OF A CAUSAL RELATIONSHIP BETWEEN SKIN CANCER IN HUMANS AND EXPOSURE TO USED MOTOR OIL.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>482F,>250C

Vapor Pres:1

Spec Gravity:0.878

Evaporation Rate & Reference: