

HANLEY PAINT MFG CO.,INC. -- ECONOLITE LATEX WHITE SPECIAL COLORS,37778,10P-SERIES --
8010-00-045-3478

===== Product Identification =====

Product ID:ECONOLITE LATEX WHITE SPECIAL COLORS,37778,10P-SERIES

MSDS Date:10/16/1992

FSC:8010

NIIN:00-045-3478

MSDS Number: BTSCN

=== Responsible Party ===

Company Name:HANLEY PAINT MFG CO.,INC.

Address:6050 LUCKETT COURT

City:EL PASO

State:TX

ZIP:79932

Countr

y:US

Info Phone Num:915-585-2062

Emergency Phone Num:800-228-5635

CAGE:HANLE

=== Contractor Identification ===

Company Name:HANLEY PAINT MFG CO.,INC.

Address:6050 LUCKETT COURT

Box:City:EL PASO

State:TX

ZIP:79932

Country:US

Phone:915-585-2062

CAGE:HANLE

===== Composition/Information on Ingredients =====

Ingred Name:HEMIACETALS OF METHYL-1-AZA-3,7-DIOXABICYCLO(3.3.0)OCTANE

Fraction by Wt: 0.08%

Other REC Limits:NONE RECOMMENDED

Ingred Name:VOLATILE ORGANIC COMPOUNDS

RTECS #:9

999999VO

Fraction by Wt: 12.6%

Other REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY
CAUSE IRRITATION.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY
CAUSE RESPIRATORY IRRITATION.
Explanation of Carcinogenicity:THERE ARE NO INGREDIENTS ABOVE 0.1%
WHICH ARE IDE
NTIFIED AS CARCINOGENS BY NTP,IARC OR OSHA.
Effects of Overexposure:INGEST:NAUSEA,VOMITING.
Medical Cond Aggravated by Exposure:UNLIKELY TO AGGRIVATE EXISTING
MEDICAL CONDITIONS.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH
AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF NEEDED.INGEST:GET
PROMPT QUALIFIED ME DICAL ATTENTION.IF CONS
CIOUS,INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE MEDIA APPROPRIATE FOR SURROUNDING FIRE.
Fire Fighting Procedures:USE A SELF-CONTAINED BREATHING APPARATUS AND
FULL PROTECTIVE EQUIPMENT.COOL FIRE EXPOSED CONTAINERS WITH WATER
FOG.
Unusual Fire/Explosion Hazard:MANUFACTURER STATES NONE KNOWN.

===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP WITH NON-CO
MBUSTIBLE INERT
ADSORBANT(EG.CLAY);PLACE COLLECTED MATERIEL IN AN APPROPRIATE
CONTAINER FOR DISPOSAL;CLEAN SPILL AREA TO REMOVE SLIPPERINESS.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM CHILDREN.AVOID
FREEZING.
Other Precautions:FOLLOW LABEL DIRECTIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF SPRAYED,USE A RESPIRATOR FOR LATEX PAINT

S.
Ventilation:USE GENERAL DILUTION VENTILATION.
Protective Gloves:PLASTIC OR RUBBER.
Eye Protection:CHEMICAL GOGGLES.
Other Protective Equipment:NONE
Work Hygienic Practices:USE REASONABLE CARE IN HANDLING THIS
PRODUCT.WASH HANDS AFTER USE AND BEFORE EATING.
Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Vapor Density:>1
Spec Gravity:1.38
Evaporation Rate & Reference: