

POLYMERIC SYSTEMS, INC. -- PSI-631 SILICONE SEALANT -- 8040-00-118-2695

=====
Product Identification
=====

Product ID:PSI-631 SILICONE SEALANT

MSDS Date:07/31/1990

FSC:8040

NIIN:00-118-2695

MSDS Number: BTSMF

=== Responsible Party ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:WHEATLAND AND MASON STREETS

City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Info Phone Num:215-935-1170

Emergency Phone

Num:215-935-1170

Preparer's Name:EDWARD F.CLUFF

CAGE:0KND3

=== Contractor Identification ===

Company Name:POLYMERIC SYSTEMS, INC.

Address:723 WHEATLAND STREET

Box:City:PHOENIXVILLE

State:PA

ZIP:19460

Country:US

Phone:610-935-1170

CAGE:0KND3

=====
Composition/Information on Ingredients
=====

Ingred Name:DIHYDROXPOLYDIMETHYLSILOXANE

CAS:70131-67-8

Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Other REC Limits:NONE

RECOMMENDED
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:0.1 MG/M3 RDUST;9394

Ingred Name:DIMETHYL SILOXANE (DOW CORNING 200)
CAS:63148-62-9
RTECS #:JT6484500
Other REC Limits:NONE RECOMMENDED

Ingred Name:SILICA, AMORPHOUS, PRECIPITATED AND GEL
CAS:112945-52-5
RTECS #:VV7310000
Other REC Limits:NONE RECOMMENDED
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3; 9293

Ingred Name:METHYL OXIMINO SILANE
CAS:22984-54-9
Other REC Limits:NONE RECOMMENDED

Ingred Name:METHYLETHYLKETOXIME
CAS:29129-02-0
Fraction by Wt: 4%
Oth
er REC Limits:NONE RECOMMENDED

===== Hazards Identification =====

LD50 LC50 Mixture:TWA FOR CRYSTALLINE SILICA IS 10MG/M3
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYES:MAY CAUSE IRRITATION.SKIN:MAY
CAUSE IRRITATION.INGEST:MAY CAUSE GI TRACT IRRITATION.INHAL:MAY
CAUSE RESPIRATORY IRRITATION AND CNS DEPRESSION.
Explanation of Carcinogenicity:CRYSTALLI
NE SILICA IS POTENTIAL
CARCINOGEN.
Effects of Overexposure:INHAL:NARCOTIC EFFECT.
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING
RESPIRATORY AILMENTS MAY BE AT INCREASED RISK FROM EXPOSURE TO THE
DUST FROM THIS PRODUCT.

===== First Aid Measures =====

First Aid:SKIN:REMOVE CONTAMINATED CLOTHING;WASH WITH SOAP AND
WATER.EYES:FLUSH WITH WATER FOR 15 MINUTES.INHAL:REMOVE TO FRESH
AIR.GIVE OXYGEN OR ARTIFICIAL RESPIRATION IF N

EEDED.INGEST:GET

PROMPT QUALIFIED MEDICAL ATTENTION. IF CONSCIOUS, INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point Method: COC

Flash Point: 250F, 121C

Extinguishing Media: WATER, CARBON DIOXIDE, DRY CHEMICAL, SAND, FOAM.

Fire Fighting Procedures: USE A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE EQUIPMENT. COOL FIRE EXPOSED CONTAINERS WITH WATER FOG.

Unusual Fire/Explosion Hazard: FIRE CONDITIONS MAY EVOLVE TOXIC FUMES.

=====
===== Accidental Release Measures =====

Spill Release Procedures: LET THE PRODUCT AIR CURE ON AN ABSORBANT. COLLECT AND PLACE IN AN APPROPRIATE CONTAINER FOR DISPOSAL.

Neutralizing Agent: NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions: AVOID MOISTURE DURING STORAGE.

Other Precautions: FOLLOW LABEL DIRECTIONS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN

ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS.

Ventilation: LOCAL VENTILATION AT THE WORKSITE; MECHANICAL (GENERAL) VENTILATION TO MAINTAIN TLV/PEL.

Protective Gloves: DISPOSABLE PLASTIC

Eye Protection: SAFETY GLASSES

Other Protective Equipment: PROTECTIVE CLOTHING, AS NEEDED. PROVIDE A LOCAL EYE WASH STATION AND SAFETY SHOWER.

Work Hygienic Practices: USE REASONABLE CARE IN HANDLING THIS PRODUCT. WASH HANDS AFTER USE AND BEFORE EATING.

Supplement

al Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:N1

Vapor Pres:1

Spec Gravity:1.3

pH: 7

Evaporation Rate & Reference:>1 (N-BUTYL ACETATE=1)

Solubility in Water:SLIGHT

Appearance and Odor:PASTE;SLIGHT MEDICINAL ODOR.COLOR NOT REPORTED.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MOISTURE

Stability Condition to Avoid:HIGH HEAT,SOURCES OF IGNITION.

Hazardous Decomposition Pro

ducts:METHYLETHYLKETOXIME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL,STATE AND LOCAL REGULATIONS.MFR STATES THAT THE CURED PRODUCT CAN BE DISPOSED OF A SYNTHETIC RUBBER SCRAP.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or im

plied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.